

CHECKED JPO

Notes:

All cast iron parts shall be gray iron conforming to the requirements of AASHTO M 105, Class 35B.

Bolts, anchor studs, washers and nuts shall conform to the requirements of ASTM A 307 and shall be galvanized according to AASHTO M 232.

Downspouts located on the exterior side of a painted steel fascia beam shall be painted with the finish coat specified for the exterior side of the fascia beam.


As an alternate, bolts, anchor studs, washers and nuts may be stainless steel according to Article 1006.29(d) of the Standard Specifications.

Structural steel weldments of equal sections and of the same configuration may be substituted for the cast iron scupper frame. Fillet or full penetration welds shall be used for the weldments. Details shall be submitted to the Engineer for approval. Structural steel weldments shall not be substituted for the cast iron scupper grate. Structural steel frames and downspouts shall be galvanized according to AASHTO M111.

The Contractor shall take appropriate measures to assure that Protective Coat is not applied to the scupper.

Cost of the Grate, Frame, Downspout, Anchor Studs, Bolts, Washers and Nuts including complete installation of the scupper shall be paid for at the contract unit price each for Drainage Scupper, DS-11.

Fiberglass pipe conforming to ASTM D 2996 with a short-time rupture strength hoop tensile stress of 30,000 psi min, may be used in lieu of the cast iron or steel equivalent.



ANCHOR STUD DETAIL

BILL OF MATERIAL

ITEM	UNIT	QUANTIT
Drainage Scupper, DS-11	Each	2

DRAINAGE SCUPPER DS-11 STRUCTURE NO. 016-2119



600 WEST FULTON STREET CHICAGO, ILLINOIS

TEL 312 454 9100 WEB www.epsteinglobal.com

SHEET NO. S44 S52 SHEETS

TOTAL SHEET NO. F.A.I. RTE. COUNTY SECTION COOK 110 80 94 1314B-1 CONTRACT NO. 60F65 ILLINOIS FED. AID PROJECT