

DS-11 11-1-09

		DESIGNED	- SP	REVISI	ONS			
		CHECKED	- SP,	NAME	DATE			SHEET NO. 3
T	TYLININTERNATIONAL	DRAWN	- SP					
		CHECKED	- SP,PDF					68 SHEETS
		DATE	- 03/18/10					

Notes:

All cast iron parts shall be gray iron conforming to the requirements of AASHTO M 105, Class 35B.

Bolts, anchor studs, washers and nuts shall conform to the requirements of ASTM A 307 and shall be galvanized according to AASHTO M 232.

Downspouts located on the exterior side of a painted steel fascia beam shall be painted with the finish coat specified for the exterior side of the fascia beam.

As an alternate, bolts, anchor studs, washers and nuts may be stainless steel according to Article 1006.29(d) of the Standard Specifications.

Structural steel weldments of equal sections and of the same configuration may be substituted for the cast iron scupper frame. Fillet or full penetration welds shall be used for the weldments. Details shall be submitted to the Engineer for approval. Structural steel weldments shall not be substituted for the cast iron scupper grate. Structural steel frames and downspouts shall be galvanized according to AASHTO MIII.

The Contractor shall take appropriate measures to assure that Protective Coat is not applied to the scupper.

Cost of the Grate, Frame, Downspout, Anchor Studs, Bolts, Washers and Nuts including complete installation of the scupper shall be paid for at the contract unit price each for Drainage Scupper, DS-11.

Alternate fiberglass downspout conforming to ASTM D 2996 with a short-time rupture strength hoop tensile stress of 30,000 psi min. may be used in lieu of the cast iron or steel equivalent.



682540(57-294)\STRUCTURAL\1-57 OVER 1294\0161251-60J27-03

ANCHOR STUD DETAIL

BILL OF MATERIAL

ITEM	UNIT	QUANTITY
Drainage Scupper, DS-11	Each	18

DRAINAGE SCUPPER DS-11 STRUCTURE NO. 016-1251

	F.A.T			~ ~				1		TOTAL		SHEET	0
. 37	RTE.	RTE. SECTION							COUNTY	SHEETS		NO.	201
	57			1	414	1.2B			COOK	516		282	17/
S									CONTRACT	NO.	60)J27	6
	FED. ROAD DIST. NO. 1 ILLINOIS FED. AID PROJECT												