## INDEX OF SHEETS

SHEET NO.	DESCRIPTION							
1	COVER SHEET							
2	INDEX OF SHEETS, STATE STANDARDS, AND GENERAL NOTES							
3 2 2	SUMMARY OF QUANTITIES							
4 2	TYPICAL SECTIONS							
5-10	ROADWAY AND PAVEMENT MARKING PLANS							
11-16	DETECTOR LOOP REPLACEMENT PLANS							
17	DETAILS FOR FRAMES AND LIDS ADJUSTMENTS WITH MILLING							
18	PAVEMENT PATCHING FOR HMA SURFACED PAVEMENT							
19	CURB OR CURB AND GUTTER REMOVAL AND REPLACEMENT							
20	BUTT JOINT AND HMA TAPER DETAILS							
21	TRAFFIC CONTROL AND PROTECTION FOR SIDEROADS, INTERSECTIONS, AND DRIVEWAYS							
22	TYPICAL APPLICATION FOR RAISED REFLECTIVE PAVEMENT MARKERS							
23	DISTRICT ONE TYPICAL PAVEMENT MARKINGS							
24	TRAFFIC CONTROL AND PROTECTION AT TURN BAYS							
25	PAVEMENT MARKING LETTERS AND SYMBOLS FOR TRAFFIC STAGING							
26	ARTERIAL ROAD INFORMATION SIGN							
27	DISTRICT ONE DETECTOR LOOP INSTALLATION DETAIL FOR ROADWAY RESURFACING							

## STATE STANDARDS

000001- <i>05</i>	STANDARD SYMBOLS, ABBREVIATIONS AND PATTERNS	
442201 <b>-03</b>	CLASS C AND D PATCHES	w sage
604001- <i>0</i> <b>3</b>	FRAME AND LIDS, TYPE 1	
606001- <i>04</i>	CONCRETE CURB TYPE B AND COMBINATION CONCRETE CURB AND GUTTER	
701301- <i>0</i> <b>3</b>	LANE CLOSURE, 2L, 2W, SHORT TIME OPERATIONS	
701606 <i>-0</i> 6	URBAN LANE CLOSURE, MULTILANE 2W WITH MOUNTABLE	MEDIAN
701701-00	URBAN LANE CLOSURE, MULTILANE INTERSECTION	
701901-01	TRAFFIC CONTROL DEVICES	

## GENERAL NOTES

BEFORE STARTING ANY EXCAVATION, THE CONTRACTOR SHALL CALL "JULIE" AT 800-892-0123 FOR FIELD LOCATIONS OF BURIED ELECTRIC, TELEPHONE AND GAS FACILITIES. (48 HOURS NOTIFICATION REQUIRED).

10 FEET (3 METER) TRANSITIONS SHALL BE USED TO MATCH PROPOSED CURB AND GUTTER AND MEDIAN ITEMS OF WORK TO EXISTING CURB AND GUTTERS AND MEDIANS IN THE FIELD, UNLESS OTHERWISE SHOWN. THE TRANSITIONS SHALL BE PAID FOR AT THE CONTRACT UNIT PRICE FOR THE PROPOSED ITEMS OF WORK SPECIFIED.

THE CONTRACTOR SHALL COORDINATE CONSTRUCTION ACTIVITIES WITH UTILITY COMPANIES AND THE VILLAGES OF HINSDALE, WESTERN SPRINGS AND LA GRANGE.

THE CONTRACTOR WILL NOT BE ALLOWED TO SET UP A YARD OR FIELD OFFICE ON STATE PROPERTY WITHOUT WRITTEN PERMISSION FROM THE DEPARTMENT.

WHEN MILLED PAVEMENT IS OPEN TO TRAFFIC, THE MAXIMUM GRADE DIFFERENTIAL BETWEEN PASSES OF THE MILLING MACHINE SHALL NOT EXCEED 1½ INCHES (40 MM) WHERE THE SPEED LIMIT IS 45 MPH (80 KM/H) OR LESS AND 1 INCH (25 MM) WHERE THE SPEED LIMIT IS GREATER THAN 45 MPH (80 KM/H). WITH WRITTEN APPROVAL FROM THE ENGINEER, A MAXIMUM GRADE DIFFERENTIAL OF 3 INCHES (75 MM) MAY BE ALLOWED IF THE EDGE OF THE MILLING IS SLOPED A MINIMUM 1:3 (V:H).

BUTT JOINTS WILL BE INSTALLED AT THE ENDS OF ALL RESURFACING (WHERE RESURFACING MEETS EXISTING PAVEMENT), IN ACCORDANCE WITH THE "BUTT JOINT AND HMA TAPER DETAILS" SHEET INCLUDED IN THE PLANS, UNLESS OTHERWISE SPECIFIED.

THE RESIDENT ENGINEER SHALL CONTACT MS. PATRICE HARRIS, AREA TRAFFIC FIELD ENGINEER AT (708) 597-9800 A MINIMUM OF 2 WEEKS PRIOR TO PLACEMENT OF PERMANENT PAVEMENT MARKING.

THE RESIDENT ENGINEER SHALL CONTACT THE TRAFFIC CONTROL SUPERVISOR AT (847) 705-4470 A MININMUM OF 72 HOURS PRIOR TO THE PLACEMENT OF TEMPORARY TRAFFIC CONTROL DEVICES.

THE RESIDENT ENGINEER SHALL DETERMINE THE LOCATIONS OF CLASS "D" PATCHES, CURB AND GUTTER REMOVAL AND REPLACEMENT.

FILE NAME =	USER NAME = shiranisb	DESIGNED	-	REVISED	-	
c:\pw_work\PWIDOT\SHIRANISB\d0143230\D17	6709-sht-plan.dgn	DRAWN	-	REVISED	-	
PLDT SCALE = 50.0000 '/ IN.		CHECKED		REVISED	•	
	PLOT DATE = 6/27/2009	DATE		REVISED	-	
		<u> </u>				

STATI	E OI	F ILLINOIS
DEPARTMENT	OF	TRANSPORTATION

INDEX OF S	HEETS, LIS	T OF STATE	STANDARDS	, PLAN NOTES
47TH STRE	EET / DUP	AGE COUNT	LINE TO	EAST AVE.
SCALE:	SHEET NO.	OF SHEETS	STA.	TO STA.

_	F.A.U. SECTION							T	COUNTY	TOTAL	SHEE NO.
	1488			32	12	RS-3			COOK	27	2
								1	CONTRACT	NO.	50H69
	FED. R	OAD	DIST.	NO.	1	ILLINOIS	FEO.	AID	PROJECT		