INDEX OF SHEETS

SHEET NO	DESCRIPTION
1	COVER SHEET
2	INDEX OF SHEETS, STATE STANDARDS AND GENERAL NOTES
3	SUMMARY OF QUANTITIES
4	TYPICAL SECTIONS
5-7	PROPOSED ROADWAY AND PAVEMENT MARKING PLAN
8	DETAILS FOR FRAMES AND LIDS ADJUSTMENT WITH MILLING (BD-8)
9	CITY OF CHICAGO DETAILS FOR P.C. CONCRETE DRIVEWAY,
	ALLEY RETURN AND SIDEWALK (BD-17)
10	PAVEMENT PATCHING FOR HMA SURFACED PAVEMENT (BD-22)
11	CURB AND GUTTER REMOVAL AND REPLACEMENT (BD-24)
12	BUTT JOINT AND HMA TAPER DETAILS (BD-32)
13	TRAFFIC CONTROL AND PROTECTION FOR SIDE ROADS,
	INTERSECTIONS, AND DRIVEWAYS (TC-10)
14	TRAFFIC CONTROL AND PROTECTION AT TURN BAYS
	(TO REMAIN OPEN TO TRAFFIC) (TC-14)
14A	PAVEMENT MARKING LETTERS AND SYMBOLS FOR TRAFFIC STAGING (TC-16
15	ARTERIAL ROAD INFORMATION SIGN (TC-22)
16-17	CITY OF CHICAGO TYPICAL PAVEMENT MARKINGS (TC-24)

STATE STANDARDS

STATE STA	<u>NDARDS</u>				
000001 <i>-05</i>	STANDARD SYMBOLS, ABBREVIATIONS, AND PATTERNS				
442201- <i>03</i>	CLASS C AND D PATCHES				
602401 <i>-0</i> 2	MANHOLE TYPE A				
602601 -02	PRECAST REINFORCED CONCRETE FLAT SLAB TOP				
604001- <i>03</i>	FRAME AND LIDS, TYPE 1				
642001- <i>01</i>	CONCRETE CURB TYPE B AND COMBINATION CONCRETE CURB AND GUTTER				
701501- <i>05</i>	URBAN LANE CLOSURE, 2L, 2W, UNDIVIDED				
701601- <i>00</i>	URBAN LANE CLOSURE, MULTILANE, 1W OR 2W WITH NONTRAVERSABLE MEDIAN				
701606 -<i>06</i>	URBAN LANE CLOSURE, MULTILANE, 2W WITH MOUNTABLE MEDIAN				
701701- <i>06</i>	URBAN LANE CLOSURE, MULTI LANE INTERSECTION				
701801- <i>04</i>	LANE CLOSURE MULTILANE 1W, 2W, CROSSWALK OR SIDEWALK CLOSURE				
701901 -0/	TRAFFIC CONTROL DEVICES				
780001- 02	TYPICAL PAVEMENT MARKINGS				

GENERAL NOTES

- BEFORE STARTING ANY EXCAVATION, THE CONTRACTOR SHALL CALL "JULIE" AT 800-892-0123 OR 811 FOR FIELD LOCATIONS OF BURIED ELECTRIC, TELEPHONE, AND GAS FACILITIES. (48 HOUR NOTIFICATION IS REQUIRED)
- 2. 10 FEET (3 METER) TRANSITIONS SHALL BE USED TO MATCH PROPOSED CURB AND GUTTER AND MEDIAN ITEMS OF WORK TO EXISTING CURB AND GUTTER AND MEDIANS IN THE FIELD UNLESS OTHERWISE SHOWN. THE TRANSITIONS SHALL BE PAID FOR AT THE CONTRACT UNIT PRICE FOR THE PROPOSED ITEMS OF WORK SPECIFIED.
- 3. THE CONTRACTOR SHALL COORDINATE CONSTRUCTION ACTIVITIES WITH UTILITY COMPANIES.
- 4. THE CONTRACTOR WILL NOT BE ALLOWED TO SET UP A YARD OR FIELD OFFICE ON STATE PROPERTY WITHOUT WRITTEN PERMISSION FROM THE DEPARTMENT.
- 5. WHEN ARTIFICIAL LIGHTING IS USED IN NIGHT OPERATIONS THE CONTRACTOR SHALL EXERCISE THE UTMOST PRECAUTIONS IN PREVENTING ADVERSE VISIBILITY TO THE MOTORING PUBLIC AND ADJOINING RESIDENTIAL AREAS.
- 6. THE FOLLOWING RATES OF APPLICATION HAVE BEEN ASSUMED IN CALCULATING PLAN QUANTITIES;

BITUMINOUS MATERIALS (PRIME COAT)

0.0004 TONS/SQ YD

- 7. THE ENGINEER SHALL CONTACT THE TRAFFIC CONTROL SUPERVISORS AT (847) 705-4470 A MINIMUM OF 72 HOURS PRIOR TO THE START OF WORK.
- 8. TWO WEEKS PRIOR TO PLACEMENT OF PERMANENT PAVEMENT MARKINGS THE RESIDENT ENGINEER SHALL CONTACT PATRICE HARRIS, AREA TRAFFIC FIELD TECHNICIAN, AT (773) 597-9800.
- 9. WHEN MILLED PAVEMENT IS OPEN TO TRAFFIC THE MAXIMUM GRADE DIFFERENTIAL BETWEEN PASSES OF THE MILLING MACHINE SHALL NOT EXCEED 1 1/2" (40 MM) WHERE THE SPEED LIMIT IS 45 MPH (80 KM/H) OR LESS AND 1" (25 MM) WHERE THE SPEED LIMIT IS GREATER THAN 45 MPH (80 KM/H). WITH WRITTEN APPROVAL FROM THE ENGINEER, A MAXIMUM GRADE DIFFERENTIAL OF 3" (75 MM) MAY BE ALLOWED IF THE EDGE OF THE MILLING IS SLOPED A MINIMUM 3:1 (H:V).
- 10. BUTT JOINTS WILL BE INSTALLED AT THE END OF ALL RESURFACING (WHERE RESURFACING MEETS EXISTING PAVEMENT). IN ACCORDANCE WITH THE "BUTT JOINT AND HMA TAPER DETAILS" SHEET INCLUDED IN THE PLANS, UNLESS OTHERWISE SPECIFIED.
- 11. FOR PAVEMENT MARKING, REFER TO CITY OF CHICAGO TYPICAL MARKINGS FOR DETAILS SHOWN.
- 12. MATCH EXISTING PAVEMENT MARKINGS AT PROJECT LIMITS.
- 13. ALL PATCHES OPENED ON A PARTICULAR DAY MUST BE FILLED THAT DAY TO THE PAVED SURFACE

- 14. CONTINGENCY QUANTITIES HAVE BEEN INCLUDED FOR THE FOLLOWING ITEMS TO BE USED AT THE DIRECTION OF THE ENGINEER:
 - 60406000 FRAMES AND LIDS, TYPE 1, OPEN LID 15 EACH 60406100 FRAMES AND LIDS, TYPE 1, CLOSED LID 15 EACH
- 15. NO OVERNIGHT LANE CLOSURES SHALL BE ALLOWED.

USER NAME = wlancaster	DESIGNED	-	MWR	REVISED -
	DRAWN	-	MWR	REVISED -
PLOT SCALE = 1.0000 '/ IN.	CHECKED	-	SNS	REVISED -
PLOT DATE = 7/17/2009	DATE	-	6/24/2009	REVISED -