

SYMBOLS

- PORTABLE CHANGEABLE MESSAGE SIGN
- Þ SIGN
- $\boldsymbol{\Phi}$ Type II Barricade, drum, or vertical barricade with monodirectional flashing light

- THE ROAD CONSTRUCTION AHEAD SIGN SHALL BE LOCATED 3 TO 5 MILES IN ADVANCE OF THE PROJECT LIMITS.
- ② THE MESSAGE AND SIZE OF THE WORK ZONE PUBLIC INFORMATION SIGN SHALL BE AS SPECIFIED BY THE DEPARTMENT.
- THE MESSAGE BOARD SHALL BE USED TO DISPLAY STATUS OF LANES WITHIN THE PROJECT. THE PRIMARY MESSAGES SHALL BE:

 "RIGHT LANE CLOSED" / " X MILES AHEAD"

 "LEFT LANE CLOSED" / " X MILES AHEAD"
- THREE, TYPE II BARRICADES, DRUMS, OR VERTICAL BARRICADES AT 50' CENTERS.



FILE NAME =	USER NAME = gelinh	DESIGNED	REVISED			F.A.I. SECTI	ON COUN	TY TOTAL	SHEET
c:\pw_work\PWIDOT\GELINH\d0120465\D876C	95-sht-staging.dgm	DRAWN	REVISED	STATE OF ILLINOIS	TRAFFIC CONTROL & PROTECTION PLAN	270 60-2HB-I-		JIILLIJ	NO.
	PLOT SCALE = 50.00000 '/ IN.	CHECKED	REVISED	DEPARTMENT OF TRANSPORTATION		210 60-200-1-		CONTRACT NO. 76	4
	PLOT DATE = 6/23/2009	DATE	REVISED		SCALE: 1' = 50" SHEET NO OF SHEETS STA. 249+00.00 TO STA	ILLINOIS FED. AID PROJEC			