### STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION

10" O.D.

6" I.D.

6" I.D.

7" O.D.

**DOWNSPOUT** 


914"


SECTION B-B

# CONTRACT NO. 83827

ROUTE NO.	SECTION	COUNTY		TOTAL SHEETS	SHEET NO.	SHEET NO. 514
	*	DUPAGE		106	35	of S34 SHEETS
PER BOAR DIET NO 7		1) I TAINTO	EED ATO BE	recy-		


\* 00-00116-00-BR






BOLT HOLE DETAIL


## ANCHOR STUD DETAIL



9<sub>16</sub> " ♦ holes on an

834" \$ bolt circle





VIEW C-C

All cast iron parts shall be gray iron conforming to the requirements of AASHTO M 105, Class 35B.

Bolts, anchor studs, washers and nuts shall conform to the requirements of ASTM A 307 and shall be galvanized according to AASHTO M 232.

Downspouts located on the exterior side of a painted steel fascia beam shall be painted with the finish coat specified for the exterior side of the fascia beam.

As an alternate, bolts, anchor studs, washers and nuts may be stainless steel according to Article 1006.29(d) of the Standard Specifications.

Structural steel weldments of equal sections and of the same configuration may be substituted for the cast iron scupper frame. Fillet or full penetration welds shall be used for the weldments. Details shall be submitted to the Engineer for approval. Structural steel weldments shall not be substituted for the cast iron scupper grate. Structural steel frames and downspouts shall be galvanized according to AASHTO M111.

The Contractor shall take appropriate measures to assure that Protective Coat is not applied to the scupper.

Cost of the Grate, Frame, Downspout, Anchor Studs, Bolts, Washers and Nuts including complete installation of the scupper shall be paid for at the contract unit price each for Drainage Scupper, DS-12.


Alternate fiberglass downspout conforming to ASTM D 2996 with a short-time rupture strength hoop tensile stress of 30,000 psi min. may be used in lieu of the cast iron or steel eauivalent.


## BILL OF MATERIAL

ITEM	UNIT	QUANTITY
Drainage Scupper, DS-12	Each	6

DRAINAGE SCUPPER. DS-12

JEFFERSON AVENUE OVER WEST BRANCH DUPAGE RIVER FAU 3570 SECTION 00-00116-00-BR DUPAGE COUNTY STA. 7+64.45 STRUCTURE NUMBER 022-6756





See sheet 11 of 34 for scupper location relative to parapet.

GM
SRT