CONTRACT *: 83894

S-13 SHEETS

—The diameter of this part is equal or larger than the The diameter of this part diameter of bar spliced. is the same as the diameter of the bar spliced.

ROLLED THREAD DOWEL BAR


** ONE PIECE Wire Connector

William

WELDED SECTIONS


BAR SPLICER ASSEMBLY ALTERNATIVES

** Heavy Hex Nuts conforming to ASTM A 563, Grade C, D or DH may be used.




FOR INTEGRAL OR SEMI-INTEGRAL ABUTMENTS

Bar Splicer for #5 bar Min. Capacity = 23.0 kips - tension Min. Pull-out Strength = 9.2 kips - tension No. Required = 80



INSTALLATION AND SETTING METHODS

"A": Set bar splicer assembly by means of a template bolt. "B" : Set bar splicer assembly by nailing to wood forms or cementing to steel forms. (E): Indicates epoxy coating.



FOR PILE BENT ABUTMENTS

Bar Splicer for #5 bar Min. Capacity = 23.0 kips - tension Min. Pull-out Strength = 9.2 kips - tension No. Required =

NOTES

Bar splicer assemblies shall be of an approved type and shall develop in tension at least 125 percent of the yield strength of the lapped reinforcement bars.

Splicer rods shall be of minimum 60 ksi yield strength, threaded or coiled full length. All reinforcement bars shall be lapped and tied to the splicer rods or dowel bars.

Bar splicer assemblies shall be epoxy coated according to the requirements for reinforcement bars.

Other systems of similar design may be submitted to the Engineer for approval. Approval shall be based on certified test results from an approved testing laboratory that the proposed bar splicer assembly satisfies the following requirements:

Minimum Capacity (Tension in kips) = $1.25 \times fy \times A_t$

(Tension III kips)
Minimum *Pull-out Strength = 1.25 x fs_{allow} x A_t (Tension in kips)


Where fy = Yield strength of lapped reinforcement bars in ksi.

 fs_{allow} = Allowable tensile stress in lapped reinforcement bars in ksi (Service Load)

 A_t = Tensile stress area of lapped reinforcement bars. * = 28 day concrete

BAR SPLICER ASSEMBLIES					
Bar Size to be Spliced	Splicer Rod or Dowel Bar Length	Strength Requirements			
		Min. Capacity kips - tension	Min. Pull-Out Strength kips - tension		
#4	1'-8''	14.7	5.9		
#5	2'-0"	23.0	9.2		
#6	2'-7''	33.1	13.3		
#7	3′-5′′	45.1	18.0		
#8	4'-6''	58.9	23.6		
#9	5′-9′′	75.0	30.0		
#10	7′-3′′	95.0	38.0		
#11	9′-0′′	117.4	46.8		

Bar splicer assemblies shall be according to Section 508 of the Standard Specifications, except as noted. The furnishing and installation of bar splicer assemblies will be measured and paid for at the contract unit price each for "BAR SPLICERS."



STANDARD

Bar Size	No. Assemblies Required	Location

EC GROUP, INC.

420 N. Front Street, McHenry, IL 60050 t. 815.385.1778 f. 815.385.1781

DESIGNED KMA CHECKED AEU DRAWN WJH CHECKED RGD WILL COUNTY DEPARTMENT OF HIGHWAYS

BAR SPLICER ASSMEBLY DETAILS CEDAR ROAD OVER JACKSON CREEK WILL COUNTY SECTION NO. 01-00056-15-BR STRUCTURE NO. 099-3381

DATE 4-10-2009