
SUB-BASE GRANULAR MATERIAL, TYPE A 4"
BRIDGE APPROACH PAVEMENT
(SEE STANDARD 420401)

BRIDGE APPROACH CONNECTOR (FLEXIBLE):
HOT-MIX ASPHALT SURFACE COURSE, MIX "D", N70 (IL-9.5), 2"
HOT-MIX ASPHALT BINDER COURSE, IL 19.0 mm, N70, 10" TO 13" (IN 4 LIFTS)

ROADWAY RESURFACING:
HOT-MIX ASPHALT SURFACE COURSE, MIX "D", N70 (IL-9.5), 1 1/2"
LEVELING BINDER (MACHINE METHOD), N70, 3/4" MIN.



SCALE: 1"=50"

NOTES:

1. EARTH EXCAVATION QUATITIES HAVE BEEN INCLUDED FOR THE FOLLOWING LOCATIONS:

FOR BRIDGE APPROACH PAVEMENT AND BRIDGE APPROACH CONNECTOR (FLEXIBLE)

140 CU YD

FOR AGGREGATE SHOULDERS, TYPE B

55 CU YĎ

2. SEE SHEET NO. 16 FOR PROFILE GRADE



USER NAME = jcoleman	DESIGNED	-	JCC	REVISED -	
	DRAWN	-	acc	REVISED -	
PLOT SCALE = 50.0000 '/ IN.	CHECKED	-	MJL	REVISED -	
PLOT DATE = 7/8/2008	DATE	-	07/09/2008	REVISED -	

STATE	OF	ILLINOIS	
DEPARTMENT	OF	TRANSPORTATION	

TERMINAL, TYPE 6A

FAS 1317 / ILLINOIS ROUTE 113						RTE.	SEC
-			TERRY			1317	111
	KUP	12FI	ROAD	WAY	PLAN		
SHEET	NO.	0F	SHEETS	STA.	TO STA.	FED. ROAD	D DIST. NO.

.