

CONTRACT NO. 94533 TOTAL SHEET SECTION COUNTY RTE. SHEETS NO. 781 1YRS, 2ZRS-1 CRAWFORD 378 171 STA. TO STA. FED. ROAD DIST. NO. ILLINOIS FED. AID PROJECT



BUTT JOINT DETAIL



MILLED TEMPORARY RAMP

NOTES

- 1. REFER TO THE HOT-MIX ASPHALT SURFACE REMOVAL DETAILS BELOW AND THE HOT-MIX ASPHALT SURFACE REMOVAL SCHEDULE FOR MILLING THICKNESSES.
- 2. BUTT JOINTS AND TEMPORARY RAMPS SHALL BE PLACED AS SHOWN ON THE PLANS OR AS DIRECTED BY THE ENGINEER.
- 3. BUTT JOINTS SHALL BE CONSTRUCTED IMMEDIATELY PRIOR TO THE PLACING OF THE PROPOSED HOT-MIX ASPHALT COURSES.
- 4. TAPER THE TEMPORARY RAMP AT A RATE OF 900mm (3') PER 25mm (1") OF MILLING THICKNESS.
- 5. TEMPORARY RAMPS SHALL BE CONSTRUCTED AT ALL BUTT JOINT LOCATIONS. AT ALL OTHER PAVEMENT TRANSITIONS THE MILLED TEMPORARY RAMP SHALL BE USED. THE INSTALLATION AND SUBSEQUENT REMOVAL OF THE TEMPORARY RAMP WILL BE PAID FOR AT THE CONTRACT UNIT PRICE PER SQUARE METER FOR TEMPORARY RAMP. MILLED TEMPORARY RAMPS WILL NOT BE PAID FOR SEPARATELY, BUT SHALL BE INCLUDED IN THE COST OF HOT-MIX ASPHALT SURFACE REMOVAL.

- 1. REFER TO THE HOT-MIX ASPHALT SURFACE REMOVAL SCHEDULE FOR MILLING THICKNESSES AT & AND LOCATIONS WHERE EACH OCCURS.
- 2. MILLING SHALL BE DONE AT THE NOMINAL THICKNESS CALLED FOR AT ¢ ACROSS THE SECTION.
- 3. MILLING TO THE BOTTOM OF WHEEL RUTS SHALL NOT BE NECESSARY UNLESS REQUIRED TO OBTAIN SLOPE OR THE DESIGN DEPTH AT
- 4. NOMINAL MILLING AREAS SHALL BE PAID FOR UNDER THE FOLLOWING: M4400715 - HOT-MIX ASPHALT SURFACE REMOVAL, 15mm M4400725 - HOT-MIX ASPHALT SURFACE REMOVAL, 25mm M4400740 - HOT-MIX ASPHALT SURFACE REMOVAL, 40mm


¢ FAP 781 (IL. 33) MILL ENTIRE SECTION AT THE SAME DEPTH CALLED FOR AT ¢ DESIGN DEPTH AT PROPOSED & SEE NOTE 1. EXIST. BITUMINOUS EXIST. PCC BASE

HOT-MIX ASPHALT SURFACE REMOVAL DETAIL (NOMINAL DEPTH)

- 1. REFER TO THE HOT-MIX ASPHALT SURFACE REMOVAL SCHEDULE FOR MILLING THICKNESSES AT & AND LOCATIONS WHERE EACH OCCURS.
- 2. MILLING SHALL BE DONE TO ATTAIN THE DESIRED DESIGN CROSSLOPE ACROSS THE SECTION.
- 3. MILLING TO THE BOTTOM OF WHEEL RUTS SHALL NOT BE NECESSARY UNLESS REQUIRED TO OBTAIN SLOPE OR THE DESIGN DEPTH AT

PEVISIONS

4. VARIABLE MILLING AREAS SHALL BE PAID FOR UNDER THE FOLLOWING: M4400950 - HOT-MIX ASPHALT SURFACE REMOVAL, VARIABLE DEPTH



HOT-MIX ASPHALT SURFACE REMOVAL DETAIL (VARIABLE DEPTH)

ALL DIMENSIONS ARE IN MILLIMETERS UNLESS OTHERWISE SHOWN.

1151010			
NAME	DATE	ILLINOIS DEPART	IMENT OF TRANSPORTATION
		DUTT IO	INT, TAPER AND
		ASPHAL I	MILLING DETAILS
		SCALE NO SCALE	DRAWN BY KO.I

DATE APRIL 18, 2008

HENRY, MEISENHEIMER & GENDE, INC., 1075 LAKE RD., P.O. BOX 70, CARLYLE, ILLINOIS 62231 (618)-594-3711 WWW.HMGENGINEERS.COM

CHECKED BY RGH