



NOTES:


- ALL DIMENSIONS ARE IN INCHES (MILLIMETERS) UNLESS OTHERWISE SHOWN.
- 2. TWO PIECE SHAFT WILL BE MATCHED MARKED AND INTERCHANGEABLE BETWEEN DIFFERENT UNITS. FIELD DRILLING OF THE HOLES WILL NOT BE ALLOWED.
- 3. THE POLE WILL MEET AASHTO DESIGN CRITERIA AS SPECIFIED.
- 4. THE INSTALLING CONTRACTOR WILL PROVIDE A UL LISTED GROUNDING CONNECTOR. BURNDY K2C23, T&B SP4DL OR APPROVED EQUAL.
- 5. POLES WILL BE INSTALLED IN ACCORDANCE TO MANUFACTURER'S INSTRUCTIONS.
- 6. POLES WILL BE SET PLUMB ON THE FOUNDATION WITHOUT THE USE OF LEVELING NUTS, WASHERS OR SHIMS.





POLE BASE PLATE DETAIL

15 INCH (381.0) BOLT CIRCLE



SCALE: NONE

FILE NAME =	USER NAME = bauerdl	DESIGNED -	REVISED	-	R.	TOMSONS	09-06-00	Γ
:\pw_work\pwidot\bauerd1\d0108315\be100 9. dgn		DRAWN -	REVISED	-	R.	TOMSONS	09-03-03	
	PLOT SCALE = 50.000 '/ in.	CHECKED -	REVISED	-	R.	TOMSONS	02-27-13	l
1	PLOT DATE = 2/27/2013	DATE -	REVISED	=				1

STATE OF	ILLINOIS
DEPARTMENT OF	TRANSPORTATION

CCTV CAMERA STRUCTURE 50' (15.24 m) MOUNTING HEIGHT					F.A RTE.	SECTION	COUNTY TOTAL SHEET NO.			
								177	50L	
						BE-1000	CONTRACT NO.			
	SHEET NO. 1	OF 1	SHEETS	STA.	TO STA.	FED. ROAD DIST. NO. 1 ILLINOIS FED. AID PROJECT				