



Illinois Department of Transportation

2300 South Dirksen Parkway / Springfield, Illinois / 62764

September 10, 2019

SUBJECT: FAI Route 155 (I-155)
Project NHPP-FBYL(491)
Section 90-106X[VB-1,HB-2]BJR,BRR
Tazewell County
Contract No. 68E27
Item No. 33, September 20, 2019 Letting
Addendum B

NOTICE TO PROSPECTIVE BIDDERS:

Attached is an addendum to the plans or proposal. This addendum involves revised and/or added material.

1. Revised page ii to the Table of Contents to the Special Provisions.
2. Added page 110 to the Special Provisions.

Prime contractors must utilize the enclosed material when preparing their bid and must include any changes to the Schedule of Prices in their bid.

Very truly yours,

A handwritten signature in black ink, appearing to read 'Jack A. Elston'.

Jack A. Elston, P.E.
Bureau Chief, Design and Environment

PORTLAND CEMENT CONCRETE (BDE)	88
PORTLAND CEMENT CONCRETE BRIDGE DECK CURING (BDE).....	88
PROGRESS PAYMENTS (BDE).....	90
REMOVAL AND DISPOSAL OF REGULATED SUBSTANCES (BDE)	91
SPEED DISPLAY TRAILER (BDE)	101
STEEL COST ADJUSTMENT (BDE).....	102
SUBCONTRACTOR AND DBE PAYMENT REPORTING (BDE)	105
SUBCONTRACTOR MOBILIZATION PAYMENTS (BDE).....	106
TEMPORARY PAVEMENT MARKING (BDE).....	106
TRAFFIC CONTROL DEVICES - CONES (BDE).....	108
WEEKLY DBE TRUCKING REPORTS (BDE).....	109
WORKING DAYS (BDE).....	109
SURFACE FILLER, SPECIAL (GALLON)	110

SURFACE FILLER, SPECIAL (GALLON)

Effective April 23, 2010

This work shall consist of filling cracks over 1/32" and other surface defects such as popouts with a gun-grade elastomeric sealant prior to overcoating with "Protective Coat, Special".

Material. The material shall be a 1-component, polyurethane-based, non-sag elastomeric sealant that meets ASTM C-920, Type S, Grade NS, Class 100/50, use T, NT, G, M.

The surface filler material shall be as recommended by the Manufacturer for the "Protective Coat, Special" and shall be compatible with the protective coating applied to the concrete parapet as specified in the Special Provision for "Protective Coat, Special".

Construction. All cracks and surface defects to be repaired shall be sound, dry, and clean of any foreign material. Preparation, filling, and tooling shall be according to the Manufacturer's specifications. Curing time shall be as recommended by the manufacturer, but a minimum of one day cure time shall be allowed prior to overcoating with "Protective Coat, Special".

A manufacturer's technical representative shall be present on the first day of surface filling operations to ensure correct interpretation of the Manufacturer's specifications.

Method Measurement. The surface filler will be measured for payment in Gallons used in place to the nearest 0.1 Gallon.

Basis of Payment. The surface filler will be paid for at the contract unit price per Gallons for SURFACE FILLER, SPECIAL (GALLON), which price shall include the furnishing of all materials, crack and surface defect preparation, and the application of the surface filler as specified.