

F.A.P.	SECTION	COUNT	Y	TOTAL SHEETS	SHEET NO.
666	SP-Z. RS-4	SANGA	80	78	
STA.		TO STA.			
FED. ROA	D DIST, NO. IL	LINOIS FED.	AID	PROJECT	





INSTALLING THE LOOP WIRE:
THE NEGATIVE LEAD SHALL BE CONNECTED TO THE BLACK CONDUCTOR
OF A PAIR OF CONDUCTORS IN THE LEAD-IN CABLE AND THE POSITIVE
LEAD SHALL BE CONNECTED TO THE COLOR-CODED CONDUCTOR OF
THE CABLE PAIR.

DETECTOR LOOP WIRE INSTALLATION

DETECTOR NOTES:

- THE DETECTOR LOOP SHALL BE CENTERED IN THE LANE IN WHICH IT IS SHOWN. ANY ADJUSTMENTS ARE TO BE MADE ONLY AT THE DIRECTION OF THE ENGINEER.
- 2. THE DETECTOR LOOPS SHALL CONSIST OF THE NUMBER OF TURNS AS SHOWN IN THE PLANS OR AS DIRECTED BY THE ENGINEER.
- 3. ACCEPTANCE OF THE LOOPS AS METERED SHALL BE DETERMINED BY THE ENGINEER.
- 4.ALL DETECTOR WIRES SHALL BE MARKED WITH WATERPROOF LABELS USING THE WIRING IDENTIFICATION SHOWN ON THE PLANS. THE + AND OF EACH LOOP MUST BE USED TO IDENTIFY CURRENT FLOW. ALWAYS CONNECT THE BLACK WIRE OF EACH PAIR TO THE NEGATIVE (-) LOOP WIRE.
- 5. ALL QUADRAPOLE LOOPS SHALL BE 2-4-2 DESIGN.
- 6. THE CONTRACTOR SHALL CONTACT DISTRICT 6 OPERATIONS FOR ASSISTANCE IN DETECTOR LOOP LAYOUT AT LEAST 48 HOURS BEFORE INSTALLING DETECTOR LOOPS (Ph. * 217-558-6523)

REVISIONS		THE WOLC DEPART	MENT OF TRANSPORTATION
NAME	DATE	ILLINUIS DEPARTI	MENT OF TRANSPORTATION
***************************************		TRAFFIC	SIGNAL DETAILS
····		,	
			(I-55 BUS/9TH STREET)
		DETECTO	OR LOOP DETAILS
***************************************		ON F VERT.	
	+	SCALE: HORIZ.	DRAWN BY
		DATE	CHECKED BY

			1.22		ļ	┿	710	1,50		
					ļ	+-	ļ	 	 	
NINTH/ENOS NLF NRF NLE NRE SRF						4	Į	 		<u> </u>
NINTHZENOS						1				<u> </u>
NLF	4	144	0.41			1.	177	5.44	1	
NRF	4	141	0.35			Т	175	5.37	1	T
NIF	4	144	0.41			†	166	3.77		1
NRF	4	141	0.41 0.35 0.41 0.35 0.31 0.36			+	164	5.44 5.37 3.77 3.71 4.80	1	
SPE	4	139	0.33		 	+-	164 170 172	4 90		
SLF SLF	4	142	0.30		 	╁	170	4.00	 	
	·	142	0.36			+-	112	4.86 3.21		
<u> </u>	4	142	0.36			L	161	3.21		
SRE	4	139	0.31			L	158	3.15		
EAP	2-4-2	314	0.91			Г	318	1.51		
SLE SRE EAP WAP	2-4-2 2-4-2	298	0.86			Т	318 317	1.51 3.61		
						1	T			
	***************************************	····				+-	 		 	
MINTH / IECEEDEN	ıkı			 	 	┿	 	 	 	+
NINTH/JEFFERSO SLT	2-4-2	400	1.05		ļ	٠	407	1.27	 	
3L1	2-4-2	406	1,25		ļ	4-	407	1.37		ļ
		<u> </u>				1	ļ		<u> </u>	ļ
					L	L	<u> </u>			
NINTH/MADISON NLT		1			İ	1	Į.		ľ	
NLT	2-4-2	408	1.29			Т	409	1.46		
				1		T				
						T	1			1
		l	t	!	l	+	1	 	t	1
		!	 	 	h	╁	†	 	 	
		 		 	ļ	+-	 	 	 	
	······································	ļ	 		ļ	1-		ļ	 	
		ļ		ļ		1	ļ	ļ	ļ	
			ļ			1	!			
		<u> </u>				L	L			
		L				Γ	l	L		
		l	I			Т	T	T		
			T	1		T	Ī	1		1
		l	1			٢	i		 	
		h				╀				
	·					╆	 	 		
						╀				
						₽				ļ
						L				
						L				
						Г				
						T				
				·		†				
					·	†~				
						╁╌		 	 	
					ļ	₽				
						ļ.,				
						₽-			ļ	
						₽				ļ
						Ļ				ļ
						↓-				
						L				
						L.	<u></u>			1
					<u> </u>	L				
						ı				1
				· · · · · · · · · · · · · · · · · · ·		Т				
						†~~		l		
						t				1
	***************************************		 			t	t		t	
						 	 	 	 	
			 		ļ	╀╌	 	}	 	
		ļ	 			۱	 	-		
			<u> </u>		 	╂	ļ	ļ	ļ	ļ
						┖				
						L				ļ
T						L				
		L				Γ	1			
			I			T	I	I		1
						t	1			
			l			t	<u> </u>		1	1
		<u> </u>	·		 	t		 	 	
+			 			†-	 		 	
			 		 	╁			 	
 				ļ		۰		 	 	
		L				╀	_			
						L			-	ļ
				I		L				
						•				
						L				
						t				
						F				

READING @ HANDHOLE OR JUNCTION BOX

METERED μη Ω

CALCULATED μη Ω

411 1.32 409 1.33 READING @ CONTROLLER

CALCULATED METERED
μη Ω μη Ω

NUMBER

OF

TURNS

LOOP

DESIGNATION