

TRAFFIC SIGNAL INSTALLATION ELECTRICAL SERVICE REQUIREMENTS WATTAGE (YELLOW) Systems LASHER NERGY COSTS TO:

TEMPORARY CABLE DIAGRAM LEGEND

TEMPORARY CONTROLLER CABINET

TEMPORARY TRAFFIC SIGNAL SECTION OR PEDESTRIAN SIGNAL SECTION 12" (300mm

TEMPORARY SERVICE INSTALLATION INDICATES NUMBER OF CONDUCTORS IN CABLE, ALL CONDUCTORS TO BE NUMBER 14 AWG WIRE UNLESS OTHERWISE NOTED

▶● EMERGENCY VEHICLE LIGHT DETECTOR

VEHICLE DETECTOR, INDUCTION LOOP

CONFIRMATION BEACON


VI VIDEO DETECTOR

PUSHBUTTON DETECTOR

12" (300mm) PEDESTRIAN SIGNAL SECTION MICROWAVE VEHICLE SENSOR

 \odot

PUSH BUTTON "A" SHALL PLACE A CALL IN PHASES 2 AND 4 PUSH BUTTON "B" SHALL PLACE A CALL IN PHASES 4 AND 6
PUSH BUTTON "C" SHALL PLACE A CALL IN PHASES 6 AND 8 (3) PUSH BUTTON "D" SHALL PLACE A CALL IN PHASES 8 (3) AND 2




- I. DURING THE MAINTENANCE OF TRAFFIC PRE-STAGE AND STAGES 1, 2, 3 AND 4, THE SIGNAL HEADS SHALL BE MOVED AS NECESSARY TO ALIGN WITH THE TRAFFIC LANES.
- 2. - THESE SIGNAL HEADS SHALL BE BAGGED DURING MAINTENANCE OF TRAFFIC STAGE IA AND IB DUE TO THE TRAFFIC BEING ONE-WAY NORTHBOUND.
- 3. * THESE SIGNAL LENSES SHALL BE DISPLAYED AFTER STAGE 4 IS COMPLETED
 IN CASE THE PERMANENT SIGNALS ARE NOT OPERATIONAL. DURING MAINTENANCE
 OF TRAFFIC PRE-STAGE AND STAGES ITHROUGH 4, THEY SHALL BE BAGGED AND REMAIN INACTIVE, THE PROPOSED CONTROLLER SEQUENCE POST STAGE 4 SHALL BE USED FOR PHASING.

COUNTY TOTAL SHEET NO. COOK 246 153 SECTION 3509 00-00173-00-FP COOK TO STA.

FED. ROAD DIST. NO. 7 ILLINOIS FED. AID PROJECT

TEMPORARY CONTROLLER SEQUENCE PRE-STAGE AND STAGES 2A, 2B, 3A, 3B, 4, AND WINTER SHUTDOWN



PHASE DESIGNATION DIAGRAM

TEMPURARY CONTROLLER SEQUENCE STAGE 1A AND 1B SHERIDAN RD ISABELLA ST 4-6 -2-

PHASE DESIGNATION DIAGRAM

PROPOSED CONTROLLER SEQUENCE POST STAGE 4 OL SHERIDAN RD ISABELLA ST 4-6-

PHASE DESIGNATION DIAGRAM

NUMBER REFERS TO ASSOCIATED PHASE

