NOTES:

- I. ALL MATERIALS AND METHODS SHALL BE IN ACCORDANCE WITH STANDARD SPECIFICATIONS FOR WATER AND SEWER MAIN CONSTRUCTION IN ILLINOIS LATEST EDITION.
- 2. CONTRACTORS SHALL CONTACT EACH UTILITY COMPANY PRIOR TO CONSTRUCTION. ANY DAMAGE CAUSED TO EXISTING UTILITIES SHALL BE THE CONTRACTORS RESPONSIBILITY AND CONTRACTOR SHALL LEND ALL POSSIBLE ASSISTANCE IN RESTORING SERVICE.
- 3. NOT ALL OF THE GAS, POWER OR TELEPHONE LINES, WERE ABOVE OR BELOW GROUND, HAVE BEEN SHOWN ON THE PLANS. THE LOCATION OF EXISTING UNDERGROUND UTILITIES, SUCH AS GAS OR WATER MAINS, ETC..., AS SHOWN ON THE PLANS HAVE BEEN DETERMINED FROM THE BEST AVAILABLE INFORMATION AND ARE GIVEN FOR THE CONVENIENCE OF THE CONTRACTOR. THE CONTRACTOR SHALL ASSUME RESPONSIBILITY FOR ALL UTILITIES, WHETHER SHOWN OR NOT, AND MUST REALIZE THAT THE ACTUAL LOCATIONS AND THOSE SHOWN MAY BE DIFFERENT.
- 4. INTERRUPTION OF UTILITY SERVICE IS NOT EXPECTED. HOWEVER, IF INTERRUPTION OF ANY UTILITY SERVICE IS NECESSARY, THE CONTRACTOR SHALL GIVE AT LEAST ONE DAY NOTICE TO CUSTOMERS INVOLVED AND SHALL USE ALL HIS RESOURCES TO MINIMIZE INTERRUPTION.
- 5. ALL DISTURBED AREAS SHALL BE GRADED TO PROVIDE POSITIVE DRAINAGE. CULVERTS, FIELD TILES AND OTHER DRAINAGE FACILITIES DAMAGED DURING CONSTRUCTION SHALL BE REPLACED BY CONTRACTOR AT NO ADDITIONAL COST TO THE VILLAGE.
- 6. ANY PERMANENT SURFACE, STREET, DRIVEWAY, OR SIDEWALK DAMAGE BY CONTRACTOR SHALL BE REPAIRED BY CONTRACTOR.
- 7. DETECTABLE WARNINGS SHALL BE YELLOW IN COLOR AT ALL LOCATIONS.

SUMMARY OF QUANTITIES

CODE #	ITEM DESCRIPTION	T	OTAL	UNIT
20100110	TREE REMOVAL (6 - 15 UNIT DIAMETER)	10	00	TIMU
20200100	EARTH EXCAVATION	30	00	CU YD
21400100	GRADING AND SHAPING DITCH	40	00	FOOT
25000100	SEEDING, CLASS 1	0.	.9	ACRE
28100107	STONE RIP RAP CLASS A 4	60	00	SQ YD
42400200	PORTLAND CEMENT CONCRETE SIDEWALK 5 INCH	1,01	11	50 FT
42400400	PORTLAND CEMENT CONCRETE SIDEWALK 7 INCH	52	24	SQ FT
42400800	DETECTABLE WARNINGS	25	56	SQ FT
44000 3 C	CURB REMOVAL	98	3	FCOT
44000600	SIDEWALK REMOVAL	14	Ö1	SQ FT
50300225	CONCRETE STRUCTURES	28	3	CU YD
50901760	PIPE HANDRAIL	24	40	FOOT
54010604	PRE CAST CONCRETE BOX CULVERT, 6'x4'	24	4	FOOT
542A0220	PIPE CULVERT CL A I, 15"	20	2	FOOT
67100100	MOBILIZATION	1		LUMP SUM
70100450	TRAFFIC CONTROL AND PROTECTION	ŧ		LUMP SUM
72000100	SIGN PANEL TYPE I	14	14	SQ FT
72400500	RELOCATE SIGN PANEL ASSEMBLEY	3		EACH
72900100	METAL POST TYPE A	16	-ප	FOOT
78001150	PAINT PAVEMENT MARKING LINE 12"	13	44	FOOT
54001001	BOX CULVERT END SECTIONS, CUIVERT NO I	2		EACH
42300100	PORTLAND CEMENT CONCRETE DRIVEWAY PAVEMENT, 5 INCH	16	.3	SQ YD
××00050	3 SPLIT RAIL FENCE	68	30	FOOT
X8210425	LUMINAIRE, STREET LIGHTING, HIGH PRESSURE SODIUM VAPOR, 250 WATT, 240 VOLT	10	i	EACH
X0325714	FLASHING BEACON POST MOUNTED, SOLAR POWERED INSTALLATION	ON 6		EACH

A SPECIALTY ITEMS

NO.	DESCRIPTION	8Y	DATE	NO.	DESCRIPTION	BY	DATE	l	HY	DATE
Г								DESIGNED		
Г								DRAW	WFL.	3/27/12
			T	T			ĺ	CHECKED	JHC	3/27/12
			1	Al	REVISED PER IDOT REQUEST	WDS	7/30/12			

VILLAGE OF GOREVILLE JOHNSON COUNTY, IL SAFE ROUTES TO SCHOOL NOTES AND QUANTITIES

 \triangle

 Δ

 \triangle

