









LAP DETAIL III

Pavement Width	Bar Size	Pavement Thickness	I	(Approx. Spacing)	B	0	0
12 feet	#7	کے 14″	个	23 spaces (24 bars) @ 6"	31/2"	3′′	26"
14 feet	#7	14" }	T	27 spaces (28 bars) @ 6" }	31/2"	3′′	26"
16 feet	#7	14"	1	31 spaces (32 bars) @ 6" }	31/2"	3''	26''

NOTES:

- 1. THE PAVEMENT REINFORCEMENT SHALL BE 4.5" FROM THE TOP OF PAVEMENT.
- EXCEPT AS NOTED OR SHOWN, THE DIMENSIONS AND NOTES SPECIFIED FOR LAP DETAIL I ARE TYPICAL FOR LAP DETAIL II AND III.
- THE (B) DIMENSION AND THE DISTANCE FROM THE END OF THE TRANSVERSE BAR TO THE EDGE OF PAVEMENT MAY BE INCREASED BY 1" FOR SLIP FORM PAVING.

RDT-1

11	REVISIONS				
	DATE	NAME	\wedge		
F •	7/27/06	ADDENDUM 1	/1\		
63RD S					
EX					
CONTI					

ILLINOIS DEPARTMENT OF TRANSPORTATION F.A.I. 90/94 (DAN RYAN EXPRESSWAY) STREET TO GARFIELD BLVD (NB LOCAL LANES)

ROADWAY DETAILS EXTENDED LANE REINFORCEMENT FOR TINUOUSLY REINFORCED PCC PAVEMENT

SCALE: NONE

DRAWN BY: NJH CHECKED BY: RMG

CTE | AECOM