

NOUTE NO.	OUTE NO. SECTION		COUNTY		SHEET NO.	Sŀ
FAI-55	**	Wi	'LL	505	353	32
HED. ROAD DEST. NO. 7		(LLINOIS	FED. AD PROJECT-			

SHEET NO. <u>12</u> 32 SHEETS

** SECTION 2006-032 BY CONTRACT NO. 60886

GENERAL NOTES

- 1 The strip seal shall be made continuous and shall have a minimum thickness of ¼". The configuration of the strip seal shall match the configuration of the Locking Edge Rails.
- The height and thickness of the Locking Edge Rails shown are minimum dimensions. The actual configuration of the Locking Edge Rails and matching strip seal may vary from manufacturer to manufacturer. Flanged edge rails will not be allowed.
- Looking Edge Rails may be spliced at slope discontinuities and stage construction joints.
- The manufacturer's recommended installation methods shall be followed.
- 5. The joint opening and deck dimensions detailed on the superstructure are based on a preformed joint seal. If the cantractor elects to use the alternate strip seal joint, the opening and deck dimensions shall be modified according to the dimensions detailed on this sheet. Required modifications shall be made at no additional cost to the State.

(Sheef 2 of 2) BRIDGE JOINT SYSTEM-EXPANSION (ALTERNATE STRIP SEAL) I-55 OVER MS (ABANDONED) R.R. FAI ROUTE 55-SEC. 2006-032 BY WILL COUNTY STA. 710+34.86 STRUCTURE NO. 099-0022 (NB) STRUCTURE NO. 099-0023 (SB)

