



PROPOSED LOCAL LANES

STA. 3537+00.25 TO STA. 3541+43.17 - SUPERELEVATION = 5.7% (SUPERELEVATION TRANSITION SECTION FROM STA. 3541+43.17 TO STA. 3545+91.96 IS SIMILAR)

** SEE PLAN SHEETS FOR DETAILS

1. SEE ROADWAY DETAILS FOR VARIABLE HEIGHT OF THE DOUBLE FACE BARRIER WALL AND FOR THE TYING OF THE BARRIER BASE TO THE PCC SHOULDER AND FOR THE LIMITS OF CONSTRUCTION OF THE SUB-BASE GRANULAR MATERIAL UNDER THE DOUBLE FACE BARRIER WALL.

- 2. SHOULDER RUMBLE STRIPS SHALL BE CONSTRUCTED IN THE PROPOSED AND EXISTING SHOULDERS OF THE LOCAL AND EXPRESS LANES ACCORDING TO IDOT STANDARD 642001.
- 3. TYPICAL SECTIONS NEED TO BE VERIFIED WITH THE ROADWAY PLANS AS THEY ARE A REPRESENTATION OF THE PLANS. THEY DO NOT SHOW ALL CONFIGURATIONS, JUST THE MOST PREDOMINANT.
- 4. THE SLOPE OF THE STABILIZED SUB-BASE $4last_2^{\prime\prime}$ UNDER THE SHOULDERS AND CURB AND GUTTER SHALL MATCH THE SLOPE OF THE ADJACENT PAVEMENT IN THE NORMAL CROWNED AREAS.

SSR= 2.00

MAINLINE: STRUCTURAL DESIGN TRAFFIC: YEAR 2020 PV= 125,272 SU= 10,930 MU= 31,949 ROAD/STREET CLASSIFICATION: CLASS 1 P= 8% S= 37% M = 37%TRAFFIC FACTOR: ACTUAL TF= 264.46 MINIMUM TF= 12.39

SUBGRADE SUPPORT RATING:

MODIFIED EXISTING RETAINING WALL TOPSOIL FURNISH AND PLACE SEEDING (SEE LANDSCAPING PLANS FOR DETAILS) LONGITUDINAL SAWED OR CONSTRUCTION JOINT, FOR LONGITUDINAL SAWED JOINT, POUR IN PLACE NO. 6 DEFORMED EPOXY TIE BARS 30" LONG AT 30" C-C. FOR LONGITUDINAL CONSTRUCTION JOINT, DRILL AND GROUT NO. 8 DEFORMED EPOXY TIE BARS 24" LONG AT 24" C-C. (SHALL BE INCLUDED IN THE COST OF C.R.P.C.C. PAVEMENT 14") LONGITUDINAL CONSTRUCTION JOINT. DRILL AND GROUT NO. 6 DEFORMED EPOXY TIE BARS 24" LONG AT 24" C-C. (SHALL BE INCLUDED IN THE COST OF THE APPLICABLE COMB. CONC. CURB AND GUTTER TYPE) LONGITUDINAL CONSTRUCTION JOINT.
DRILL AND GROUT NO. 8 DEFORMED EPOXY TIE BARS 24" LONG AT 24" C-C.
(SHALL BE INCLUDED IN THE COST OF P.C.C. BASE COURSE 9") LONGITUDINAL CONSTRUCTION JOINT.
DRILL AND GROUT NO. 8 DEFORMED EPOXY TIE BARS 30" LONG AT 24" C-C.
(SHALL BE INCLUDED IN THE COST OF THE APPLICABLE P.C.C. SHOULDER(TYPE) SUB-BASÉ GRANULAR MATÉRIAL, TYPÉ B 12"

F.A.I. SECTION

94/90 *

PROPOSED LEGEND

CONTINUOUSLY REINFORCED PORTLAND CEMENT CONCRETE PAVEMENT 14" AND PAVEMENT REINFORCEMENT 14"

(2)

3

(4)

(5)

(6)

(7)

(8)

(9)

(10)

(ii)

(12)

(13)

(14)

(16)

(17)

(18)

(19)

(20)

(21)

(22)

(23)

(24)

(25)

(26)

(27)

28)

(29)

(30)

(31)

(32)

(33)

36

37)

NOT USED

STABILIZED SUB-BASE 41/2"

CONCRETE GUTTER, TYPE B

CONCRETE MEDIAN SURFACE, 6"

CHAIN LINK FENCE, 4' (SPECIAL)

BARRIER BASE

PIPE UNDERDRAINS 6"

RETAINING WALL

SAND BACKETLL

SUB-BASE GRANULAR MATERIAL, TYPE B 6"

SUB-BASE GRANULAR MATERIAL, TYPE B 24"

STRIP REFLECTIVE CRACK CONTROL TREATMENT

PORTLAND CEMENT CONCRETE BASE COURSE 91/2"

PORTLAND CEMENT CONCRETE SHOULDERS 11"

CONCRETE MEDIAN SURFACE, 5" (MODIFIED)

CONCRETE BARRIER, DOUBLE FACE, 32" HEIGHT

CONCRETE BARRIER, SINGLE FACE, 32" HEIGHT

BARRIER WALL MARKERS, TYPE C (80' C-C)

COMBINATION CONCRETE CURB AND GUTTER, TYPE B-6.12

COMBINATION CONCRETE CURB AND GUTTER, TYPE M-2.24

COMBINATION CONCRETE CURB AND GUTTER, TYPE M-4.24

COMBINATION CONCRETE CURB AND GUTTER, TYPE M-4.48 (MODIFIED)

CONCRETE MEDIAN SURFACE, 6" (SPECIAL)

PORTLAND CEMENT CONCRETE PAVEMENT 11" (JOINTED)

(EXCAVATE AND PLACE EXISTING GRANULAR MATERIAL

PORTLAND CEMENT CONCRETE SHOULDERS 14"(& VAR)

BITUMINOUS MATERIALS (PRIME COAT)

GEOTECHNICAL FABRIC FOR GROUND STABILIZATION

BITUMINOUS CONCRETE SURFACE COURSE, SUPERPAVE, MIX "D" N70, 11/2"

POLYMERIZED LEVELING BINDER (MACHINE METHOD), SUPERPAVE, IL-4.75, N50, 1"

COUNTY TOTAL SHEE

588

COOK

FED. ROAD DIST. NO. ILLINOIS FED. AID PROJECT

62303 * (2021-922 PT2 ETC 2324.6-1P) R-11

AC TYPE= N/A AC GRADE: BINDER:= SURFACE:=

BOWMAN, BARRETT & ASSOCIATES INC. CONSULTING ENGINEERS
Chicago, Illinois
312.228.0100

ILLINOIS DEPARTMENT OF TRANSPORTATION DATE NAME F.A.I. 94/90 (DAN RYAN EXPRESSWAY) ADDENDUM GARFIELD BLVD TO 31ST STREET (SB LOCAL LANES) PROPOSED TYPICAL SECTIONS SCALE: NTS DRAWN BY: JDC DATE: 06/09/06 CHECKED BY: RS

PRTYP-3

PROPOSED LOCAL LANES STA. 3529+00 TO 3530+92.51 - SUPERELEVATION = 5.7% (SUPERELEVATION TRANSITION SECTION FROM STA. 3530+92.51 TO 3537+00.25 IS SIMILAR) B SB LOCAL