0

0

0

0

STATE OF ILLINOIS

DEPARTMENT OF TRANSPORTATION

PROPOSED HIGHWAY PLANS

VARIOUS ROUTES SECTION D4 INTERSTATE DELINEATORS 2024 PROJECT HSIP-8S4T(893) **SAFETY IMPROVEMENT VARIOUS COUNTIES**


C-94-076-23

INDEX OF SHEETS

- **COVER SHEET**
- **GENERAL NOTES/JOB SPECIFIC NOTES**
- **SUMMARY OF QUANTITIES**
- 4-5 SCHEDULE OF QUANTITES
- **6 DISTRICT STANDARD**

HIGHWAY STANDARDS


635001-02 701426-09 701901-08




ENGINEERING SCALES. REDUCED SIZED PLANS WILL NOT CONFORM TO STANDARD SCALES. IN MAKING MEASUREMENTS ON REDUCED PLANS, THE ABOVE SCALES MAY BE USED.

JOINT UTILITY LOCATION INFORMATION FOR EXCAVATORS 1-800-892-0123 OR 811

PROJECT ENGINEER ANNA GHIDINA 309-671-4460





VAR D4 INTER. DELINEATOR 2024

VARIOUS 6 1



PRINTED BY THE AUTHORITY OF THE STATE OF ILLINOIS

CONTRACT NO. 68H73

ADDITIONAL SUPPLEMENTAL TRAFFIC CONTROL

The Department reserves the right at any time to add additional Traffic Control Systems or devices within the active contract limits, by means of an additional contract. All terms of Article 105.08 of the Standard Specifications shall be followed by each Contractor.

RECOVERABLE DELINEATOR INSTALLATION

The contractor shall install the recoverable delineators starting at the beginning mile marker within the respective county. Locations within the rest areas shall be on the ramps into the truck parking areas. Verification of these areas may be obtained from the Operations - Traffic Section.

DESIGNED -DRAWN -REVISED -HECKED . REVISED

STATE OF ILLINOIS **DEPARTMENT OF TRANSPORTATION** GENERAL NOTES/JOB SPECIFIC NOTES

CONTRACT NO. 68H73

				VARIOUS COUNTIES	VARIOUS COUNTIES				
	CLINANAADV OF OLIANITITIEC			URBAN	RURAL				
	SUMMARY OF QUANTITIES			0021	0021				
ITEM NUMBER	ITEM DESCRIPTION	UNIT	TOTAL QUANTITY	QUANTITY	QUANTITY				
67100100	MOBILIZATION	LSUM	1	0.5	0.5				
X2600002	RECOVERABLE DELINEATORS	EACH	3747	1832	1915				
X6350120	DELINEATOR REMOVAL	EACH	1029	659	370				

USER NAME = Anna Ghidina	DESIGNED -	REVISED -
	DRAWN -	REVISED -
PLOT SCALE = 40.0000 / in	CHECKED -	REVISED -
PLOT DATE = 6/27/2023	DATE -	REVISED -

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

SCALE:

					F.A. RTE	SE	ECTION		COUNTY	TOTAL SHEETS	SHEE
	SUMMARY	of Qua	ANTITIES		VAR	D4 INTER. D	DELINEATOR	2024	VARIOUS	6	3
									CONTRACT	NO. 6	8H73
SHEET	OF	SHEETS	STA.	TO STA.			ILLINOIS	FED. AI	ID PROJECT		

		I-74 Knox (County - URBA	N			
	Mile	Post			White	Yellow	Removal
Direction	Begin	End	Distance (Ft)	Spacing	Each	Each	Each
Eastbound	45	51	31680	400	79		
Westbound	45	51	31680	400	79		
US 34 Interchange							
EB 74 to WB 34			2500	100	4	25	
WB 34 to EB 34			1600	100	4	16	
EB 74 to EB 34			1600	100	4	16	
EB 34 to EB 74			2500	100	4	25	
WB 74 to EB 34			2500	100	4	25	
EB 34 to WB 34			1600	100	4	16	
WB 74 to WB 34			1600	100	4	16	
WB 34 to WB 74			2500	100	4	25	
Main St. (EX 48)							
WB Exit to EB East Main St.			1600	100	4	16	
WB Entrance from East Main			1200	100	4	12	
WB Exit to WB East Main St.			1600	100	4	16	
EB Exit			1000	100	4	10	
EB Entrance			1200	100	4	12	
CH 9 (EX 51)							
WB Exit			2000	100	4	20	
WB Entrance			1800	100	4	18	
EB Exit			2000	100	4	20	
EB Entrance			1900	100	4	19	
			TOTAL		226	307	
			GRAND T	OTAL	5.	33	

		I-74 Knox	County - RURA	۱L			
	Mile	Mile Post			White	Yellow	Removal
Direction	Begin	Begin End		Spacing	Each	Each	Each
Eastbound	51	68	89760	400	224		
Westbound	51	68	89760	400	224		
EXIT 54			•			•	•
WB Exit			1200	100	4	25	
WB Entrance			2200	100	4	16	
EB Exit			2000	100	4	16	
EB Entrance			1600	100	4	25	
Spoon River Rest Area							
WB Exit			1300	100	13	13	
WB Entrance			1000	100	10	10	
EB Exit			1400	100	14	14	
EB Entrance			1000	100	10	10	
	_		TOTA	TOTAL		129	
			GRANDT	OTAL	640		

I-74 Peoria County - RURAL										
	Mile	Mile Post			White	Yellow	Removal			
Direction	Begin	End	Distance (Ft)	Spacing	Each	Each	Each			
Eastbound	68	71	15840	400	40		40			
Westbound	68	71	15840	400	40		40			
			TOTAL		80	0	80			
	GRAND TOTAL		80							

	1-7	4 Tazewe	ll County - URE	BAN			
	Mile	Post			White	Yellow	Removal
Direction	Begin	End	Distance (Ft)	Spacing	Each	Each	Each
Eastbound	96	104	42240	400	106		106
Westbound	96	104	42240	400	106		106
Pinecrest (EX 98)							
WB Entrance			1630	100	4	16	20
WB Exit			2000	100	4	20	24
EB Entrance			3000	100	4	30	34
EB Exit			1948	100	4	19	23
Morton (EX 102)							
WB Entrance			2500	100	4	25	29
WB Exit			2500	100	4	25	29
EB Entrance			2800	100	4	28	32
EB Exit			2400	100	4	24	28
			TOTA	\L	244	187	431
			GRAND T	OTAL	4:	31	

	I-7	4 Woodfo	ord County - RU	RAL	•		·	
	Mile	Mile Post			White	Yellow	Removal	
Direction	Begin	End	Distance (Ft)	Spacing	Each	Each	Each	
Eastbound	110	118	42240	400	106		106	
Westbound	110	118	42240	400	106		106	
Goodfield (EX 112)								
WB Entrance			2000	100	4	20	24	
WB Exit			1600	100	4	16	20	
EB Entrance			2000	100	4	10	14	
EB Exit			1600	100	4	16	20	
Mackinaw Dells Rest Area				,				
WB Entrance			2800	100	4	28		
WB Exit			2800	100	4	28		
EB Entrance			2500	100	4	25		
EB Exit			2800	100	4	28		
			TOTA	<u></u>	244	171	290	
		•	GRAND 1	OTAL	4	15		

SCALE:

SHEET

USER NAME = Anna Ghidina	DESIGNED -	REVISED -
	DRAWN -	REVISED -
PLOT SCALE = 40.0000 / in.	CHECKED -	REVISED -
PLOT DATE = 6/27/2023	DATE -	REVISED -

9	STATE	OF	ILLINOI	S
DEPARTIV	IENT (OF 1	RANSP	ORTATION

	HEDULE OF QUANTITES		F.A. SECTION			COUNTY	TOTAL SHEETS	SHEET NO.
SCHEDULE OF QUANTITES		VAR	D4 INTER. DELINEATOR 2024		VARIOUS	6	4	
						CONTRACT	NO. 68	3H73
OF SHEETS STA	. TO STA.			ILLINOIS	FED. AI	D PROJECT		

	I-474 Tazewell County - URBAN											
	Mile	Mile Post			White	Yellow	Removal					
Direction	Begin	End	Distance (Ft)	Spacing	Each	Each	Each					
Eastbound	9	15	31680	400	79		79					
Westbound	9	15	31680	400	79		79					
Goodfield (EX 112) Ramp												
WB Entrance			1400	100	4	14	18					
WB Exit			1800	100	4	18	22					
EB Entrance			2500	100	4	10	14					
EB Exit			1200	100	4	12	16					
		TOTAL		174	54	228						
			GRAND TOTAL		2							

I-155 Tazewell County - RURAL Mile Post White Yellow Removal							
Direction	Begin	End	Distance (Ft)	Spacing	Each	Each	Each
Northbound	11	31	105600	400	264	Lucii	Lacii
Southbound	11	31	105600	400	264		
Curve 1 NB	20.5	20.7	1056	100	10	10	
Curve 1 SB	20.5	20.7	1056	100	10	10	
Curve 2 NB	19.1	19.4	1584	100	15	15	
Curve 2 NB	19.1	19.4	1584	100	15	15	
	15.1	15.4	1364	100	13	13	
I-74/I-155 Interchange NB 155 to EB 74			2400	100	4	T 24	<u> </u>
			2400	100	4	24	
NB 155 to WB 74			3500	100	4	35	
EB 74 to SB 155			3300	100	4	33	
WB 74 to SB 155			3500	100	4	35	
Birchwood (EX 31)							
SB Entrance			2700	100	4	27	
SB Exit			1850	100	4	18	
NB Entrance			3000	100	4	30	
NB Exit			2150	100	4	21	
Queenwood (EX 30)							
SB Entrance			1800	100	4	18	
SB Exit			1500	100	4	15	
NB Entrance			2000	100	4	20	
NB Exit			2100	100	4	21	
Broadway (EX 28)							
SB Entrance			1950	100	4	19	
SB Exit			1360	100	4	13	
NB Entrance			2000	100	4	20	
NB Exit			1750	100	4	17	
Tremont (EX 25)							
SB Entrance			2000	100	4	20	
SB Exit			1600	100	4	16	
NB Entrance			2300	100	4	23	
NB Exit			1520	100	4	15	
Townline (EX 22)							
SB Entrance			1930	100	4	19	
SB Exit			1700	100	4	17	
NB Entrance			2000	100	4	20	
NB Exit			1850	100	4	18	
Hopedale (EX 19)							
SB Entrance			2500	100	4	25	
SB Exit			1950	100	4	19	
NB Entrance			2000	100	4	20	
NB Exit			1700	100	4	17	
Delavan (EX 15)							
SB Entrance			2000	100	4	20	
SB Exit			1400	100	4	14	
NB Entrance			1500	100	4	15	
NB Exit			2000	100	4	20	
			TOTA		706	714	
			GRAND T			120	

USER NAME = Anna.Ghidina	DESIGNED -	REVISED -
	DRAWN -	REVISED -
PLOT SCALE = 40.0000 / in	CHECKED -	REVISED -
PLOT DATE = 6/27/2023	DATE -	REVISED -

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

SCALE:

				F.A. RTE.	SECTION		COUNTY	TOTAL SHEETS	SHEET NO.		
SCHEDULE OF QUANTITIES			VAR.	D4 INTER. DELINEATOR 2024		VARIOUS	6	5			
							CONTRACT	NO. 68	3H73		
	SHEET	OF	SHEETS	STA.	TO STA.		ILLINOIS FED. AID PROJECT				

MODEL: Default

2' MIN **ON HORIZONTAL CURVES** 6' MAX SPACING RADIUS ON CURVE LOCATION OF CURVE Delineators shall be placed (FEET) (FEET) 2 feet from break point SHOULDER on all interchange ramps and wherever pavement PAVEMENT superelevation exceeds 6% Grade of pavement edge ii II **SECTIONAL VIEW** -DELINEATORS (WHITE SHEETING) DELINEATORS (YELLOW SHEETING) DELINEATORS (YELLOW SHEETING) -DELINEATORS (WHITESHEETING) **PLAN VIEW GENERAL NOTES** Delineators on mainline shall be placed at 400' spacing on tangent sections, and 200' spacing on curved sections. Delineators on ramps, shall be placed as follows: 1. On tangent sections, acceleration lanes and deceleration lanes at maximum spacing of 100'. 2. On outside of all curved sections. (See table above for spacing) 08-25-15 NEW STANDARD SECTION COUNTY STATE OF ILLINOIS RECOVERABLE DELINEATORS DETAIL VAR D4 INTER. DELINEATOR 2024 VARIOUS 6 6 **DEPARTMENT OF TRANSPORTATION** CONTRACT NO. 68H73 NOT TO SCALE CADD STD. 635002-D4 FED. ROAD DIST. NO. | ILLINOIS FED. AID PROJECT

STANDARD.

CADD

THIS

USING

WHEN

RECOVERABLE DELINEATORS

DISTRICT SPECIA ON INTERSTATE

USE USE

DESIGNER NOTES:

SPACING FOR RECOVERABLEDELINEATORS