PROP. PAY LIMIT OF HMA SURF. REMOVAL FULL THICKNESS OF MILLING TEMP. RAMP (NOTE "C") (NOTE "E") PROP. HMA SURFACE REMOVAL EXIST. PAVEMENT MILLED TEMPORARY RAMP (FOR BUTT JOINT AND HMA TAPER SEE DETAIL BELOW) OPTION 1 PROP. PAY LIMIT OF HMA SURF. REMOVAL FULL THICKNESS OF MILLING SAW CUT (INCLUDED IN THE COST OF HMA SURFACE (NOTE "C") PROP. HMA SURFACE REMOVAL REMOVAL - BUTT JOINT) _1¾ (45) FOR E AND F MIX 4'-6" (1.35 m) PAY LIMIT FOR BUTT JOINT 1/2 (40) FOR C AND D MIX EXIST. HMA EXIST. PAVEMENT HMA CONSTRUCTED TEMPORARY RAMP (FOR BUTT JOINT AND HMA TAPER SEE DETAIL BELOW) OPTION 2 TYPICAL TEMPORARY RAMP HMA TAPER LENGTH SAW CUT (INCLUDED IN THE COST OF HMA SURFACE PROP. HMA SURF. CRSE. REMOVAL - BUTT JOINT) PROP. HMA BINDER CRSE. 4'-6" (1,35 m) VARIES 13/4 (45) FOR E AND F MIX PAY LIMIT FOR BUTT JOINT (NOTE "D") 11/2 (40) FOR C AND D MIX EXIST. HMA SURF. EXIST. PAVEMENT HMA SURF, REMOVAL - BUTT JOINT

CONTRACT NO. 62037

F.A. SECTION COUNTY TOTAL SHEETS NO. 303 134(B&B-2)R-1 LAKE 137 108 TO STA. FED. ROAD DIST. NO. 1 ILLINOIS FED. AID PROJECT PROP. HMA OR PCC
SURFACE REMOVAL - BUTT JOINT
30'-0" (9.0 m) (NOTE "A") SAW CUT (INCLUDED IN THE COST OF HMA OR P.C.C. SURFACE REMOVAL - BUTT JOINT) EXIST. HMA OR PCC SURFACE 15'-0" (4.5 m) (NOTE "B") (NOTE "D") 13/4 (45) FOR E AND F MIX 11/2 (40) FOR C AND D MIX * * EXIST. PAVEMENT BUTT JOINT DETAIL TAPER LENGTH * * VARIES 13/4 (45) FOR E AND F MIX PROP. HMA BINDER CRSE. 11/2 (40) FOR C AND D MIX * * EXIST. PAVEMENT HMA TAPER DETAIL TYPICAL BUTT JOINT AND HMA TAPER FOR RESURFACING ONLY * * PC CONCRETE, HMA OR HMA RESURFACED PAVEMENT. NOTES A: MAINLINE ROADWAYS AND MAJOR SIDE ROADS. B: MINOR SIDE ROADS. C: THE TEMP. RAMP SHALL BE CONSTRUCTED IMMEDIATELY UPON REMOVAL OF THE EXISTING HMA SURFACE. D: THE BUTT JOINT SHALL BE CONSTRUCTED IMMEDIATELY PRIOR TO PLACING THE PROPOSED HMA COURSES. E: TAPER THE TEMP. RAMP AT A RATE OF 3'-0" (900 mm) PER 1 INCH (25 mm) OF MILLING THICKNESS. F: INSTALLATION AND REMOVAL OF THE 4'-6" (1.35 m) TEMP. RAMP IS INCLUDED IN COST OF HMA SURFACE REMOVAL - BUTT JOINT

G: SEE ARTICLE 406.08 AND 406.14 OF THE STANDARD SPECIFICATIONS FOR "HMA AND/OR PCC SURFACE REMOVAL, BUTT JOINT".

* SEE TYPICAL SECTIONS FOR MILLING THICKNESS.

** * 20'-0" (6.1 m) PER 1 (25) RESURFACING (NOTE "A") 10'-0" (3.0 m) PER 1 (25) RESURFACING (NOTE "B")

ALL DIMENSIONS ARE IN INCHES (MILLIMETERS) UNLESS OTHERWISE SHOWN.

09/09/9

R. SHAH A. ABBAS M. GOMEZ BUTT JOINT AND HMA TAPER DETAILS

SCALE: VERT. NONE

CHECKED BY

BD400-05 (VI=BD32)

BASIS OF PAYMENT:

THE BUTT JOINT WILL BE PAID FOR AT THE CONTRACT UNIT PRICE PER SOUARE YARD ISQUARE METER) FOR "HOT-MIX ASPHALT SURFACE REMOVAL - BUTT JOINT" OR FOR "PORTLAND CEMENT CONCRETE SURFACE REMOVAL- BUTT JOINT".

TYPICAL BUTT JOINT AND HMA TAPER
FOR MILLING AND RESURFACING

BUTT JOINT AND

HMA TAPER

DATE NAME SCALE NAME

PLOT PLOT USER