





TYPE || Not to Scale

TURBIDITY CURTAIN GENERAL NOTES:

- 1. TYPE I IS DESIGNED FOR USE IN SPALL LAKES AND PONDS WITH LITTLE OR NO WIND CURRENT AND LIGHT TURBIDITY.
- 2. TYPE II IS DESIGNED FOR USE ON RIVERS AND STREAMS, LARGE OPEN LAKES, BAYS, AND BEACHES WITH MODERATE CURRENTS AND WIND EXPOSURE.
- 3. TYPE III IS SIMILAR TO TYPE II ONLY WITH ADDITIONAL STRESS PLATES OR SPECIAL FABRIC TO HELP RELIEVE STRESSES CAUSED BY STRONG CURRENTS.
- 4. WHEN THE CURTAIN IS NO LONGER REQUIRED AS DETERMINED BY THE INSPECTOR, THE CURTAIN AND RELATED COMPONENTS SHALL BE REMOVED SO AS TO MINIMIZE TURBIDITY. REMAINING SEDIMENT SHALL BE SUFFICIENTLY SETTLED BEFORE REMOVING THE CURTAIN. SEDIMENT MAY BE REMOVED AND THE ORIGINAL DEPTH OR PLAN ELEVATION RESTORED. ANY SPOILS MUST BE TAKEN TO UPLAND AREA AND STABILIZED.

Turbidity Curtain



USER NAME = espina	DESIGNED	-	CLG	REVISED			MCHENRY	COUNTY	DIVISION	OF	TRANSPORTATION	
	DRAWN	-	EPS	REVISED	-							4
PLOT SCALE = 1.0000 '/ IN.	CHECKED	-	MJL	REVISED	-							\vdash
PLOT DATE = 8/2/2010	DATE	-	6/18/2010	REVISED	-							\perp