

АM 11:08:51 .

Approach slab and parapet concrete shall be paid for as Concrete Superstructure.

The approach footing maximum applied service bearing pressure (Qmax) = 2.0 ksf.



SOUTH APPROACHES BILL OF MATERIAL

Bar	No.	Size	Length	Shape	
a2(E)	32	#6	6'-6''		
a 30(E.)	136	#4	24'-8"		
a 31 (E)	186	#5	32'-3"		
Ь 10 (E)	96	#4	32'-7"		
b _Π (Ε)	278	#9	29′-9″	ـــــــ	
<i>Ь₁₂ (Е)</i>	1	#4	14′-8″		
b13(E)	1	#4	13′-5″		
d5(E)	74	#5	6'-10''	<u> </u>	
d6(E)	74	#5	7'-11''		
d7(E)	31	#5	2'-2"		
e ₆₇ (E)	28	#4	16'-1''		
e ₆₈ (E)	4	#8	32'-6''		
e ₆₉ (E)	4	#4	32′-6″		
$t_1(E)$	116	#4	15'-6"		
† ₂ (E)	126	#4	14'-3"		
w6(E)	120	#5	32'-6"		
w7(E)	120	#5	34'-1"		
Concrete Superstructure			Cu. Yd.	239.5	
Concrete Structures			Cu. Yd.	59.1	
Reinforcement Bars,			Pound 51.710		
Epoxy Coated				51,710	

APPROACH SLAB SECTIONS AND DETAILS - SOUTH APPROACH STRUCTURE NO. 101-0190

.* Е.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.				
	1-HBR & 1-2HB-D	WINNEBAGO	216	83				
RT	E 251 & FOREST HILLS RD	CONTRACT	NO. 6	4B79				
. ROAD DIST. NO. 7 ILLINOIS FED. AID PROJECT								
. A.F	2, 303 & F.A.U. 5146							