GENERAL NOTES

THE THICKNESS OF HMA SHOWN ON THE PLANS IS THE NOMINAL THICKNESS. DEVIATIONS FROM THE NOMINAL THICKNESS WILL BE PERMITTED WHEN SUCH DEVIATIONS OCCUR DUE TO IRREGULARITIES IN THE EXISTING SURFACE OR BASE ON WHICH THE HMA IS PLACED.

EXCEPT AS NOTED ON THE PLANS, PAVEMENT GRADES SHOWN ARE AT THE TOP OF PAVEMENT SURFACES.

BEFORE ORDERING PIPE CULVERTS OR PIPE DRAINS, THE CONTRACTOR SHALL CONSULT THE ENGINEER FOR EXACT LENGTHS.

THE ENGINEER WILL BE THE SOLE JUDGE CONCERNING CURING TIME FOR THE VARIOUS HMA LIFTS.

FOR STABILIZATION, ALL TYPE III BARRICADES SHALL REQUIRE A MINIMUM OF FOUR SAND BAGS PER BARRICADE.

SEEDING SHALL NOT BE PERMITTED AT ANY TIME WHEN THE GROUND IS FROZEN, WET, OR IN AN UNTILLABLE CONDITION. LOCATIONS TO BE SEEDED WILL BE DETERMINED BY THE ENGINEER.

ONLY THOSE TREES DESIGNATED BY THE ENGINEER OR LISTED IN THE TREE REMOVAL SCHEDULE SHALL BE REMOVED. THE CONTRACTOR SHALL PROTECT ALL REMAINING TREES FROM DAMAGE DUE TO HIS

THE FINISHED EARTHWORK SHALL HAVE A VEGETATION SUSTAINING SOIL COVERING THE TOP FOUR INCHES IN AREAS TO BE SEEDED OR SODDED. THE VEGETATION SUSTAINING SOIL REQUIRED WILL NOT BE PAID FOR SEPARATELY BUT SHALL BE INCLUDED IN THE COST OF FURNISHED EXCAVATION.

ALL ELEVATIONS REFERRING TO U.S.G.S. MEAN SEA LEVEL DATUM.

ABANDONED UNDERGROUND UTILITIES THAT CONFLICT WITH CONSTRUCTION SHALL BE DISPOSED OF OUTSIDE THE LIMITS OF THE RIGHT OF WAY ACCORDING TO ARTICLE 202.03 OF THE STANDARD SPECIFICATIONS AND AS DIRECTED BY THE ENGINEER. THIS WORK WILL NOT BE PAID FOR SEPARATELY, BUT SHALL BE INCLUDED IN THE COST OF EARTH EXCAVATION.

ANY REFERENCE TO A STANDARD IN THESE PLANS SHALL BE INTERPRETED TO MEAN THE EDITION AS INDICATED BY THE SUBNUMBER SHOWN IN THE LIST OF STANDARDS OR THE COPY INCLUDED IN THESE PLANS. THE FOLLOWING RATES OF APPLICATION HAVE BEEN USED IN CALCULATING PLAN QUANTITIES:

	GRANULAR MATERIALS	2.05	TONS / CU YD
	BIT MATERIALS (PRIME COAT)	0.375	GAL / SQ YD
	ON AGGREGATE BASES		
	BITUMINOUS MATERIALS	0.08	GAL / SQ YD
-	(PRIME COAT)		* .
	POLYMERIZED BIT MATERIALS	0.10	GAL / SQ YD
	(PRIME COAT)		
-	FOR ADDITIONAL HMA LIFTS	0.08	GAL / SQ YD
	"FOG COAT"		
	FOR ADDITIONAL HMA LIFTS	0.05	GAL / SQ YD
-	"FOG COAT"		
	AGGREGATE PRIME COAT	0.002	TONS / SQ YD
-	HMA RESURFACING	112	LBS / SQ YD / IN
ĺ	SHORT TERM PAVEMENT MARKING	10	FT /100 FT OF APPLICATION
1	MIX FOR CRACKS, JTS & FLGWYS	0.0003	TONS / SQ YD
I	LEVEL BINDER (HAND METHOD)	0.0005	TONS / SQ YD
ĺ	SUPPLEMENTAL WATERING	3	GAL / SQ YD / APPLICATION
l	CALCIUM CHLORIDE	2	LB / SQ YD / APPLICATION
ı	TEMPORARY DITCH CHECKS	5	TONS AGGREGATE

THE WORK REQUIRED TO CONNECT ANY SEWER TO AN EXISTING DRAINAGE STRUCTURE OR PIPE WILL NOT BE PAID FOR SEPARATELY, BUT SHALL BE CONSIDERED AS INCLUDED IN THE CONTRACT UNIT PRICE BID FOR THE SEWER ITEMS.

MEMBERS OF JULIE KNOWN TO BE WITHIN THE LIMITS OF THE IMPROVEMENT ARE:

MEDIACOM

CORNELL-RANSOM TELEPHONE COMPANY

COMED, AN EXELON COMPANY

THE CONTRACTOR SHALL CONTACT JULIE AT LEAST 48 HOURS PRIOR TO EXCAVATION TO DETERMINE WHICH UTILITIES ARE IN THE AREA.

HIGHWAY STANDARDS

000001-05 STANDARD SYMBOLS, ABBREVIATIONS AND PATTERNS

001001-02 AREAS OF REINFORCEMENT BARS

001006 DECIMAL OF AN INCH AND OF A FOOT

280001-05 TEMPORARY EROSION CONTROL SYSTEMS

420401-08 BRIDGE APPROACH PAVEMENT CONNECTOR

482001-02 HMA SHOULDER ADJACENT TO FLEXIBLE PAVEMENT

482011-03 HMA SHOULDER STRIPS/SHOULDERS WITH RESURFACING OR WIDENING AND RESURFACING PROJECTS

515001-03 NAME PLATE FOR BRIDGES

542401-01 METAL END SECTION FOR PIPE CULVERTS

601101-01 CONCRETE HEADWALL FOR PIPE DRAIN

610001-05 SHOULDER INLET WITH CURB

630001-08 STEEL PLATE BEAM GUARDRAIL

630201-06 PCC/HMA STABILIZATION AT STEEL PLATE BEAM GUARDRAIL

630301-05 SHOULDER WIDENING FOR TYPE 1 (SPECIAL) GUARDRAIL TERMINALS

631031-08 TRAFFIC BARRIER TERMINAL, TYPE 6

635001-01 DELINEATORS

635006-03 REFLECTOR AND TERMINAL MARKER PLACEMENT

635011-02 REFLECTOR MARKER AND MOUNTING DETAILS

701001-02 OFF-ROAD OPERATIONS, 2L, 2W, MORE THAN 15' AWAY

701006-03 OFF-ROAD OPERATIONS, 2L, 2W, 4.5 M (15') TO 600 MM (24") FROM PAVEMENT EDGE

701301-03 LANE CLOSURE, 2L, 2W, SHORT TIME OPERATIONS

701306-02 LANE CLOSURE, 2L, 2W, SLOW MOVING OPERATIONS DAY ONLY, FOR SPEEDS > 45 MPH

701311-03 LANE CLOSURE, 2L, 2W, MOVING OPERATIONS - DAY ONLY

701321-10 LANE CLOSURE, 2L, 2W, BRIDGE REPAIR WITH BARRIER

701326-03 LANE CLOSURE, 2L, 2W, PAVEMENT WIDENING, FOR SPEEDS > 45 MPH

701901-01 TRAFFIC CONTROL DEVICES

704001-06 TEMPORARY CONCRETE BARRIER

781001-03 TYPICAL APPLICATIONS RAISED REFLECTIVE PAVEMENT MARKERS

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

PREPARED BY:

ACTING DISTRICT STUDIES & PLANS ENGINEER

DATE:

FILE NAME =	USER NAME = IDOTCAD	DESIGNED	-	SPF	REVISED -
W:\2299-03 - IL Route 23 Roodway\DGN\CADD Sheets\D366822-sht-gennote.dgn		DRAWN	-	AJP	REVISED -
	PLOT SCALE = 50.0000 '/ in.	CHECKED	-	JMS	REVISED -
	PLOT DATE = 8/2/2010	DATE	-	08/05/10	REVISED -

STATE OF ILLINOIS **DEPARTMENT OF TRANSPORTATION**

SCALE: N/A

		F.A.P RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.		
IGHWAY STANDARDS AND GENERAL NOTES		68	(102) BR-1	LIVINGSTON	58	2		
				CONTRACT	NO. 6	6822		
SHEET NO 1 OF 1 SHEETS ST	TA TO STA	THE IMPLEMENTAL AND PROJECT						