GENERAL NOTES

BRIDGE APPROACH PAVEMENT REMOVAL SHALL BE INCLUDED IN THE COST OF "PAVEMENT REMOVAL".

THE THICKNESS OF HMA SHOWN ON THE PLANS IS THE NOMINAL THICKNESS. DEVIATIONS FROM THE NOMINAL THICKNESS WILL BE PERMITTED WHEN SUCH DEVIATIONS OCCUR DUE TO IRREGULARITIES IN THE EXISTING SURFACE OR BASE ON WHICH THE HMA IS PLACED.

EXCEPT AS NOTED ON THE PLANS, PAVEMENT GRADES SHOWN ARE AT THE TOP OF PAVEMENT SURFACES.

THE ENGINEER WILL BE THE SOLE JUDGE CONCERNING CURING TIME FOR THE VARIOUS HMA LIFTS.

FOR STABILIZATION, ALL TYPE III BARRICADES SHALL REQUIRE A MINIMUM OF FOUR SAND BAGS PER BARRICADE.

SEEDING SHALL NOT BE PERMITTED AT ANY TIME WHEN THE GROUND IS FROZEN, WET, OR IN AN UNTILLABLE CONDITION. LOCATIONS TO BE SEEDED WILL BE DETERMINED BY THE ENGINEER.

ONLY THOSE TREES DESIGNATED BY THE ENGINEER OR LISTED IN THE TREE REMOVAL SCHEDULE SHALL BE REMOVED. THE CONTRACTOR SHALL PROTECT ALL REMAINING TREES FROM DAMAGE DUE TO HIS OPERATIONS.

THE FINISHED EARTHWORK SHALL HAVE A VEGETATION SUSTAINING SOIL COVERING THE TOP FOUR INCHES IN AREAS TO BE SEEDED OR SODDED. THE VEGETATION SUSTAINING SOIL REQUIRED WILL NOT BE PAID FOR SEPARATELY BUT SHALL BE INCLUDED IN THE COST OF "FURNISHED EXCAVATION".

ON EXISTING PAVEMENT WHICH MAY BE SUPERELEVATED, THE NEW HMA PAVEMENT SHALL BE BUILT WITH THE SAME SUPERELEVATION UNLESS NEW SUPERELEVATION RATES ARE GIVEN ON THE PLANS.

ALL ELEVATIONS REFER TO U.S.G.S. MEAN SEA LEVEL DATUM.

ABANDONED UNDERGROUND UTILITIES THAT CONFLICT WITH CONSTRUCTION SHALL BE DISPOSED OF OUTSIDE THE LIMITS OF THE RIGHT OF WAY ACCORDING TO ARTICLE 202.03 OF THE STANDARD SPECIFICATIONS AND AS DIRECTED BY THE ENGINEER. THIS WORK WILL NOT BE PAID FOR SEPARATELY, BUT SHALL BE INCLUDED IN THE COST OF EARTH EXCAVATION.

ANY REFERENCE TO A STANDARD IN THESE PLANS SHALL BE INTERPRETED TO MEAN THE EDITION AS INDICATED BY THE SUBNUMBER SHOWN IN THE LIST OF STANDARDS OR THE COPY INCLUDED IN THESE PLANS.

THE FOLLOWING RATES OF APPLICATION HAVE BEEN USED IN CALCULATING PLAN QUANTITIES:

	GRANULAR MATERIALS	2.05	TONS / CL! YD	
	BIT MATERIALS (PRIME COAT)	0.375	GAL / SQ YD	
	ON AGGREGATE BASES	0.375	GAL / SU TD	
	BITUMINOUS MATERIALS	0.08	GAL / SQ YD	
	(PRIME COAT)	0.08	GAL / SQ TD	
	FOR ADDITIONAL HMA LIFTS	0.05	GAL / SQ YD	
	"FOG COAT"	0.05	GAL / SU ID	
	AGGREGATE PRIME COAT	0.002	TONS / SQ YD	
	HMA RESURFACING	112	LBS / SQ YD / IN	
	SHORT TERM PAVEMENT MARKING	10	FT /100 FT OF APPLICATION	
	MIX FOR CRACKS, JTS & FLGWYS	0.0003	TONS / SQ YD	
	LEVEL BINDER (HAND METHOD)	0.0005	TONS / SQ YD	
	SUPPLEMENTAL WATERING	3	GAL / SQ YD / APPLICATION	
	CALCIUM CHLORIDE	2	LB / SQ YD / APPLICATION	
	TEMPORARY DITCH CHECKS	5	TONS AGGREGATE	

THE WORK REQUIRED TO CONNECT ANY SEWER TO AN EXISTING DRAINAGE STRUCTURE OR PIPE WILL NOT BE PAID FOR SEPARATELY, BUT SHALL BE CONSIDERED AS INCLUDED IN THE CONTRACT UNIT PRICE BID FOR THE SEWER ITEMS.

MEMBERS OF JULIE KNOWN TO BE WITHIN THE LIMITS OF THE IMPROVEMENT

- 1. AMEREN CIPS
 2. AT&T
 3. MEDIA COM
 4. NICOR GAS CO
 5. VERIZON
 6. VILLAGE OF FO AI&I MEDIA COM NICOR GAS COMPANY VERIZON VILLAGE OF FORREST

COMMITMENTS

COMMITMENTS ARE NOT TO BE ALTERED WITHOUT THE WRITTEN APPROVAL OF ALL PARTIES TO WHICH THE COMMITMENT WAS MADE.

- 1. THE PROPOSED TEMPORARY EASEMENT IS NOT TO BE USED FOR PARKING OR STORAGE OF CONSTRUCTION MATERIALS OR EQUIPMENT WITHOUT THE EXPRESS CONSENT OF THE PROPERTY OWNER.
- 2. THE SLOPE AND SWALE BETWEEN THE CURB AND THE RIGHT OF WAY BETWEEN THE ENTRANCE AT STA 476+97 LT AND THE ENTRANCE AT STA 478+34.8 LT WILL BE PAVED AS A PAVED DITCH TO ALLOW FOR EASE OF MAINTENANCE AND IMPROVED DRAINAGE.
- 3. THE SIDEWALK ON PRIVATE PROPERTY WILL BE REMOVED FROM STA 476+12 LT TO STA 476+55 LT AND A NEW SIDEWALK WILL BE PLACED FROM STA 476+12 LT TO THE PROPOSED COMMERCIAL ENTRANCE AT STA 476+97 LT. THE WALK SHALL BE SLOPED TOWARDS THE ROADWAY DITCH.
- 4. AN EROSION CONTROL FENCE WILL BE PLACED FROM STA 470+00, 52.8' LT TO STA 473+00, 67.8' LT PRIOR TO CONSTRUCTION TO ENSURE THAT CONSTRUCTION ACTIVITIES DO NOT ENCROACH UPON THE WETLAND.

HIGHWAY STANDARDS

000001-05	STANDARD SYMBOLS, ABBREVIATIONS AND PATTERNS
001001-02	AREAS OF REINFORCEMENT BARS
001006	DECIMAL OF AN INCH AND OF A FOOT
280001-05	TEMPORARY EROSION CONTROL SYSTEMS
420401-08	BRIDGE APPROACH PAVEMENT CONNECTOR
515001-03	NAME PLATE FOR BRIDGES
601101-01	CONCRETE HEADWALL FOR PIPE DRAIN
602301-02	INLET - TYPE A
602401-02	MANHOLE TYPE A
602701-02	MANHOLE STEPS
604001-03	FRAME AND LIDS TYPE 1
604006-04	FRAME AND GRATE TYPE 3
604036-02	GRATE TYPE 8
606001-04	CONCRETE CURB TYPE B AND COMBINATION CONCRETE CURB AND GUTTER
606006-02	OUTLETS FOR CONC. CURB AND GUTTER TYPE B-6.24 (B-15.60)
630001-08	STEEL PLATE BEAM GUARDRAIL
630201-06	PCC/HMA STABILIZATION AT STEEL PLATE BEAM GUARDRAIL
630301-05	SHOULDER WIDENING FOR TYPE 1 (SPECIAL) GUARDRAIL TERMINALS
631031-08	TRAFFIC BARRIER TERMINAL, TYPE 6
635006-03	REFLECTOR AND TERMINAL MARKER PLACEMENT
635011-02	REFLECTOR MARKER AND MOUNTING DETAILS
666001-01	RIGHT OF WAY MARKERS
701001-02	OFF-RD OPERATIONS, 2L, 2W, MORE THAN 15' (4.5m) AWAY
701006-03	OFF-RD OPERATIONS, 2L, 2W, 15' (4.5 m) TO 2' (600 mm) FROM
	PAVEMENT EDGE
701011-02	OFF-RD MOVING OPERATIONS, 2L, 2W, DAY ONLY
701301-03	LANE CLOSURE, 2L, 2W, SHORT TIME OPERATIONS
701311-03	LANE CLOSURE 2L, 2W MOVING OPERATIONS-DAY ONLY
701321-10	LANE CLOSURE, 2L, 2W, BRIDGE REPAIR WITH BARRIER
701501-05	URBAN LANE CLOSURE, 2L, 2W, UNDIVIDED
701901-01	TRAFFIC CONTROL DEVICES
704001-06	TEMPORARY CONCRETE BARRIER
781001-03	TYPICAL APPLICATIONS RAISED REFLECTIVE PAVEMENT MARKERS

DEPARTMENT OF ILLINOIS DEPARTMENT OF TRANSPORTATION DISTRICT THREE	
REVIEWED BY: Dres Beaut	-
ACTING DISTRICT STUDIES & PLANS ENGINEER	
DATE: 08/17/10	_
EXAMINED BY: Herbert Lang	
DISTRICT CONSTRUCTION ENGINEER	•
Naw 2 Mellin	
DISTRICT MATERIALS ENGINEER	-
Some a Bucken	
DISTRICT OPERATIONS ENGINEER	-

FILE NAME =	USER NAME = \$USER\$	DESIGNED -	JML	REVISED -		
\$FILEL\$		DRAWN -	110	REVISED -		
+ 1	PLOT SCALE = \$SCALE\$	CHECKED -	MSW	REVISED -		
	PLOT DATE = \$DATE\$	DATE -	08/13/10	REVISED -		

SCALE: