

STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION



INSTALLATION AND SETTING METHODS

"A" : Set bar splicer assembly by means of a template bolt. "B" : Set bar splicer assembly by nailing to wood forms or (E) : Indicates epoxy coating.



6'-0''



STANDARD MECHANICAL SPLICER

Location	Bar size	No. assemblies required		
		-		

NOTES

Splicer bars shall be deformed with threaded ends and have a minimum 60 ksi yield strength.

All reinforcement shall be lapped and tied to the splicer bars. Bar splicer assemblies shall be epoxy coated according to the requirements for reinforcement bars. See Section 508 of the Standard Specifications. See special provision for Mechanical Splicers. See approved list of bar splicer assemblies and mechanical splicers for

alternatives.

BAR SPLICER AND ASSEMBLY	<u>DETAILS</u>
<u>S.N. 090-0177</u>	
STRAND ASSOCIATES,	INC.

SHEET NO. 19		F.A.P. RTE.	SECTION		COUNTY	TOTAL SHEETS	SHEET NO.	
		693	(119	BR-2)BR		TAZEWELL	65	36
22 S	HEETS					CONTRACT	NO. 68	660
		FED. ROAD DIST. NO. ILLINOIS FED. AID PROJECT						