

TYPE I ELASTOMERIC EXP. BRG.



BEARING ASSEMBLY

Note: Shim plates shall not be placed under Bearing Assembly.



Notes: Anchor bolts shall be ASTM F1554 all-thread (or an Engineer-approved alternate material) of the grade(s) and diameter(s) specified. ASTM A307 Grade C anchor bolts may be used in lieu of ASTM F1554 Grade 36 (Fy=36ksi). The corresponding specified grade of AASHTO M314 anchor bolts may be used in lieu of ASTM F1554.

Anchor bolts at fixed bearings may be either cast in place or installed in holes drilled after the supported member is in place.

Anchor bolts for side retainers may be cast in place or installed in holes drilled before or after members are in place.

Drilled and set anchor bolts shall be installed according to Article 521.06 of the Standard Specifications.

Side retainers and other steel members required for the bearing assembly shall be included in the cost of

Elastomeric Bearing Assembly, Type I. Two $^{I}_{B}$ in adjusting shims shall be provided for each bearing in addition to all other plates or shims and placed as shown on bearing details.

The structural steel plates of the Bearing Assembly shall conform to the requirements of AASHTO M 270 Grade 50.







Johnson, Depp & Quisenberry CONSULTING ENGINEERS Springfield, Illinois					
DESIGNED:	DCD	DRAWN:	SJS		
CHECKED:	CMV	CHECKED:	CMV/DCD		
I-2E-1		11-1-09			



SECTION B-B

FIXED BEARING

BILL	0F	MATERIAL

Item	Unit	Total
Elastomeric Bearing Assembly Type I	Each	6
Anchor Bolts, 1 ¹ 2"	Each	24

BEARING DETAILS - PIERS STRUCTURE NO. 057-0250

SHEET 17 OF 27	F.A.I. RTE.	SECTION			COUNTY	TOTAL SHEETS	SHEET NO.
	55	(57-7HB-1)BR			MCLEAN	153	67
		STA. 626+53.70			CONTRACT	NO. 7	0520
	FED. RC	AD DIST. NO.	ILLINOIS FED.	AIC	PROJECT		