

Σ

11:18:30

2010

10/19/

ANSAMISCELI

٩

BRIDGE

@21~M01@_1L1@1_L

45

0602

06611



INSTALLATION AND SETTING METHODS

"A" : Set bar splicer assembly by means of a template bolt. "B" : Set bar splicer assembly by nailing to wood forms or cementing to steel forms. (E) : Indicates epoxy coating.

3



yield strenath. alternatives.

> SHEET NO.3 45 SHEETS

Mechanical coupler (E) ***** Reinforcement bar - Reinforcement bar

STANDARD MECHANICAL SPLICER



<u>NOTES</u>

Splicer bars shall be deformed with threaded ends and have a minimum 60 ksi

All reinforcement shall be lapped and tied to the splicer bars. Bar splicer assemblies shall be epoxy coated according to the requirements for reinforcement bars. See Section 508 of the Standard Specifications. See special provision for Mechanical Splicers.

See approved list of bar splicer assemblies and mechanical splicers for

		<u>S.N.</u>	085-0514		
36	F.A.P RTE	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
	713	120B-3	SCHUYLER	75	56
			CONTRACT	NO. 72	2A03
	FED. RC	AD DIST. NO ILLINOIS FED. AI	D PROJECT		
DL			Klingner d	& Associa	tes P.C.

BAR SPLICER ASSEMBLY DETAILS