



**SYMBOLS**

- ↑ ARROW BOARD
- ☐ PORTABLE CHANGEABLE MESSAGE SIGN
- ⊥ SIGN
- ⊕ TYPE II BARRICADE, DRUM, OR VERTICAL BARRICADE WITH MONODIRECTIONAL FLASHING LIGHT

SEE STANDARD 701400-04 FOR COMPLETE SIGN DETAILS

•SEE STANDARD 701400-02 + 701401-04 + 701406-04 FOR SOUTH BOUND I-55 TRAFFIC CONTROL

LANE CLOSURE TAPER  
SEE IDOT STANDARD DRAWING 701402-06 & 701411-04 FOR TRAFFIC CONTROL DEVICE PLACEMENT

LANE CLOSURE TAPER, SEE IDOT STANDARD DRAWING 701402-06 & 701411-04 FOR TRAFFIC CONTROL DEVICE PLACEMENT

**GENERAL NOTES**

STANDARD 701400-04 IS USED WHERE AT ANY TIME A LANE IS CLOSED ON A FREEWAY/EXPRESSWAY. WHEN THE LEFT LANE IS CLOSED, LEFT LANE CLOSED SIGNS SHALL BE SUBSTITUTED FOR THE RIGHT LANE CLOSED SIGN.

THE FIRST TWO SIGNS AND THE MESSAGE BOARD ARE STATIONARY.

THE LAST FOUR SIGNS AND ARROWBOARD SHALL BE MOVED AS NECESSARY TO MAINTAIN THE REQUIRED DISTANCE FROM THE START OF THE LANE CLOSURE TAPER(S).

- ① THE ROAD CONSTRUCTION AHEAD SIGN SHALL BE LOCATED 3 TO 5 MILES IN ADVANCE OF THE PROJECT LIMITS.
- ② THE MESSAGE AND SIZE OF THE WORK ZONE PUBLIC INFORMATION SIGN SHALL BE AS SPECIFIED BY THE DEPARTMENT.
- ③ IDOT WILL PROVIDE INFORMATION FOR TRAFFIC WARNING MESSAGES.
- ④ THREE, TYPE II BARRICADES, DRUMS, OR VERTICAL BARRICADES AT 50' CENTERS.

WORK ZONE	
SPEED LIMIT	W2-1115(0)-3618
<b>45</b>	R2-1-3648
BEGINS	W2-1113(0)-3612
\$375 FINE MINIMUM	R2-1106-3618

FILE NAME =	USER NAME = laughl1nr1	DESIGNED - LLO	REVISED -
et:\pwork\pwork\dot\laughl1nr1\0231206\062A64-sh1-mot.dgn		DRAWN - JJS	REVISED -
		CHECKED - MTM	REVISED -
		DATE - JANUARY 2010	REVISED -

**STATE OF ILLINOIS  
DEPARTMENT OF TRANSPORTATION**

**I-72 ADVANCED WARNING AND MAINTENANCE OF TRAFFIC**

SCALE: SHEET NO. 4 OF 4 SHEETS STA. TO STA.

F.A.I R.T.E.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
72	(84-3HB-5)BR	SANGAMON	84	25
S.N. 084-0078		CONTRACT NO. 72C70		
FED. ROAD DIST. NO. 6 ILLINOIS FED. AID PROJECT				