

TYPE I ELASTOMERIC EXP. BRG.



BEARING ASSEMBLY Shim plates shall not be placed under Bearing Assembly.



Anchor bolts shall be ASTM F1554 all-thread (or an Engineer-approved alternate material) of the grade(s) and diameter(s) specified. ASTM A307 Grade C anchor bolts may be used in lieu of ASTM F1554 Grade 36 (Fy=36ksi). The corresponding specified grade of AASHTO M314 anchor bolts may be used in lieu of ASTM F1554.

Anchor bolts at fixed bearings may be either cast in place or installed in holes drilled after the supported member is in place.

Anchor bolts for side retainers may be cast in place or installed in holes drilled before or after members are in place.

Drilled and set anchor bolts shall be installed according to Article 521.06 of the Standard Specifications. Side retainers and other steel members required for

the bearing assembly shall be included in the cost of Elastomeric Bearing Assembly, Type I.

The structural steel plates of the Bearing Assembly shall conform to the requirements of AASHTO M 270 Grade 50. Two l_{B} in. adjusting shims shall be provided for each bearing

in addition to all other plates or shims and placed as shown on bearing details.

See Sheet 28 of 43 for Shim Plate Schedule.







SIDE RETAINER N. ABUT. Equivalent rolled angle with stiffeners will be allowed in lieu of welded plates.





Equivalent rolled angle with stiffeners will be allowed in lieu of welded plates.

