




/ - SEAL GVERLAP OF POLYETHYLENE TUBE WRAP











GENERAL NOTES: CIRCUMSTERENTIAL WRAPS OF PLASTIC THE STRAPS SHOULD BE PLACED AT NO STRATER THAN FOUR FOOT INTERVALS ALONG THE BARREL OF THE

PIPE WIL THE EXCESS FOLDED OVER TOP TO TAKE OUT EXCESS SLACK HELDING TO MAININGE THE SPACE BETWEEN THE FOLYEDINGEN AND THE PIPE, COMMELTE THE ESTALLATION BY OVERLAPPING THE POLYEDINENE TUBS WARP AT LACH END AND SEAL ENDS WITE PLASTIC THE WIREPS. (PER NAWA COS)

FOR DUCTILE IRON PIPE

PLASTIC TIE

DRAWN BY SAG CHECKED BY DWB

CONTRACT NO. 63049 COUNTY TOTAL SHEE SHEETS NO.

129 96

F.A.P. SECTION

STA.

MASG

EXISTING HYDRANT---(TO BE REMOVED)

EXISTING VALVE BOX (TO BE REMOVED)

EXISTING AUXILIARY GATE-VALVE (TO BE ABANDONE IN CLOSED FOSITION)

350 00-00242-00-CH COOK

TO STA.

FED. ROAD DIST. NO. 7 ILLINOIS FED. AID PROJECT