
HOT-MIX ASPHALT MIXTURE REQUIREMENTS NOTES:

1. CONTRACTOR SHALL MILL BEFORE PATCHING.


HOT-MIX ASPHALT MIXTURE REQUIREMENTS

MIXTURE TYPE	VOIDS
RESURFACING	
HOT-MIX ASPHALT SURFACE COURSE, MIX "C", N50 (IL 9,5mm); 2"	4% @ 50 GYR.
PATCHING	
CLASS D PATCHES (HMA BINDER IL-19 mm); TYPE II - IV - 7-INCH	4% @ 70 GYR.
DRIVEWAYS	
HOT-MIX ASPHALT SURFACE COURSE, MIX "C", N50 (IL 9.5 mm); 2"	4% @ 50 GYR.

THE UNIT WEIGHT USED TO CALCULATE ALL HOT-MIX ASPHALT SURFACE MIXTURES IS 112 LBS/SQ. YD./IN FOR "AC TYPE" AND "PERCENT RAP" SEE DISTRICT ONE SPECIAL PROVISIONS.



EXISTING TYPICAL SECTION ALGONQUIN ROAD STA. 17 + 75 TO STA. 50 + 86



PROPOSED TYPICAL SECTION **ALGONQUIN ROAD** STA. 17 + 75 TO STA. 50 + 86

EXISTING LEGEND

HOT-MIX ASPHALT SURFACE COURSE, 1 1/2" AREA REFLECTIVE CRACK CONTROL TREATMENT (PETROMAT) HOT-MIX ASPHALT SURFACE COURSE, 1" HOT-MIX ASPHALT BINDER COURSE, 5" AGGREGATE BASE COURSE, 10"± AGGREGATE SHOULDER, 4"± SIDEWALK AGGREGATE BASE COURSE EXISTING SUB-GRADE GROUND SURFACE HOT-MIX ASPHALT SURFACE REMOVAL, 2" AGGREGATE SHOULDER REMOVAL, 2" (INCLUDED IN THE COST OF HMA SURFACE REMOVAL, 2")

SCALE: NONE

PROPOSED LEGEND

- HOT-MIX ASPHALT SURFACE COURSE, MIX "C", N50 2"
- CLASS D PATCHES, TYPE II IV, 7-INCH
- AGGREGATE WEDGE SHOULDER, TYPE B

LEGEND NOTES:

ITEM TO BE REMOVED

- SIDEWALK REMOVAL AND REPLACEMENT TO BE DETERMINED BY THE ENGINEER, UNLESS OTHERWISE SHOWN.
- CURB AND GUTTER REMOVAL AND REPLACEMENT TO BE DETERMINED BY THE ENGINEER, UNLESS OTHERWISE SHOWN.

DESIGNED - MWP	REVISED - IDOT REVIEW 06-01-09
DRAWN - KAR	REVISED - IDOT REVIEW 08-03-09
CHECKED - RWL	REVISED -
DATE - 04-15-09	FILE - 090225-TYP.sht

VILLAGE OF FOX RIVER GROVE, ILLINOIS ALGONQUIN ROAD ARRA (LAPP) **IMPROVEMENTS**

SECTION COUNTY TYPICAL SECTIONS AND 09-00022-00-RS 3878 HMA MIXTURE REQUIREMENTS CONTRACT NO. 63277 FED. ROAD DIST. NO. C-91-622-09 STA. TO STA.