

TYPE I ELASTOMERIC EXP. BRG.



BEARING ASSEMBLY

Note: Shim plates shall not be placed under Bearing Assembly.

Notes:

Anchor bolts shall be ASTM F1554 all-thread (or an Engineer-approved alternate material) of the grade(s) and diameter(s) specified. ASTM A307 Grade C anchor bolts may be used in lieu of ASTM F1554 Grade 36 (Fy=36ksi). The corresponding specified grade of AASHTO M314 anchor bolts may be used in lieu of ASTM F1554.

Anchor bolts at fixed bearings may be either cast in place or installed in holes drilled after the supported member is in place.

Anchor bolts for side retainers may be cast in place or installed in holes drilled before or after members are in place.

Drilled and set anchor bolts shall be installed according to Article 521.06 of the Standard Specifications.

Side retainers and other steel members required for the W. Abut. bearing assembly shall be included in the cost of Elastomeric Bearing Assembly, Type I.

Two $l_{\mathcal{B}}$ in. adjusting shims shall be provided for each bearing in addition to all other plates or shims and placed as shown on bearing details.

1⁵8" Ø

PINTLE





(Interior Girders) (26 reg'd.)

SIDE RETAINERS (W. ABUTS)

Equivalent rolled angle with stiffeners



07004 SCALE COOMBE-BLOXDORF P.C. SHEET NO 0RAWN BY Engineers / Land Surveyors CHECKED BY RM/MCB Springfield, Illinois 59 SHE Design Firm License No. 184-002703



I-2E-1 10-1-08

= CFC_

NAME

SER

SECTION B-B

FIXED BEARING

BILL OF MATERIAL

Item	Unit	Total		
Elastomeric Bearing Assembly Type I	Each	17		
Anchor Bolts, 1'2" \$	Each	34		
Anchor Bolts, 1" Ø	Each	42		

BEARING DETAILS <u>STRUCTURE_NO. 082-0162 (E.B.)</u> STRUCTURE NO. 082-0163 (W.B.)

												_	
0. 35	F.A.I RTE.	A.I. SECTION							COUNTY		TOTAL SHEETS		SHEET NO.
0. 00	64 82-2VB					ST. CLAIR 153			90				
ETS								1	CON	TRACT	NO. 7	'6	867
	FED.	ROAD	DIST.	N0.	7	ILLINOIS	FED.	AID	PRO	JECT			