<u>NOTES</u>

- 1. TYPE III BARRICADES AND ROAD CLOSURE SIGNS SHALL BE POSITIONED AS SHOWN, IN ACCORDANCE WITH HIGHWAY STANDARD 701901 AND AS DIRECTED BY THE ENGINEER.
- 2. TYPE A LOW INTENSITY FLASHING WARNING LIGHTS SHALL BE USED ON EACH SIGN IN ADVANCE OF THE WORK DURING HOURS OF DARKNESS.
- 3. ALL WARNING SIGNS SHALL BE A MINIMUM OF 48" x 48" AND HAVE A BLACK LEGEND AND BORDER ON A FLUORESCENT ORANGE REFLECTORIZED BACKGROUND.
- 4. THE CONTRACTOR SHALL MAINTAIN ACCESS TO ENTRANCES AT ALL TIMES.
- 5. LONGITUDINAL DISTANCES MAY BE ADJUSTED TO FIT FIELD CONDITIONS.
- 6. ALL TYPE III BARRICADES UTILIZED FOR ROAD CLOSURES SHALL HAVE A LOW INTENSITY FLASHING LIGHT MOUNTED ON TOP OF EACH BARRICADE.
- EXACT LOCATION OF ALL WARNING SIGNS AND BARRICADES SHALL BE STAKED IN THE FIELD FOR APPROVAL BY THE ENGINEER PRIOR TO INSTALLATION.
- 8. ALL RESIDENTS FRONTING THE PROJECT SHALL BE NOTIFIED AT LEAST 48 HOURS PRIOR TO ROAD CLOSURES AFFECTING THEIR ACCESS.
- 9. SEE HIGHWAY STANDARD 701501 AND 701701 FOR LANE CLOSURES ON IL ROUTE 13 AND WEST MAIN STREET, RESPECTIVELY.

LEGEND

- W20-3(0)-48 (ROAD CLOSED AHEAD)
- 2 W20-1(0)-48 (ROAD CONSTRUCTION AHEAD)
- TYPE III BARRICADES W/ R-11-2-4830 (ROAD CLOSED) SIGN AND TYPE A LOW INTENSITY FLASHING LIGHTS
- 4 24" x 24"

"H" ST

"E" ST

"D"

AVE

/ADAMS

STA 54+50

LINCOLN ST

ST

-(1) STA 56+50

STA 109+00

STA 41+25 2

STA 111+00

STA 81+00

STA 83+00

17TH ST

×STA 43+25//℅

(1) (2) ISTH 4

5 24" × 24"

7


6 24" × 24"

1

7 W16-8(0)-1808 (ALL 4" LETTERS) 17TH ST

WORK ZONE

TYPE A LOW INTENSITY FLASHING LIGHT



180

PROPOSED 17TH ST EXTENSION

NOT TO SCALE

DATE NAME SCALE NAME PLOT PLOT USER

TRAFFIC CONTROL