





## GENERAL NOTES:

- 1. BOTH THE TRENCH AND DRAIN TILE SHALL BE WRAPPED WITH NON-WOVEN GEOTEXTILE FILTER FABRIC.
- 2. WASHED AGGREGATE SHALL BE PLACED AROUND THE DRAIN TILE.
- 3. HOLE SHALL BE DRILLED INTO STRUCTURE.
- 4. HYDRAULIC CEMENT SHALL BE PLACED AROUND THE PIPE TO SEAL THE OPENING, BOTH INSIDE AND OUTSIDE THE STRUCTURE.

PIPE UNDERDRAIN, FABRIC LINED TRENCH, 4"

| CONTRACT NO. 63055 | F.A.U. | SECTION | COUNTY | TOTAL SHEET | NO. 1346 & O. 00050-00-CH | COOK/DUPAGE | 94 | 61 | O. 00050-00-CH | COOK/DUPAGE | F.D. ROAD DIST. NO. 7 | ILLINOIS | F.D. AID | PROJECT | M-8003(569)

ILLINOIS DEPARTMENT OF TRANSPORTATION

ROADWAY DETAILS

DATE: 5/27/08
DESIGNED BY: KRK
LE CHECKED BY: DJK

NOT TO SCALE