

**STATE OF ILLINOIS**  
**DEPARTMENT OF TRANSPORTATION**

F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
876	2025-1093-RS	COOK	33	1
		ILLINOIS	CONTRACT NO. 80B19	

FOR INDEX OF SHEETS, SEE SHEET NO. 2

**THE PROJECT IS LOCATED IN:  
THE VILLAGES OF GLENWOOD  
& HOMEWOOD**


**TRAFFIC DATA:**  
ADT = 34,900 (2023)

**POSTED SPEED LIMIT = 35 & 40 MPH**

**DESIGN DESIGNATION = OTHER PRINCIPAL ARTERIAL**

**PROPOSED  
HIGHWAY PLANS**  
**FAP ROUTE 876: IL 1 (HALSTED STREET)**  
**SOUTH OF RIDGE ROAD TO STRIEFF LANE**  
**SECTION: 2025-1093-RS**  
**PROJECT: NHPP-WWFK(227)**  
**STANDARD OVERLAY & ADA IMPROVEMENTS**  
**COOK COUNTY**

**C-91-252-25**




FULL SIZE PLANS HAVE BEEN PREPARED USING STANDARD ENGINEERING SCALES. REDUCED SIZED PLANS WILL NOT CONFORM TO STANDARD SCALES. IN MAKING MEASUREMENTS ON REDUCED PLANS, THE ABOVE SCALES MAY BE USED.

**J.U.L.I.E.**  
**JOINT UTILITY LOCATION INFORMATION FOR EXCAVATION**  
**1-800-892-0123**  
**OR 811**

**PROJECT ENGINEER: DANIEL WILGREEN, P.E. (847)-705-4240**  
**PROJECT MANAGER: J. ALAIN MIDY, P.E. (847)-221-3063**

**CONTRACT NO. 80B19**



**BLOOM & THORNTON TOWNSHIP**

GROSS LENGTH = 3,512 FT. = 0.67 MILES  
NET LENGTH = 3,405 FT. = 0.64 MILE

**STATE OF ILLINOIS**  
**DEPARTMENT OF TRANSPORTATION**

SUBMITTED Aug 11<sup>th</sup> 2025 Joseph IR REGIONAL ENGINEER

October 3, 2025 Scott A. Etk ENGINEER OF DESIGN AND ENVIRONMENT

October 3, 2025 Cherry 5 DIRECTOR OF HIGHWAYS PROJECT IMPLEMENTATION

**PRINTED BY THE AUTHORITY  
OF THE STATE OF ILLINOIS**



MODEL: FINAL\_SOO\_1 [Sheet]  
FILE NAME: c:\ppl\_work\pwwid\hamwi\md1063787\ID117225-shh-SOQ.dgn

SUMMARY OF QUANTITIES					TYPE      CODE					
					IL-1 COOK	IL-1 COOK	IL-1 COOK			
					ROADWAY	ROADWAY	APS SIGNALS			
					80% FED 20% STATE	100% STATE	80% FED 20% STATE			
	CODE NO.	ITEM	UNIT	TOTAL QUANTITY	0005	0005	0021			
	20200100	EARTH EXCAVATION	CU YD	20	20					
	21101615	TOPSOIL FURNISH AND PLACE, 4"	SQ YD	122	122					
	25000400	NITROGEN FERTILIZER NUTRIENT	POUND	1	1					
	25000500	PHOSPHORUS FERTILIZER NUTRIENT	POUND	1	1					
	25000600	POTASSIUM FERTILIZER NUTRIENT	POUND	1	1					
	25200110	SODDING, SALT TOLERANT	SQ YD	126	126					
	25200200	SUPPLEMENTAL WATERING	UNIT	0.8	0.8					
	35101600	AGGREGATE BASE COURSE, TYPE B 4"	SQ YD	10	10					
	40600290	BITUMINOUS MATERIALS (TACK COAT)	POUND	17368	17368					
	40600370	LONGITUDINAL JOINT SEALANT	FOOT	13713	13713					
	40600400	MIXTURE FOR CRACKS, JOINTS, AND FLANGEWAYS	TON	39	39					
	40600982	HOT-MIX ASPHALT SURFACE REMOVAL - BUTT JOINT	SQ YD	218	218					
	40601005	HOT-MIX ASPHALT REPLACEMENT OVER PATCHES	TON	86	86					
	40603200	POLYMERIZED HOT-MIX ASPHALT BINDER COURSE, IL-4.75, N50	TON	1053	1053					
	40605026	POLYMERIZED HOT-MIX ASPHALT SURFACE COURSE, STONE MATRIX ASPHALT, 9.5, MIX "F", N80	TON	2501	2501					
	42001300	PROTECTIVE COAT	SQ YD	415	415					
	42400200	PORTLAND CEMENT CONCRETE SIDEWALK 5 INCH	SQ FT	1320	1320					
	42400800	DETECTABLE WARNINGS	SQ FT	100	100					
	44000159	HOT-MIX ASPHALT SURFACE REMOVAL, 2 1/2"	SQ YD	25511	25511					
	44000600	SIDEWALK REMOVAL	SQ FT	1485	1485					
	44002216	HOT-MIX ASPHALT REMOVAL OVER PATCHES, 4"	SQ YD	380	380					
✱ = SPECIALTY ITEM										
		USER NAME    = mohammad.hamwi	DESIGNED   -	REVISED   -	STATE OF I DEPARTMENT OF TR					
			DRAWN       -	REVISED   -						
			CHECKED   -	REVISED   -						
		PLOT DATE     = 8/14/2025	DATE          -	REVISED   -						

MODEL: FINAL SOQ 2 [Sheet]  
FILE NAME: c:\pw work\pwidot\hamwim\d1063787\D117225-sht-SOQ.dgn


\* = SPECIALTY ITEM



[illegible][illegible]

LEGEND - EXISTING

- ① PORTLAND CEMENT CONCRETE PAVEMENT ±9"
- ② HOT MIX ASPHALT PAVEMENT ±4"
- ③ EXISTING CURB AND GUTTER




EXISTING TYPICAL SECTION

STATION:  
14+56 TO 49+68

LEGEND - PROPOSED

- ④ POLYMERIZED HOT-MIX ASPHALT SURFACE COURSE, SMA, 9.5, MIX "F", N80, 1 3/4"
- ⑤ POLYMERIZED HOT-MIX ASPHALT BINDER COURSE, IL-4.75, N50, 3/4"
- ⑥ COMBINATION CURB & GUTTER (REMOVAL & REPLACEMENT DETERMINED BY RE)



PROPOSED TYPICAL SECTION

STATION:  
14+56 TO 49+68

LOCATION	HOT-MIX ASPHALT MIXTURE REQUIREMENTS		QUALITY MANAGEMENT PROGRAM (QMP)
	MIXTURE TYPE	AIR VOIDS @ Ndesign	
	PAVEMENT RESURFACING		
IL-1	POLYMERIZED HMA SURFACE COURSE, STONE MIX ASPHALT, 9.5 MIX "F", N80 1¾"	3.5% @ 80 GYR	QCP
IL-1	POLYMERIZED HMA BINDER COURSE, IL-4.75, N50, ¾"	3.5% @ 50 GYR	QC/QA
	PATCHING		
IL-1	CLASS D PATCHES (HMA BINDER IL-19.0 MM: 9")	4% @ 70 GYR	QC/QA
IL-1	HMA REPLACEMENT OVER PATCHES (HMA BINDER IL-19.0)	4% @ 70 GYR	QC/QA
QMP DESIGNATIONS: QUALITY CONTROL/QUALITY ASSURANCE (QC/QA); QUALITY CONTROL FOR PERFORMANCE (QCP); PAY FOR PERFORMANCE (PFP)			



NOTES:

- THE UNIT WEIGHT USED TO CALCULATE ALL HMA SURFACE COURSE MIXTURES IS 112 LBS/SQYD/IN.
- THE "AC TYPE" FOR POLYMERIZED HMA MIXES SHALL BE "SBS/SBR PG 76-22" AND FOR NON-POLYMERIZED HMA THE "AC TYPE" SHALL BE "PG 64-22" UNLESS MODIFIED BY RECLAIMED MATERIALS SPECIFICATIONS.
- THE LONGITUDINAL JOINT SEALANT SHALL BE PLACED ON THE POLYMERIZED HMA BC IL-4.75 N50
- THE CONTRACTOR SHALL PATCH THEN MILL.

MODEL: Typical Section [Sheet]  
FILE NAME: c:\pawork\pawork\hamw\md1063787\ID117225-shh-typical.dgn


	USER NAME = mohammad.hamwi	DESIGNED -	REVISED -	STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION	TYPICAL SECTION IL-1 (HALSTED ST) FROM SOUTH OF RIDGE RD TO STRIEFF LN			F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
		DRAWN -	REVISED -					876	2025-1093-RS	COOK	33	6
		CHECKED -	REVISED -					CONTRACT NO. 80B19				
	PLOT DATE = 8/9/2025	DATE -	REVISED -		SCALE:	SHEET 1	OF 1 SHEETS	STA.	TO STA.	ILLINOIS FED. AID PROJECT		

MODEL: Excl - Plan 1 (Sheet)  
FILE NAME: c:\pwworking\hamw\m\1063787\1017225-shh-plan.dgn



STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION				ROADWAY PLAN IL-1 (HALSTED ST) FROM SOUTH OF RIDGE RD TO STRIEFF LN				F.A.P. RTE. 876		SECTION 2025-1093-RS	COUNTY COOK	TOTAL SHEETS 33	SHEET NO. 7
SCALE: 1"=50'				SHEET 1 OF 2 SHEETS				STA. 10+00.00		TO STA. 40+00.00			
								ILLINOIS		FED. AID PROJECT			

USER NAME = mohammad.hamwi	DESIGNED -	REVISED -
	DRAWN -	REVISED -
	CHECKED -	REVISED -
	DATE -	REVISED -
PLOT DATE = 8/14/2025		



IL. ROUTE 1  
(HALSTED ST.)

MATCHLINE STA. 55+00.00

**THERMOPLASTIC PAVEMENT MARKING LEGEND**

① PROP. THERMOPLASTIC PAVEMENT MARKING LINE, 4" SOLID EDGE LINE YELLOW (TYP.)	⑤ PROP. THERMOPLASTIC PAVEMENT MARKING LINE, 6" SKIP DASH, WHITE TURN LANE @ 6' SKIP & 2' DASH (TYP.)	⑩ PROP. THERMOPLASTIC PAVEMENT MARKING LINE, 12" DIAGONAL 45° @ 150' C-C (MINIMUM 5) WHITE (TYP.)
② PROP. THERMOPLASTIC PAVEMENT MARKING LINE, 4" SKIP DASH, 10' DASH-30' WHITE (TYP.)	⑥ PROP. THERMOPLASTIC PAVEMENT MARKING LINE, 6" SOLID, WHITE TURN LANE (TYP.)	⑪ PROP. THERMOPLASTIC PAVEMENT MARKING LINE, 12" LINE WHITE (TYP.)
③ PROP. THERMOPLASTIC PAVEMENT MARKING LINE, 4" SOLID EDGE LINE WHITE (TYP.)	⑦ PROP. THERMOPLASTIC PAVEMENT MARKING LINE, 8" GORE MARKING AND CHANNELIZING LINES WHITE (TYP.)	⑫ PROP. THERMOPLASTIC PAVEMENT MARKING LINE, 24" SOLID STOP LINES, WHITE (TYP.)
④ PROP. THERMOPLASTIC PAVEMENT MARKING LINE, 4" DOUBLE SOLID YELLOW LINE, 2 @ 11" C-C (TYP.)	⑧ PROP. THERMOPLASTIC PAVEMENT MARKING LINE, 12" DIAGONAL 45° @ 10' OR LESS LINE WHITE (TYP.)	⑬ PROP. THERMOPLASTIC PAVEMENT MARKING, LETTERS AND SYMBOLS WHITE (TYP.)
	⑨ PROP. THERMOPLASTIC PAVEMENT MARKING LINE, 12" DIAGONAL 45° @ 150' C-C (MINIMUM 5) YELLOW (TYP.)	⑭ PROP. THERMOPLASTIC PAVEMENT MARKING LINE, 4" SKIP DASH LINE YELLOW (TYP.)

**MODIFIED URETHANE PAVEMENT MARKING LEGEND**


(A) PROP. MODIFIED URETHANE PAVEMENT MARKING LINE, 4" SOLID EDGE LINE YELLOW (TYP.)
(B) PROP. MODIFIED URETHANE PAVEMENT MARKING LINE, 4" SKIP DASH, 10' DASH-30' WHITE (TYP.)
(C) PROP. MODIFIED URETHANE PAVEMENT MARKING LINE, 4" SKIP DASH LINE YELLOW (TYP.)

MODEL: EXCL - Plan 3 [Sheet] FILE NAME: c:\p\work\p\wid\hamw\md1063787\ID117225-shh-plan.dgn	USER NAME = mohammad.hamwi	DESIGNED -	REVISED -	STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION	ROADWAY PLAN IL-1 (HALSTED ST) FROM SOUTH OF RIDGE RD TO STRIEFF LN			F.A.P. RTE. 876	SECTION 2025-1093-RS	COUNTY COOK	TOTAL SHEETS 33	SHEET NO. 8
		DRAWN -	REVISED -									
		CHECKED -	REVISED -									
	PLOT DATE = 8/14/2025	DATE -	REVISED -									
					SCALE: 1"=50'	SHEET 2	OF 2 SHEETS	STA. 40+00.00	TO STA. 70+00.00	ILLINOIS FED. AID PROJECT		



NOTES:

- 1. WORK SHALL MEET THE REQUIREMENTS OF THE SPECIAL PROVISION, "DETECTOR LOOP REPLACEMENT AND/OR INSTALLATION (ROADWAY GRINDING, RESURFACING & PATCHING OPERATIONS)".
- 2. THIS PLAN IS FOR THE SOLE PURPOSE OF DETECTOR LOOP REPLACEMENT.



REPLACE ALL DETECTOR LOOPS AS SHOWN  
(WITHIN THE RESURFACING LIMITS)

CODE	ITEM	QUANTITY	UNIT
X8860105	DETECTOR LOOP REPLACEMENT	67	FOOT

MODEL: Schedule01 [Sheet]  
FILE NAME: c:\paw\_work\kwd\hamw\md1063787\0117225-shh-schedule.dgn

USER NAME	= mohammad.hamwi	DESIGNED	-	REVISED	-
DRAWN	-	REVIS	-	REVISED	-
PLOT SCALE	= 0.16666633' / in.	CHECKED	-	REVISED	-
PLOT DATE	= 8/14/2025	DATE	-	REVISED	-

STATE OF ILLINOIS  
DEPARTMENT OF TRANSPORTATION

DETECTOR LOOP REPLACEMENT PLAN  
IL-ROUTE 1 (HALSTED STREET) AT RIDGE ROAD

SCALE: SHEET OF 4 SHEETS STA. TO STA.

F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
876	2025-1093-RS	COOK	33	9
CONTRACT NO. 80B19				
ILLINOIS FED. AID PROJECT				

TS 1855  
ECON 60

NOTES:

1. EACH DETECTOR LOOP SHALL HAVE ITS OWN 1" COILABLE NON-METALLIC CONDUIT BETWEEN THE EDGE OF PAVEMENT AND THE ADJACENT HANDHOLE AS SHOWN ON THE PLANS AND AS STATED IN THE TRAFFIC SIGNAL SPECIFICATIONS.

2. CONTRACTOR SHALL CONFIRM THE FINAL LOCATION OF THE PEDESTRIAN EQUIPMENT BEFORE INSTALLATION WITH THE TRAFFIC SIGNAL ENGINEER.

3. APS SHALL BE PLACED PARALLEL TO THE CORRESPONDING CROSSWALK.


4. WORK SHALL MEET THE REQUIREMENTS OF THE SPECIAL PROVISIONS, DETECTOR LOOP REPLACEMENT AND/OR INSTALLATION (ROADWAY GRINDING, RESURFACING, AND PATCHING OPERATIONS).

5. ALL PUSH BUTTONS SHALL BE APS.


6. ALL PUSH BUTTONS SHALL BE LOCATED ADJACENT TO 4' BY 2.5' OF CLEAR SIDEWALK SPACE TO MEET ADA. ALL PEDESTRIAN POSTS SHALL BE LOCATED A MAXIMUM OF 10' FROM EDGE OF PAVEMENT AND MINIMUM OF 4' FROM BACK OF CURB.

7. SIDEWALK AND SIDEWALK RAMP ARE TO BE IMPROVED AT SW, NW, SE, AND NE CORNERS OF THE INTERSECTION. SEE ADA DETAIL SHEETS.



8. ALL EXISTING TRAFFIC SIGNAL CABLE NO LONGER REQUIRED SHALL BE REMOVED.




NORTHWEST CORNER



NORTHEAST CORNER



SOUTHWEST CORNER



SOUTHEAST CORNER

MODEL: Schedule02 [Sheet]  
FILE NAME: c:\paw\_work\dwg\hamw\md1063787\17225-sh-schedule.dgn

USER NAME	= mohammad.hamwi	DESIGNED	-	REVISED	-
DRAWN	-	REVIS	-	REVIS	-
PLOT SCALE	= 0.16666633' / in.	CHECKED	-	REVISED	-
PLOT DATE	= 8/14/2025	DATE	-	REVISED	-

STATE OF ILLINOIS  
DEPARTMENT OF TRANSPORTATION

TRAFFIC SIGNAL MODERNIZATION PLAN  
IL-1 (HALSTED STREET) AT 183RD STREET / ARQUILLA DRIVE




SCALE: SHEET OF 4 SHEETS STA. TO STA.

F.A.P RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
876	2025-1093-RS	COOK	33	10
CONTRACT NO. 80B19				
ILLINOIS FED. AID PROJECT				

TS 1830  
ECON 60



MODEL: Schedule03 [Sheet]  
FILE NAME: c:\paw\_work\kwd\hamw\md1063787\ID117226-shh-schedule.dgn



TS 1830  
ECON 60


USER NAME = mohammad.hamwi	DESIGNED -	REVISED -
	DRAWN -	REVISED -
PLOT SCALE = 0.16666633' / in.	CHECKED -	REVISED -
PLOT DATE = 8/14/2025	DATE -	REVISED -

STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION
---


TRAFFIC SIGNAL MODERNIZATION PLAN IL-1 (HALSTED STREET) AT 183RD STREET / ARQUILLA DRIVE			
SCALE:	SHEET	OF 4 SHEETS	STA. TO STA.

F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
876	2025-1093-RS	COOK	33	11
CONTRACT NO. 80B19				
ILLINOIS FED. AID PROJECT				

EXISTING CONTROLLER SEQUENCE




PROPOSED CONTROLLER SEQUENCE



LEGEND:

- PROTECTED PHASE
- PROTECTED/PERMITTED PHASE
- PEDESTRIAN PHASE
- OVERLAP

EXISTING AND PROPOSED EMERGENCY VEHICLE  
PREEMPTION SEQUENCE



SCHEDULE OF QUANTITIES

ITEM DESCRIPTION	UNIT	QUANTITY
UNDERGROUND CONDUIT, GALVANIZED STEEL, 2" DIA.	FOOT	62
UNDERGROUND CONDUIT, GALVANIZED STEEL, 4" DIA.	FOOT	53
HEAVY-DUTY HANDHOLE	EACH	1
MAINTENANCE OF EXISTING TRAFFIC SIGNAL INSTALLATION	EACH	1
ELECTRIC CABLE IN CONDUIT, SIGNAL NO. 14 2C	FOOT	642
ELECTRIC CABLE IN CONDUIT, SIGNAL NO. 14 3C	FOOT	656
ELECTRIC CABLE IN CONDUIT, LEAD-IN, NO. 14 1 PAIR	FOOT	545
ELECTRIC CABLE IN CONDUIT, EQUIPMENT GROUNDING CONDUCTOR, NO. 6 1C	FOOT	84
DRILL EXISTING HANDHOLE	EACH	5
PEDESTRIAN SIGNAL HEAD, LED, 1-FACE, BRACKET MOUNTED WITH COUNTDOWN TIMER	EACH	4
DETECTOR LOOP, TYPE 1	FOOT	1205
MODIFY EXISTING CONTROLLER	EACH	1
REMOVE ELECTRIC CABLE FROM CONDUIT	FOOT	186
REMOVE EXISTING HANDHOLE	EACH	1
PEDESTRIAN SIGNAL POST, 10 FT.	EACH	4
ACCESSIBLE PEDESTRIAN SIGNALS	EACH	4
CONCRETE FOUNDATION, TYPE A 12-INCH DIAMETER	FOOT	16
RE-OPTIMIZE TRAFFIC SIGNAL SYSTEM LEVEL 1	EACH	1

TRAFFIC SIGNAL  
ELECTRICAL SERVICE REQUIREMENTS

EQUIPMENT TYPE	QUANTITY	UNIT WATTAGE	TOTAL WATTAGE
SIGNAL HEAD 1 OR 3-SECTION	8	11	88
4-SECTION	-	14	-
5-SECTION	8	13	104
PROGRAMMABLE 3-SECTION	-	22	-
4-SECTION	-	32	-
5-SECTION	-	28	-
PEDESTRIAN SIGNAL	4	15	60
CONTROLLER	1	150	150
MASTER CONTROLLER	-	100	-
UPS	1	25	25
DETECTION RADAR OR VIDEO	-	20	-
BLANK-OUT SIGN	-	25	-
NETWORK SWITCH II OR III	-	35	-
CELLULAR MODEM	-	15	-
TOTAL UPS SIZING			427
UPS CHARGING	1	225	225
BATTERY HEATER MAT	1	180	180
CABINET HEATER	1	200	200
FLASHER	-	15	-
LED STREET NAME SIGN	-	120	-
LUMINAIRE	-	240	-
TOTAL SERVICE WIRE SIZING			1032

ENERGY COSTS TO:

ILLINOIS DEPARTMENT OF TRANSPORTATION  
201 WEST CENTER COURT  
SCHAUMBURG, ILLINOIS 60196

ENERGY SUPPLY: CONTACT: NEW BUSINESS DEPARTMENT  
PHONE: (866) 639-3532  
COMPANY: COMED  
ACCOUNT NUMBER: ---  
METER NUMBER: ---

STATE OF ILLINOIS  
DEPARTMENT OF TRANSPORTATION

CABLE PLAN, DESIGNATION DIAGRAM, EMERGENCY VEHICLE PREEMPTION  
SEQUENCE, AND SCHEDULE OF QUANTITIES IL-1 (HALSTED STREET) AT  
183RD STREET / ARQUILLA DRIVE

SCALE: SHEET OF 4 SHEETS STA. TO STA.

F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
876	2025-1093-RS	COOK	33	12
CONTRACT NO. 80B19				

TS 1830  
ECON 60

MODEL: Schedule04 (Sheet)  
FILE NAME: c:\paw\work\hdm\hdm1063787D117226-sh-schedule.dgn

MODEL: ADA-Strieff (Sheet)  
FILE NAME: c:\paw\_work\paw\mohammad\1063788\117225-ADA-Design.dgn

IL-1 (HALSTED STREET)

STRIEFF LANE

ADJUST EX. MEDIAN, TO BE PAID AS:

- MEDIAN REMOVAL
- CLASS D PATCHES, TYPE II, 9 INCH
- HMA REPLACEMENT OVER PATCHES
- HMA REMOVAL OVER PATCHES, 4"
- AGGREGATE BASE COURSE TYPE B 4"
- CONCRETE CURB, TYPE B
- REMOVE AND REINSTALL BRICK PAVER

### LEGEND

xx.xx'

EXISTING LENGTH

PROPOSED SIDE CURB

( ) EXISTING ELEVATION/SLOPE



PROPOSED SIDEWALK



DETECTABLE WARNINGS



SIDEWALK REMOVAL  
REPLACE W/TOPSOIL & SOD

### DESIGNER NOTES

- 1) ALL CROSS SLOPES ARE PREFERRED 1.6% (1:64), MAXIMUM 2% (1:50).
  - 2) SIDEWALK REALIGNMENT WILL REQUIRE DETAILED DESIGN
  - 3) AREAS SURROUNDED BY PCC/ASPHALT, BUILDINGS, OR ARE NEAR DRIVEWAYS, REALIGNED SIDEWALK UTILITY AND SIGNAL POLES, OR WHEN PRIVATE SIDEWALK TIES IN, WILL REQUIRE DETAILED SURVEY AND DESIGN.
  - 4) ALL BRICK CORNERS WILL REQUIRE SUPERVISOR APPROVAL BEFORE USING PROJECT DETAILS.
- BENCHMARK: NORTHEAST BOLT AT FH @ SOUTHEAST CORNER OF HALSTED ST AND STRIEFF LN

### CONSTRUCTION NOTES

- 1) ALL CROSS SLOPES ARE PREFERRED 1.6% (1:64), MAXIMUM 2% (1:50) EXCEPT WHEN TRANSITIONING TO EXISITING SIDEWALK.
- 2) MATCH EXISTING SIDEWALK WIDTH.

STATE OF ILLINOIS  
DEPARTMENT OF TRANSPORTATION


CURB RAMP IMPROVEMENT  
NE AND SE QUADRANTS OF IL-1 (HALSTED STREET) & STRIEFF LANE

SCALE: SHEET 1 OF 4 SHEETS STA. 0+00.00 TO STA. 0+00.00

F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
876	2025-1093-RS	COOK	33	13
CONTRACT NO. 80B19				
ILLINOIS FED. AID PROJECT				



MODEL: ADA-NW 183rd (Sheet)  
FILE NAME: c:\pawork\pawork\hamw\1063788D-117225-ADA-Design.dgn



### DESIGNER NOTES

- 1) ALL CROSS SLOPES ARE PREFERRED 1.6% (1:64), MAXIMUM 2% (1:50).
  - 2) SIDEWALK REALIGNMENT WILL REQUIRE DETAILED DESIGN
  - 3) AREAS SURROUNDED BY PCC/ASPHALT, BUILDINGS, OR ARE NEAR DRIVEWAYS, REALIGNED SIDEWALK UTILITY AND SIGNAL POLES, OR WHEN PRIVATE SIDEWALK TIES IN, WILL REQUIRE DETAILED SURVEY AND DESIGN.
  - 4) ALL BRICK CORNERS WILL REQUIRE SUPERVISOR APPROVAL BEFORE USING PROJECT DETAILS.
- BENCHMARK: AT ELEVATION 626.459 FT. "□" NEAST CORNER AT TCB OF SWEST CORNER OF HALSTED AND 183RD STREET

### LEGEND

xx.xx'

EXISTING LENGTH

=====

PROPOSED SIDE CURB

( )

EXISTING ELEVATION/SLOPE



PROPOSED SIDEWALK



DETECTABLE WARNINGS



SIDEWALK REMOVAL  
REPLACE W/TOPSOIL & SOD

### CONSTRUCTION NOTES

- 1) ALL CROSS SLOPES ARE PREFERRED 1.6% (1:64), MAXIMUM 2% (1:50) EXCEPT WHEN TRANSITIONING TO EXISITING SIDEWALK.
- 2) MATCH EXISTING SIDEWALK WIDTH.

USER NAME	= mohammad.hamwi
DRAWN	-
CHECKED	-
DATE	-
PLOT DATE	= 8/9/2025

DESIGNED	-
DRAWN	-
CHECKED	-
DATE	-

REVISED	-
REVISED	-
REVISED	-
REVISED	-


STATE OF ILLINOIS  
DEPARTMENT OF TRANSPORTATION

CURB RAMP IMPROVEMENT  
NW QUADRANT OF IL-1 (HALSTED STREET) & 183RD STREET

SCALE: SHEET 2 OF 4 SHEETS STA. 0+00.00 TO STA. 0+00.00

F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
876	2025-1093-RS	COOK	33	14
CONTRACT NO. 80B19				
ILLINOIS FED. AID PROJECT				

MODEL: ADA - Arquilla Dr (Sheet)  
FILE NAME: c:\p\p\work\p\work\hamw\md1063788D117225-ADA-Design.dgn



ADJUST EX. MEDIAN, TO BE PAID AS:

- MEDIAN REMOVAL
- AGGREGATE BASE COURSE TYPE B 4"
- CLASS D PATCHES TYPE I, 9 INCH
- HMA REPLACEMENT OVER PATCHES
- HMA REMOVAL OVER PATCHES, 4"
- CONCRETE CURB, TYPE B
- REMOVE AND REINSTALL BRICK PAVER

NOTES:

SEE MEDIAN DETAIL SHEET FOR MEDIAN REMOVAL AND ADJUSTMENT DETAILS

THE NORTHEAST CORNER OF IL-1 (HALSTED STREET) & ARQUILLA DRIVE WILL BE DESIGNED USING PD-6

### DESIGNER NOTES

- 1) ALL CROSS SLOPES ARE PREFERRED 1.6% (1:64), MAXIMUM 2% (1:50).
  - 2) SIDEWALK REALIGNMENT WILL REQUIRE DETAILED DESIGN
  - 3) AREAS SURROUNDED BY PCC/ASPHALT, BUILDINGS, OR ARE NEAR DRIVEWAYS, REALIGNED SIDEWALK UTILITY AND SIGNAL POLES, OR WHEN PRIVATE SIDEWALK TIES IN, WILL REQUIRE DETAILED SURVEY AND DESIGN.
  - 4) ALL BRICK CORNERS WILL REQUIRE SUPERVISOR APPROVAL BEFORE USING PROJECT DETAILS.
- BENCHMARK: AT ELEVATION 626.459 FT. "C" NEAST CORNER AT TCB OF SWEST CORNER OF HALSTED AND 183RD STREET.



### LEGEND

- XX.XX' EXISTING LENGTH
- PROPOSED SIDE CURB
- ( ) EXISTING ELEVATION/SLOPE
- PROPOSED SIDEWALK
- DETECTABLE WARNINGS
- SIDEWALK REMOVAL  
REPLACE W/TOPSOIL & SOD

### CONSTRUCTION NOTES

- 1) ALL CROSS SLOPES ARE PREFERRED 1.6% (1:64), MAXIMUM 2% (1:50) EXCEPT WHEN TRANSITIONING TO EXISITING SIDEWALK.
- 2) MATCH EXISTING SIDEWALK WIDTH.

	USER NAME   = mohammad.hamwi	DESIGNED   -	REVISED   -	STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION	CURB RAMP IMPROVEMENT SE QUADRANT OF IL-1 (HALSTED STREET) & ARQUILLA DRIVE					F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.					
		DRAWN    -	REVISED   -							876	2025-1093-RS	COOK	33	15					
		CHECKED   -	REVISED   -							CONTRACT NO. 80B19									
	PLOT DATE   = 8/9/2025	DATE       -	REVISED   -							SCALE:	SHEET 3	OF 4	SHEETS	STA. 0+00.00	TO STA. 0+00.00	ILLINOIS FED. AID PROJECT			



MODEL: median [Sheet]  
FILE NAME: c:\p\work\hamw\md1063787\17225-shh-details.dgn



SEE ADA RAMP IMPROVEMENT SHEET (IL-1 & ARQUILLA DR) FOR ADA RAMP AND CROSSWALK DETAILS

USER NAME	= mohammad.hamwi	DESIGNED	-	REVISED	-
		DRAWN	-	REVISED	-
		CHECKED	-	REVISED	-
PLOT DATE	= 8/14/2025	DATE	-	REVISED	-


STATE OF ILLINOIS  
DEPARTMENT OF TRANSPORTATION

MEDIAN RE-ADJUSTMENT DETAIL IL-1 (HALSTED STREET) & ARQUILLA DRIVE			
SCALE:	SHEET 4	OF 4	SHEETS
	STA.		TO STA.

F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
876	2025-1093-RS	COOK	33	16
CONTRACT NO. 80B19				
ILLINOIS FED. AID PROJECT				



MODEL: BD-08-1 (Sheet)  
FILE NAME: c:\p\work\dwg\hamw\md1063787\0117225-shh-DiaStus.dgn



**DETAILS FOR FRAMES AND LIDS ADJUSTMENT  
WITH MILLING**

**NOTES**

- EXISTING BROKEN FRAMES AND LIDS SHALL BE REMOVED AND DISPOSED OF BY THE CONTRACTOR AND SHALL BE REPLACED AS DIRECTED BY THE ENGINEER. REPLACEMENT FRAMES AND LIDS WILL BE PAID FOR IN ACCORDANCE WITH ARTICLE 109.04 OF THE STANDARD SPECIFICATIONS UNLESS A SEPARATE PAY ITEM HAS BEEN PROVIDED.
- IF THE EXISTING LIDS ARE OPEN, THE FRAME WILL BE ADJUSTED TO THE ELEVATION OF THE MILLED PAVEMENT SURFACE PRIOR TO THE MILLING OPERATION. THE FRAME WILL NOT BE REMOVED AND COVERED BY THE METAL PLATE.
- CITY OF CHICAGO CASTINGS ARE THE PROPERTY OF THE CITY AND THE CONTRACTOR SHALL NOTIFY THE CITY FOR REMOVAL AND DISPOSITION OF THE CASTINGS.
- THE METAL PLATE USED TO COVER THE STRUCTURE SHALL REMAIN THE PROPERTY OF THE CONTRACTOR.
- THE CONTRACTOR SHALL REMOVE ALL TRAFFIC CONTROL DEVICES BY THE END OF EACH WORK SHIFT.

**CONSTRUCTION PROCEDURES**

**STAGE 1** (BEFORE PAVEMENT MILLING)

- REMOVE A MINIMUM OF 12 (300) OF THE PAVEMENT FROM AROUND THE STRUCTURE.
- REMOVE THE EXISTING FRAME AND LID FROM THE STRUCTURE.
- COVER THE STRUCTURE OPENING WITH A 36 (900) DIAMETER METAL PLATE.
- BACKFILL WITH CRUSHED STONE AND HMA SURFACE MIX APPROVED BY THE ENGINEER. (MIN. 3 (80) HMA TO REMAIN AFTER MILLING).

**STAGE 2** (AFTER PAVEMENT MILLING)

- REMOVE THE HMA SURFACE MIX AND CRUSHED STONE.
- INSTALL THE FRAME AND LID; ADJUST THE FRAME TO ITS FINAL SURFACE ELEVATION.
- THE SURROUNDING SPACE SHALL BE FILLED WITH CLASS PP-2\* CONCRETE TO THE ELEVATION OF THE SURFACE OF THE EXISTING BASE COURSE OR THE BINDER COURSE.

\*UNLESS OTHERWISE SPECIFIED IN THE PLANS.

THE PROCEDURE EXPLAINED ABOVE SHALL CONFORM TO THE APPLICABLE PORTIONS OF SECTIONS 353, 406, 602, AND 603 OF THE STANDARD SPECIFICATIONS EXCEPT THAT "THE CONTRACTOR SHALL ADJUST THE STRUCTURES TO THE FINISHED PAVEMENT ELEVATION NO MORE THAN 5 CALENDAR DAYS PRIOR TO PLACEMENT OF THE FINAL LIFT OF SURFACE UNLESS APPROVED BY THE ENGINEER."

**LEGEND**

- |  |                               |
|--|-------------------------------|
| ① SUB-BASE GRANULAR MATERIAL                 | ⑥ FRAME AND LID (SEE NOTES)   |
| ② EXISTING PAVEMENT                          | ⑦ CLASS PP-2* CONCRETE        |
| ③ 36 (900) DIAMETER METAL PLATE              | ⑧ PROPOSED HMA SURFACE COURSE |
| ④ PROPOSED CRUSHED STONE AND HMA SURFACE MIX | ⑨ PROPOSED HMA BINDER COURSE  |
| ⑤ EXISTING STRUCTURE                         |                               |

**LOCATION OF STRUCTURES**

THE CONTRACTOR WILL BE REQUIRED TO KEEP A RECORD OF THE LOCATIONS OF THE BURIED STRUCTURES ACCORDING TO THE STATION AND DISTANCE LEFT OR RIGHT OF THE CENTERLINE OF PAVEMENT. UPON COMPLETION OF THE WORK, THE CONTRACTOR WILL DELIVER THE RECORD TO THE ENGINEER.

**BASIS OF PAYMENT**

- REMOVING FRAMES AND LIDS ON DRAINAGE AND UTILITY STRUCTURES IN THE PAVEMENT PRIOR TO MILLING, AND ADJUSTING TO FINAL GRADE PRIOR TO PLACING THE SURFACE COURSE, WILL BE PAID FOR AT THE CONTRACT UNIT PRICE EACH FOR "FRAMES AND LIDS TO BE ADJUSTED (SPECIAL)."
- THIS WORK WILL NOT BE PAID FOR WHEN DRAINAGE AND UTILITY STRUCTURES ARE SPECIFIED FOR PAYMENT AS STRUCTURE RECONSTRUCTION.
- NEW FRAMES AND LIDS, WHEN SPECIFIED, WILL BE PAID FOR SEPARATELY.
- WHEN STRUCTURES ARE TO BE ADJUSTED OR RECONSTRUCTED, THE LOWERING AND RAISING OF THE FRAMES AND LIDS WILL NOT BE PAID FOR SEPARATELY BUT WILL BE INCLUDED IN THE COST OF THE CORRESPONDING PAY ITEM.

ALL DIMENSIONS ARE IN INCHES (MILLIMETERS) UNLESS OTHERWISE SHOWN

	USER NAME = mohammad.hamwi	DESIGNED - R. SHAH	REVISED - R. BORO 03-09-11	STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION	DETAILS FOR FRAMES AND LIDS ADJUSTMENT WITH MILLING			F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
		DRAWN -	REVISED - R. BORO 12-06-11					876	2025-1093-RS	COOK	33	17
		CHECKED -	REVISED - K. SMITH 11-18-22		BD600-03 (BD-08)			CONTRACT NO. 80B19				
	PLOT DATE = 8/9/2025	DATE - 10-25-94	REVISED - K. SMITH 09-15-23		SCALE: NONE	SHEET 1	OF 1 SHEETS	STA.	TO STA.	ILLINOIS   FED. AID PROJECT		


METHOD OF MEASUREMENT

REFER TO SECTION 442 OF THE STANDARD SPECIFICATIONS FOR ROAD AND BRIDGE CONSTRUCTION AND THE RECURRING SPECIAL PROVISION "PATCHING WITH HOT-MIX ASPHALT OVERLAY REMOVAL."

BASIS OF PAYMENT

- 1. REFER TO SECTION 442 OF THE STANDARD SPECIFICATIONS FOR ROAD AND BRIDGE CONSTRUCTION AND THE RECURRING SPECIAL PROVISION "PATCHING WITH HOT-MIX ASPHALT OVERLAY REMOVAL."
- 2. SAW CUT/SCORING OF EXISTING HMA OVERLAY IS INCLUDED IN THE COST OF PAVEMENT PATCHING.
- 3. SAW CUT/SCORING OF EXISTING PAVEMENT IS INCLUDED IN THE COST OF PAVEMENT PATCHING.

\* SEE TYPICAL SECTIONS FOR THICKNESS AND MATERIALS



SEQUENCE OF CONSTRUCTION (PATCHING FIRST)

- 1. REMOVE THE EXISTING HMA MATERIAL OVER THE AREA TO BE PATCHED.
- 2. REMOVE AND REPLACE WITH CLASS C OR D PATCH.
- 3. REPLACE HMA MATERIAL OVER THE AREA TO BE PATCHED.


SEQUENCE OF CONSTRUCTION (MILLING FIRST)

- 1. MILL HMA FIRST IF THERE IS AT LEAST 4 1/2 INCHES OR MORE OF HMA MATERIAL ON TOP OF THE EXISTING PAVEMENT OR IF THE PAVEMENT IS FULL DEPTH HMA. A MINIMUM OF 2 INCHES OF HMA MATERIAL SHALL BE IN PLACE AFTER MILLING.
- 2. REMOVE AND REPLACE WITH FULL DEPTH CLASS D PATCHES TO TOP OF MILLED SURFACE.

ALL DIMENSIONS ARE IN INCHES (MILLIMETERS) UNLESS OTHERWISE SHOWN.

MODEL: BD-22-1 (Sheet)  
FILE NAME: c:\p\work\bdhamw\bd1063787\ID117225-shh-DiaStus.dgn

	USER NAME = mohammad.hamwi	DESIGNED - R. SHAH	REVISED - R. BORO 01-01-07	STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION	PAVEMENT PATCHING FOR HMA SURFACED PAVEMENT			F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
		DRAWN -	REVISED - R. BORO 09-04-07					876	2025-1093-RS	COOK	33	18
		CHECKED -	REVISED - K. ENG 10-27-08		BD400-04 (BD-22)			CONTRACT NO. 80B19				
	PLOT DATE = 8/9/2025	DATE - 10-25-94	REVISED - K. SMITH 11-18-22		SCALE: NONE	SHEET 1	OF 1 SHEETS	STA.	TO STA.	ILLINOIS FED. AID PROJECT		




- \* 3" (75) MINIMUM FROM TOP AND BOTTOM OF THE CONCRETE PAVEMENT OR BASE COURSE.
- \*\* IF THE FINAL SURFACE OF THE PAVEMENT IS CONCRETE, THE GUTTER IS TO BE FLUSH WITH THE PAVEMENT.

# CURB OR CURB AND GUTTER REMOVAL AND REPLACEMENT

ALL DIMENSIONS ARE IN INCHES (MILLIMETERS)  
UNLESS OTHERWISE SHOWN.


MODEL: BD-24-1 (Sheet)  
FILE NAME: c:\p\work\mohammad\hamwi\1063787\117225-shh-Dia\Stus.dgn

	USER NAME = mohammad.hamwi	DESIGNED - A. HOUSEH	REVISED - A. ABBAS 03-21-97	STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION	CURB OR CURB AND GUTTER REMOVAL AND REPLACEMENT			F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
		DRAWN -	REVISED - M. GOMEZ 01-22-01					876	2025-1093-RS	COOK	33	19
		CHECKED -	REVISED - R. BORO 12-15-09		BD600-06 (BD-24)			CONTRACT NO. 80B19				
	PLOT DATE = 8/14/2025	DATE - 03-11-94	REVISED - K. SMITH 07-11-19		SCALE: NONE	SHEET 1	OF 1 SHEETS	STA.	TO STA.	ILLINOIS FED. AID PROJECT		



**MILLED TEMPORARY RAMP**  
(FOR BUTT JOINT AND HMA TAPER SEE DETAIL BELOW)


**OPTION 1**



**HMA CONSTRUCTED TEMPORARY RAMP**  
(FOR BUTT JOINT AND HMA TAPER SEE DETAIL BELOW)


**OPTION 2**

**TYPICAL TEMPORARY RAMP**




**BUTT JOINT AND  
HMA TAPER**

**TYPICAL BUTT JOINT AND HMA TAPER  
FOR MILLING AND RESURFACING**



**BUTT JOINT DETAIL**



**HMA TAPER DETAIL**

**TYPICAL BUTT JOINT AND HMA TAPER  
FOR RESURFACING ONLY**

\*\* PC CONCRETE, HMA OR HMA RESURFACED PAVEMENT.

**GENERAL NOTES**

- A. MAINLINE ARTERIAL ROADWAYS AND MAJOR SIDE ROADS.
- A1. INTERSTATES
- B. MINOR SIDE ROADS.
- C. THE TEMP. RAMP SHALL BE CONSTRUCTED IMMEDIATELY UPON REMOVAL OF THE EXISTING HMA SURFACE.
- D. THE BUTT JOINT SHALL BE CONSTRUCTED IMMEDIATELY PRIOR TO PLACING THE PROPOSED HMA COURSES.
- E. TAPER THE TEMP. RAMP AT A RATE OF 3' - 4" (1.02m) PER 1 INCH (25 mm) OF MILLING THICKNESS.  
\* SEE TYPICAL SECTIONS FOR MILLING THICKNESS.
- F. SEE ARTICLE 406.08 AND 406.14 OF THE STANDARD SPECIFICATIONS FOR "HMA AND/OR PCC SURFACE REMOVAL, BUTT JOINT".  
\*\*\*  
20'-0" (6.1 m) PER 1 (25) RESURFACING (NOTE "A")  
10'-0" (3.0 m) PER 1 (25) RESURFACING (NOTE "B")

**BASIS OF PAYMENT**

1. THE BUTT JOINT WILL BE PAID FOR AT THE CONTRACT UNIT PRICE PER SQUARE YARD (SQUARE METER) FOR "HOT-MIX ASPHALT SURFACE REMOVAL - BUTT JOINT" OR FOR "PORTLAND CEMENT CONCRETE SURFACE REMOVAL- BUTT JOINT".
2. THE TEMPORARY RAMP AND SAW CUT SHALL BE INCLUDED IN THE UNIT COST FOR HMA OR PCC SURFACE REMOVAL-BUTT JOINT.

ALL DIMENSIONS ARE IN INCHES (MILLIMETERS) UNLESS OTHERWISE SHOWN.

MODEL: BD-32-1 (Sheet)  
FILE NAME: c:\p\work\hdm\hdm\1063787\117225-shh-DistStatus.dgn

USER NAME = mohammad.hamwi	DESIGNED - M. DE YONG	REVISED - A. ABBAS 03-21-97
	DRAWN - M. GOMEZ 04-06-01	REVISED - M. GOMEZ 04-06-01
	CHECKED - R. BORO 01-01-07	REVISED - R. BORO 01-01-07
PLOT DATE = 8/14/2025	DATE - 06-13-90	REVISED - K. SMITH 11-18-22


STATE OF ILLINOIS  
DEPARTMENT OF TRANSPORTATION

**BUTT JOINT AND  
HMA TAPER DETAILS**

SCALE: NONE SHEET 1 OF 1 SHEETS STA. TO STA.

F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
876	2025-1093-RS	COOK	33	20
BD400-05 BD-32		CONTRACT NO. 80B19		
ILLINOIS		FED. AID PROJECT		

MODEL: TC-10-1 [Sheet]  
FILE NAME: c:\p\work\p\work\hammad\m\1063787\17225-shh-DiaStus.dgn



NOTES:

- SIDE ROAD WITH A SPEED LIMIT OF 40 MPH (60 km/h) OR LESS AS SHOWN ON THE DRAWING AND AS DIRECTED BY THE ENGINEER:
  - ONE "ROAD CONSTRUCTION AHEAD" SIGN 36 x 36 (900x900) WITH A FLASHER MOUNTED ON IT APPROXIMATELY 200' (60 m) IN ADVANCE OF THE MAIN ROUTE.
  - THE CLOSED PORTION OF THE MAIN ROUTE SHALL BE PROTECTED BY BLOCKING WITH TYPE I, TYPE II OR TYPE III BARRICADES, 1/3 OF THE CROSS SECTION OF THE CLOSED PORTION.
- SIDE ROAD WITH A SPEED LIMIT GREATER THAN 40 MPH (60 km/h) AS SHOWN ON THE DRAWING AND AS DIRECTED BY THE ENGINEER:
  - ONE "ROAD CONSTRUCTION AHEAD" SIGN 48 x 48 (1.2 m x 1.2 m) WITH A FLASHER MOUNTED ON IT APPROXIMATELY 500' (150 m) IN ADVANCE OF THE MAIN ROUTE.
  - THE CLOSED PORTION OF THE MAIN ROUTE SHALL BE PROTECTED BY BLOCKING WITH TYPE III BARRICADES, 1/2 OF THE CROSS SECTION OF THE CLOSED PORTION.
- CONES MAY BE SUBSTITUTED FOR BARRICADES OR DRUMS AT HALF THE SPACING DURING DAY OPERATIONS. CONES SHALL BE A MINIMUM OF 28 (710) IN HEIGHT.
- WHEN THE SIDE ROAD LIES BETWEEN THE BEGINNING OF THE MAINLINE SIGNING AND THE WORK ZONE, A SINGLE HEADED ARROW (M6-1) SHALL BE USED IN LIEU OF THE DOUBLE HEADED ARROW (M6-4).
- WHEN WORK IS BEING PERFORMED ON A SIDE ROAD OR DRIVEWAY, FOLLOW THE APPLICABLE STANDARD(S). THE DIRECTIONAL ARROW (M6-1 OR M6-4) SHALL BE COVERED OR REMOVED WHEN NO LONGER CONSISTENT WITH THE TRAFFIC CONTROL SET-UP.
- ADVANCE WARNING SIGNS ARE TO BE OMITTED ON DRIVEWAYS UNLESS OTHERWISE SPECIFIED IN THE PLANS OR BY THE ENGINEER.
- THE TRAFFIC CONTROL AND PROTECTION FOR SIDE ROADS, INTERSECTIONS, AND DRIVEWAYS SHALL BE INCLUDED IN THE COST OF SPECIFIED TRAFFIC CONTROL STANDARDS OR ITEMS.

All dimensions are in inches (millimeters)  
unless otherwise shown.


USER NAME	= mohammad.hamwi	DESIGNED	- L.H.A.	REVISED	- T. RAMMACHER 01-06-00
		DRAWN	-	REVISED	- A. SCHUETZE 07-01-13
		CHECKED	-	REVISED	- A. SCHUETZE 09-15-06
PLOT DATE	= 8/9/2025	DATE	- 06-89	REVISED	- D. SENDERAK 05-03-24

STATE OF ILLINOIS  
DEPARTMENT OF TRANSPORTATION

TRAFFIC CONTROL AND PROTECTION FOR  
SIDE ROADS, INTERSECTIONS, AND DRIVEWAYS


SCALE: SHEET OF SHEETS STA. TO STA.

F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
876	2025-1093-RS	COOK	33	21
TC-10		CONTRACT NO. 80B19		
		ILLINOIS	FED. AID PROJECT	




\*\*\* REDUCE TO 40' (12 m) O.C. ON CURVES WITH POSTED OR ADVISORY SPEED 45 M.P.H. (70 km/h) OR LESS.


## TWO-LANE/TWO-WAY




## LANE REDUCTION TRANSITION



## TWO-WAY LEFT TURN



## MULTI-LANE/UNDIVIDED



## MULTI-LANE/DIVIDED

## GENERAL NOTES

- MARKERS USED WITH DASHED LINES SHALL BE CENTERED IN THE GAP BETWEEN SEGMENTS.
- MARKERS USED ADJACENT TO SOLID LINES SHALL BE OFFSET 2 TO 3 (50 TO 75) TOWARD TRAFFIC AS SHOWN.
- MARKERS THROUGH TANGENTS LESS THAN 500' (150 m) IN LENGTH BETWEEN CURVES SHALL BE INSTALLED AT THE LESSER OF THE TWO CURVE SPACINGS.
- MARKERS ARE TO BE USED ADJACENT TO BOTH SOLID WHITE LINES IN DUAL LEFT TURN LANES

## SYMBOLS



- YELLOW STRIPE
- WHITE STRIPE
- ONE-WAY AMBER MARKER
- ONE-WAY CRYSTAL MARKER (W/O)
- TWO-WAY AMBER MARKER

## LANE MARKER NOTES

- USE DOUBLE LANE LINE MARKERS SPACED AS SHOWN.
- REDUCE TO 40' (12 m) O.C. ON CURVES WHERE ADVISORY SPEEDS ARE 10 M.P.H (20 km/h) LOWER THAN POSTED SPEEDS.

## DESIGN NOTES

- DOUBLE LANE LINE MARKERS SHALL BE USED UNLESS SPECIFIED OTHERWISE.
- EXCEPT AS SHOWN ON THE LANE REDUCTION TRANSITION AND FREEWAY EXIT RAMP DETAIL, MARKERS ARE NOT TO BE SPECIFIED ON RIGHT EDGE LINES.
- THE EXACT MARKER LIMITS, SPACING, AND COLOR SHALL BE INCLUDED IN THE PLANS WHEN STANDARD SPECIFICATIONS ARE NOT BEING USED.
- MARKERS SHOULD NOT BE USED ALONGSIDE CURBS EXCEPT FOR EXTREMELY SHORT SECTIONS OF CURBS WHERE NOT MORE THAN TWO MARKERS WOULD BE INVOLVED.



## TURN LANES

All dimensions are in inches (millimeters) unless otherwise shown.


STATE OF ILLINOIS  
DEPARTMENT OF TRANSPORTATION

TYPICAL APPLICATIONS  
RAISED REFLECTIVE PAVEMENT MARKERS (SNOW-PLOW RESISTANT)


SCALE: NONE SHEET 1 OF 1 SHEETS STA. TO STA.

F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
876	2025-1093-RS	COOK	33	22
TC-11		CONTRACT NO. 80B19		
ILLINOIS		FED. AID PROJECT		







## 2-LANE ROADWAY



## MULTI-LANE UNDIVIDED



## TYPICAL LANE AND EDGE LINE MARKING




### DETAIL "A"


### DETAIL "B"

## TYPICAL CROSSWALK MARKING

- \* MARKINGS SHALL BE INSTALLED PARALLEL TO THE CENTERLINE OF THE ROAD WHICH IT CROSSES




**4' (1.2 m) WIDE MEDIANS ONLY**




DIAGONAL LINE SPACING: 50' (15 m) C-C (LESS THAN 30MPH (50 km/h))  
75' (25 m) C-C 30MPH (50 km/h) TO 45MPH (70 km/h))  
150' (45 m) C-C (MORE THAN 45MPH (70 km/h))

### MEDIANS OVER 4' (1.2 m) WIDE




A MINIMUM OF TWO PAIRS OF TURN ARROWS SHALL BE USED, WHITE IN COLOR. ADDITIONAL PAIRS SHALL BE PLACED AT 200' (60 m) TO 300' (90 m) INTERVALS.



### **MEDIAN WITH TWO-WAY LEFT TURN LANE**

## TYPICAL PAINTED MEDIAN MARKING




FULL SIZE LETTERS 8' (2.4 m) AND ARROWS SHALL BE USED.


- \* TURN LANES IN EXCESS OF 400' (120 m) IN LENGTH MAY HAVE AN ADDITIONAL SET OF ARROW - "ONLY" INSTALLED MIDWAY BETWEEN THE OTHER TWO SETS OF ARROW - "ONLY".

### **TYPICAL LEFT (OR RIGHT) TURN LANE**


## TYPICAL TURN LANE MARKING




**ISLAND OFFSET FROM PAVEMENT EDGE**

**ISLAND AT PAVEMENT EDGE**

## TYPICAL ISLAND MARKING <sup>20 (5)</sup>



## COMBINATION LEFT AND U-TURN



## U-TURN

- \* LANE REDUCTION ARROWS REQUIRED AT SPEEDS OF 45 MPH OR GREATER OR WHEN SPECIFIED IN PLANS.

D(FT)	SPEED LIMIT
345	30
425	35
500	40
580	45
665	50
750	55

TYPE OF MARKING	WIDTH OF LINE	PATTERN	COLOR	SPACING / REMARKS
CENTERLINE ON 2 LANE PAVEMENT	4 (100)	SKIP-DASH	YELLOW	10' (3 m) LINE WITH 30' (9 m) SPACE
CENTERLINE ON MULTI-LANE UNDIVIDED PAVEMENT	2 @ 4 (100)	SOLID	YELLOW	11 (280) C-C
NO PASSING ZONE LINES: FOR ONE DIRECTION FOR BOTH DIRECTIONS	4 (100) 2 @ 4 (100)	SOLID SOLID	YELLOW YELLOW	5½ (140) C-C FROM SKIP-DASH CENTERLINE 11 (280) C-C OMIT SKIP-DASH CENTERLINE BETWEEN
LANE LINES	4 (100) 5 (125) ON FREEWAYS	SKIP-DASH SKIP-DASH	WHITE WHITE	10' (3 m) LINE WITH 30' (9 m) SPACE
DOTTED LINES (EXTENSIONS OF CENTER, LANE OR TURN LANE MARKINGS)	SAME AS LINE BEING EXTENDED	SKIP-DASH	SAME AS LINE BEING EXTENDED	2' (600) LINE WITH 6' (1.8 m) SPACE
EDGE LINES	4 (100)	SOLID	YELLOW-LEFT WHITE-RIGHT	OUTLINE MEDIANS IN YELLOW
TURN LANE MARKINGS	6 (150) LINE: FULL SIZE LETTERS & SYMBOLS (8' (2.4m))	SOLID	WHITE	SEE TYPICAL TURN LANE MARKING DETAIL
TWO WAY LEFT TURN MARKING	2 @ 4 (100) EACH DIRECTION  8' (2.4m) LEFT ARROW	SKIP-DASH AND SOLID IN PAIRS	YELLOW  WHITE	10' (3 m) LINE WITH 30' (9 m) SPACE FOR SKIP-DASH: 5½ (140) C-C BETWEEN SOLID LINE AND SKIP-DASH LINE SEE TYPICAL TWO-WAY LEFT TURN MARKING DETAIL
CROSSWALK LINES (PEDESTRIAN) A. DIAGONALS (BIKE & EQUESTRIAN) B. LONGITUDINAL BARS (SCHOOL)	2 @ 6 (150) 12 (300) @ 45° 12 (300) @ 90°	SOLID SOLID SOLID	WHITE WHITE WHITE	NOT LESS THAN 6' (1.8 m) APART 2' (600) APART 2' (600) APART SEE TYPICAL CROSSWALK MARKING DETAILS.
STOP LINES	24 (600)	SOLID	WHITE	PLACE 4' (1.2 m) IN ADVANCE OF AND PARALLEL TO CROSSWALK, IF PRESENT, OTHERWISE, PLACE AT DESIRED STOPPING POINT, PARALLEL TO CROSSROAD CENTERLINE, WHERE POSSIBLE
PAINTED MEDIANS	2 @ 4 (100) WITH 12 (300) DIAGONALS @ 45° NO DIAGONALS USED FOR 4' (1.2 m) WIDE MEDIANS	SOLID	YELLOW; TWO WAY TRAFFIC WHITE: ONE WAY TRAFFIC	11 (280) C-C FOR THE DOUBLE LINE SEE TYPICAL PAINTED MEDIAN MARKING.
GORE MARKING AND CHANNELIZING LINES	8 (200) WITH 12 (300) DIAGONALS @ 45°	SOLID	WHITE	DIAGONALS: 15' (4.5 m) C-C (LESS THAN 30MPH (50 km/h)) 20' (6 m) C-C 30MPH (50 km/h) TO 45MPH (70 km/h)) 30' (9 m) C-C (OVER 45MPH (70 km/h))
RAILROAD CROSSING	24 (600) TRANSVERSE LINES; "RR" IS 6' (1.8 m) LETTERS; 16 (400) LINE FOR "X"	SOLID	WHITE	SEE STATE STANDARD 780001 AREA OF: "R"=3.6 SQ. FT. (0.33 m <sup>2</sup> ) EACH "X"=54.0 SQ. FT. (5.0 m <sup>2</sup> )
SHOULDER DIAGONALS (REQUIRED FOR SHOULDERS ≥ 8' )	12 (300) @ 45°	SOLID	WHITE - RIGHT YELLOW - LEFT	50' (15 m) C-C (LESS THAN 30MPH (50 km/h)) 75' (25 m) C-C (30 MPH (50 km/h) TO 45MPH (70 km/h)) 150' (45 m) C-C (OVER 45MPH (70 km/h))
U TURN ARROW	SEE DETAIL	SOLID	WHITE	16.3 SF
2 ARROW COMBINATION LEFT AND U TURN	SEE DETAIL	SOLID	WHITE	30.4 SF

FOR FURTHER DETAILS ON PAVEMENT MARKING REFER TO  
STANDARD SPECIFICATIONS FOR ROAD AND BRIDGE  
CONSTRUCTION AND STATE STANDARD 780001.




All dimensions are in inches (millimeters) unless otherwise shown.

USER NAME = mohammad.hamwi	DESIGNED = EVERS	REVISED = C. JUCIUS 09-09-09
	DRAWN =	REVISED = C. JUCIUS 07-01-13
	CHECKED =	REVISED = C. JUCIUS 12-21-15
PLOT DATE = 8/14/2025	DATE = 03-19-90	REVISED = C. JUCIUS 04-12-16


**STATE OF ILLINOIS**  
**DEPARTMENT OF TRANSPORTATION**

<div style="text-align: center;"> <b>DISTRICT ONE</b>  <b>TYPICAL PAVEMENT MARKINGS</b> </div>					F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
					876	2025-1093-RS	COOK	33	23
					<b>TC-13</b>			CONTRACT NO. 80B19	
SCALE: NONE	SHEET 1	OF 1	SHEETS	STA.	TO STA.				

MODEL: TC-13-1 [Sheet]  
FILE NAME: c:\pw work\pwwidot\hamwim\d117225-sht-DisStds.dgn




ALL QUANTITIES OF PLACEMENT ARE REPRESENTED  
IN LINEAR FEET OF 4" LINES TO MATCH THE  
4" TEMPORARY TAPE PAY ITEM AND REPRESENTS  
THE TOTAL QUANTITY OF 4" TAPE REQUIRED.



MODEL: TC-16-1 [Sheet]  
FILE NAME: c:\pw work\pwidot\hamwim\d1063787\D117225-sht-DistStd.dgn

F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
876	2025-1093-RS	COOK	33	24
<b>TC-16</b>		CONTRACT NO. 80B19		
ILLINOIS		FED. AID PROJECT		

MODEL: TC-22-1 [Sheet]  
FILE NAME: c:\p\work\pwork\hamw\md1063787\ID117225-shh-Dia\Sigs.dgn




## NOTES:

1. USE BLACK LETTERING ON ORANGE BACKGROUND.
2. ERECT SIGNS IN ADVANCE OF THE LOCATION FOR THE "ROAD CONSTRUCTION AHEAD" SIGN AT LOCATIONS AS DIRECTED BY THE ENGINEER.
3. ERECT SIGN ① WITH INSTALLED PANEL ② ONE WEEK PRIOR TO THE START OF CONSTRUCTION.
4. REMOVE PANEL ② SOON AFTER THE START OF CONSTRUCTION.
5. SEE SPECIAL PROVISION FOR "TEMPORARY INFORMATION SIGNING" FOR ADDITIONAL INFORMATION.
6. ONE SIGN ASSEMBLY EQUALS 25.70 SQ. FT. (2.3 SQ. M.)
7. SHALL BE PAID FOR AS TEMPORARY INFORMATION SIGNING.

ALL DIMENSIONS ARE IN INCHES (MILLIMETERS)  
UNLESS OTHERWISE SHOWN.

	USER NAME   = mohammad.hamwi	DESIGNED   -	REVISED   -   R. MIRS 09-15-97	STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION	ARTERIAL ROAD INFORMATION SIGN				F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.	
		DRAWN    -	REVISED   -   R. MIRS 12-11-97						876	2025-1093-RS	COOK	33	25	
		CHECKED   -	REVISED   - T. RAMMACHER 02-02-99						TC-22					CONTRACT NO. 80B19
	PLOT DATE   = 8/14/2025	DATE       -	REVISED   -   C. JUCIUS 01-31-07		SCALE: NONE		SHEET   1	OF   1	SHEETS	STA.	TO STA.			
							ILLINOIS   FED. AID PROJECT							



3.0" RADIUS, 0.5" BORDER, WHITE ON GREEN; REFLECTORIZED  
"DRIVEWAY" D; "ENTRANCE" D; STANDARD ARROW CUSTOM 12.0" x 5.0"


- NOTES:**
1. HALF OF THE SIGNS WILL REQUIRE A LEFT HAND FACING ARROW.
  2. TWO SIGNS SHALL BE USED AT EACH COMMERCIAL ENTRANCE  
PLACED BACK-TO-BACK: ONE WITH A RIGHT HAND ARROW (SHOWN)  
SHALL BE PLACED ON THE NEAR RIGHT SIDE THE DRIVEWAY  
AND ONE WITH A LEFT HAND ARROW SHALL BE PLACED ON THE  
FAR LEFT SIDE OF THE DRIVEWAY.
  3. SIGNS TO BE PAID FOR AS ITEM "TEMPORARY INFORMATION SIGNING".

MODEL: TC-26-1 [Sheet]  
FILE NAME: c:\p\work\p\work\hamw\md1063787\ID117225-shh-DistSign.dgn

	USER NAME = mohammad.hamwi	DESIGNED -	REVISED - C. JUCIUS 02-15-07	STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION	DRIVEWAY ENTRANCE SIGNING			F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
		DRAWN -	REVISED -					876	2025-1093-RS	COOK	33	26
		CHECKED -	REVISED -		TC-26			CONTRACT NO. 80B19				
	PLOT DATE = 8/9/2025	DATE -	REVISED -		SCALE: NONE	SHEET 1	OF 1 SHEETS	STA.	TO STA.	ILLINOIS FED. AID PROJECT		

LOOPS NEXT TO SHOULDERS

PROVIDE A PAVEMENT REPLACEMENT  
NOTE WHICH SHOULD EQUAL  
3' (900 mm) X WIDTH OF  
PAVED SHOULDER.




\* = (600 mm)

\*\* UNIT DUCT IS TO BE SHOWN ON PLAN SHEETS  
BUT SHALL NOT BE INCLUDED IN THE PAY ITEMS.

LEFT TURN LANES WITH MEDIANS  
VOLUME DENSITY ("FAR OUT" DETECTION)  
ON SAME APPROACH  
(PROTECTED / PERMITTED LEFT TURN PHASING)

HANDHOLE LOCATION MAY  
VARY DEPENDING ON GEOMETRICS  
AND DESIGN OF TRAFFIC SIGNALS.  
HEAVY-DUTY HANDHOLES TO BE  
USED WHEN THE MEDIAN IS  
MOUNTABLE. REFER TO STANDARD  
814001 TO ENSURE THAT HANDHOLE  
FITS IN MEDIAN.




\* = (600 mm)

\*\* UNIT DUCT IS TO BE SHOWN ON PLAN SHEETS  
BUT SHALL NOT BE INCLUDED IN THE PAY ITEMS.

NOTE: DUAL LEFT TURNS NOT SHOWN REFER TO  
PLAN SHEET FOR DETECTOR LOOP REPLACEMENT


LEFT TURN LANES WITHOUT MEDIANS  
VOLUME DENSITY ("FAR OUT" DETECTION)  
ON SAME APPROACH  
(PROTECTED / PERMITTED LEFT TURN PHASING)



\* = (600 mm)

NOTE: DUAL LEFT TURNS NOT SHOWN REFER TO  
PLAN SHEET FOR DETECTOR LOOP REPLACEMENT

ARTERIAL-VOLUME DENSITY ("FAR OUT" DETECTION)  
CROSS STREET-NON VOLUME DENSITY ("FAR OUT" DETECTION)




\* = (1.8m)  
\*\* = (1.5m)

LOOPS ARE SAW-CUT  
TO THE EDGE OF  
PAVEMENT. 1" (25 mm) UNIT  
DUCT IS RUN BETWEEN  
EDGE OF PAVEMENT  
AND HANDHOLE.  
(TYP. FOR LOOPS  
THAT TERMINATE  
IN HANDHOLES  
OUTSIDE PAVEMENT)

STRAIGHT SAW  
CUTS TO HEAVY-  
DUTY HANDHOLE  
IN PAVEMENT  
(TYP.)

DETAIL 1  
N.T.S.

ARTERIAL-VOLUME DENSITY ("FAR OUT" DETECTION)  
CROSS STREET-NON VOLUME DENSITY ("UPTIGHT" PRESENCE DETECTION)



OFFSET LOOPS BY  
1' (300mm) FOR  
STRAIGHT SAW CUTS

THIS DIMENSION MAY BE  
ADJUSTED FOR DRIVEWAY  
OR OTHER OBSTRUCTIONS.  
WHEN ADJUSTMENT IS  
REQUIRED, DETECTORS WILL  
NORMALLY BE MOVED CLOSER  
TO THE INTERSECTION.

\* = (1.8m)

- THESE DIMENSIONS  
WILL BE VARIABLE  
[6' (1.8m) MINIMUM,  
25' (7.6 m) MAXIMUM]

- THESE DIMENSIONS  
SHALL BE 5' (1.5m) FOR  
10' (3.0m) LANE WIDTHS

DETAIL 2  
N.T.S.

NOTES:

VEHICLES LOOP DETECTORS

- \* ALL LEAD IN CABLE SHALL BE TWO CONDUCTOR NO. 14 TWISTED, SHIELDED.
- \* EACH DETECTOR LOOP SHALL HAVE ITS OWN SAW CUT FROM THE LOOP TO THE EDGE OF PAVEMENT OR TO A HANDHOLE IN THE PAVEMENT.
- \* EACH DETECTOR LOOP SHALL HAVE ITS OWN ONE INCH (25 mm) UNIT DUCT BETWEEN THE EDGE OF PAVEMENT AND THE FIRST HANDHOLE OR JUNCTION BOX. EACH UNIT DUCT RUN SHALL BE SHOWN ON THE PLANS BY THE DESIGNER, BUT SHALL NOT BE PAID FOR SEPARATLY. THIS ITEM IS INCIDENTAL TO THE PAY ITEM FOR DETECTOR LOOPS.
- \* ONE DIMENSION OF ALL DETECTOR LOOPS SHALL BE SIX FEET (1.8 m)
- \* EACH LANE OF NON-LOCKING, PRESENCE DETECTION AND EACH LANE OF A DOUBLE LEFT TURN LANE REQUIRES A SEPARATE INDUCTIVE LOOP DETECTOR AND LEAD IN CABLE.
- \* WHEN NON-LOCKING, PRESENCE DETECTION IS USED, MORE THAN ONE LOOP PER LANE IS REQUIRED BEHIND THE STOP BAR (i.e. 1-1/2, 1-3/4, 2).
- \* WHEN SYSTEM LOOPS ARE REQUIRED ON AN APPROACH OF AN INTERSECTION, THE LOOPS USED FOR VOLUME DENSITY AND INTERSECTION TIMING SHALL ALSO BE USED AS SYSTEM DETECTORS. EACH ONE OF THESE TYPE OF LOOPS REQUIRES A SEPARATE TWO CONDUCTOR NO. 14 TWISTED SHIELDED CABLE AND A SEPARATE INDUCTIVE LOOP DETECTOR WHEN NEW CONTROLLERS ARE UTILIZED. THE DESIGNER SHALL LABEL THESE TYPES OF LOOPS AS "INTERSECTION AND SAMPLING (SYSTEM) DETECTORS" ON THE SIGNAL LAYOUT, THE INTERCONNECT PLAN AND THE SYSTEM CABLE PLAN. WHEN AN EXISTING CONTROLLER IS UTILIZED FOR THIS TYPE OF DETECTION, THE PAY ITEM "INDUCTIVE LOOP DETECTOR WITH SYSTEM OUTPUT" SHOULD BE USED.

PLACEMENT OF DETECTORS

THE FOLLOWING FIGURES REPRESENT THE MOST COMMON DETECTOR LOOP LOCATIONS AND SIZES. ADJUSTMENTS WILL BE NECESSARY FOR SPECIFIC GEOMETRIC CONSIDERATIONS.

LOCATIONS AND DEMENSIONS OF DETECTOR LOOPS ARE REQUIRED ON ALL SIGNAL LAYOUT PLAN SHEETS.

"FAR OUT" DETECTION REFERS TO LOCKING, PRESENCE TYPE DETECTION LOCATED IN THRU LANES, RIGHT TURN LANES, AND RIGHT TURN LANE TAPER AREAS (IF APPLICABLE), USUALLY 250' (75 m) IN ADVANCE OF STOP BARS. "UPTIGHT" DETECTION REFERS TO NON-LOCKING PRESENCE TYPE DETECTION LOCATED IN ALL LANES AND 10'-15' (3.0 m-4.5 m) BEHIND THE CROSSING STREET'S EDGE OF PAVEMENT EXTENDED.

NOTE:

ALL DETAILS AND NOTES SHOWN ARE FROM THE I.D.O.T. DISTRICT 1 TRAFFIC SIGNAL DESIGN GUIDELINES DATED JANUARY 1995

THIS DRAWING HAS BEEN PREPARED TO ASSIST THE RESIDENT ENGINEER FOR ALL ROADWAY RESURFACING OR S.M.A.R.T. PROJECTS WHERE THE DIMENSIONS ARE NOT SHOWN ON THE PLANS AND THE FINAL LOCATIONS FOR CROSSWALKS OR STOP BARS ARE NOT DETERMINED.

MODEL: TS-07-1 (Sheet)  
FILE NAME: c:\p\work\dwg\hamw\md1063787\D117225-shh-DistStus.dgn

USER NAME = mohammad.hamwi	DESIGNED -	REVISED -
	DRAWN -	REVISED -
	CHECKED - R.K.F.	REVISED -
PLOT DATE = 8/9/2025	DATE -	REVISED -

STATE OF ILLINOIS  
DEPARTMENT OF TRANSPORTATION


DISTRICT 1 - DETECTOR LOOP INSTALLATION  
DETAILS FOR ROADWAY RESURFACING

SCALE: NONE SHEET 1 OF 1 SHEETS STA. TO STA.


F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
876	2025-1093-RS	COOK	33	27
TS-07		CONTRACT NO. 80B19		
ILLINOIS		FED. AID PROJECT		

ADA DETAIL FOR SINGLE PERPENDICULAR CURB RAMPS W/ EXIST. 5% OR LESS RUN. SLOPE


PD-01A



PD-01B



PD-01C



DESIGNER NOTES:

- 1) ALL CROSS SLOPES ARE PREFERRED 1.6% (1:64), MAXIMUM 2% (1:50).  
2) SIDEWALK REALIGNMENT WILL REQUIRE DETAILED DESIGN.  
3) AREAS SURROUNDED BY PCC/ASPHALT, BUILDINGS, OR ARE NEAR TO DRIVEWAYS, REALIGNED SIDEWALK, UTILITY AND SIGNAL POLES, OR WHEN PRIVATE SIDEWALK TIES IN, WILL REQUIRE DETAILED SURVEY AND DESIGN.  
4) ALL BRICK CORNERS WILL REQUIRE SUPERVISOR APPROVAL BEFORE USING PROJECT DETAILS

LEGEND

- EXIST. GRASS  
PROPOSED SIDEWALK  
DETECTABLE WARNINGS  
PROPOSED SIDE CURB

CONSTRUCTION NOTES:

- 1) ALL CROSS SLOPES ARE PREFERRED 1.6% (1:64), MAXIMUM 2% (1:50) EXCEPT WHEN TRANSITIONING TO EXISTING SIDEWALK  
\* MATCH EXISTING SIDEWALK WIDTH

USER NAME	= mohammad.hamwi	DESIGNED	-	REVISED	-
DRAWN	-	R. LEDEZMA		REVISED	-
CHECKED	-			REVISED	-
DATE	-	10/02/2019		REVISED	-

STATE OF ILLINOIS  
DEPARTMENT OF TRANSPORTATION

PROJECT DETAIL FOR SINGLE PERPENDICULAR CURB RAMPS  
(PD-01)

SCALE: NONE SHEET 1 OF 1 SHEETS STA. TO STA.


F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
876	2025-1093-RS	COOK	33	28
PD-01		CONTRACT NO. 80B19		
ILLINOIS		FED. AID PROJECT		

MODEL: pd-1-1 [Sheet]  
FILE NAME: c:\p\work\1063787\11725-shh-DistShts.dgn




ADA DETAIL FOR SINGLE PERPENDICULAR CURB RAMPS W/ EXIST. 5% OR GREATER RUN. SLOPE


PD-02A



PD-02B



PD-02C



DESIGNER NOTES:

- 1) ALL CROSS SLOPES ARE PREFERRED 1.6% (1:64), MAXIMUM 2% (1:50).
- 2) SIDEWALK REALIGNMENT WILL REQUIRE DETAILED DESIGN.
- 3) AREAS SURROUNDED BY PCC/ASPHALT, BUILDINGS, OR ARE NEAR TO DRIVEWAYS, REALIGNED SIDEWALK, UTILITY AND SIGNAL POLES, OR WHEN PRIVATE SIDEWALK TIES IN, WILL REQUIRE DETAILED SURVEY AND DESIGN.
- 4) ALL BRICK CORNERS WILL REQUIRE SUPERVISOR APPROVAL BEFORE USING PROJECT DETAILS

LEGEND

PROPOSED SIDE CURB



EXIST. GRASS



PROPOSED SIDEWALK



DETECTABLE WARNINGS

CONSTRUCTION NOTES:

- 1) ALL CROSS SLOPES ARE PREFERRED 1.6% (1:64), MAXIMUM 2% (1:50) EXCEPT WHEN TRANSITIONING TO EXISTING SIDEWALK
- \* MATCH EXISTING SIDEWALK WIDTH

MODEL: pd-2-1 [Sheet]  
FILE NAME: c:\p\work\hamwi\1063787\117225-shh-DistShts.dgn

PLOT DATE = 8/9/2025	USER NAME = mohammad.hamwi	DESIGNED -	REVISED -
		DRAWN - R. LEDEZMA	REVISED -
		CHECKED -	REVISED -
	DATE = 10/02/2019	REVISED -	

STATE OF ILLINOIS  
DEPARTMENT OF TRANSPORTATION

PROJECT DETAIL FOR SINGLE PERPENDICULAR CURB RAMPS  
(PD-02)

SCALE: NONE SHEET 1 OF 1 SHEETS STA. TO STA.

F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
876	2025-1093-RS	COOK	33	29
PD-02		CONTRACT NO. 80B19		
ILLINOIS		FED. AID PROJECT		

MODEL: pd-3-1 [Sheet]  
FILE NAME: c:\pw\_work\pwidot\hamwim\d1063787\D117225-sht-DistStd.dgn

MODEL: pd-3-  
FILE NAME: C



MODEL: pd-3-  
FILE NAME: C



MODEL: pd-3-  
FILE NAME: C

- MODEL: pd-3-  
FILE NAME: C

MODEL: pd-3-  
FILE NAME: C



MODEL: pd-3-  
FILE NAME: C



MODEL: pd-3-  
FILE NAME: C



MODEL: pd-3-  
FILE NAME: C

MODEL: pd-3-  
FILE NAME: C

- MODEL: pd-3-  
FILE NAME: c

MODEL: pd-3-  
FILE NAME: c

MODEL: pd-3-  
FILE NAME: c

MODEL: pd-3-  
FILE NAME: c


MODEL: pd-3-  
FILE NAME: c

MODEL: pd-3-  
FILE NAME: c


MODEL: pd-3-  
FILE NAME: C

# ADA DETAIL FOR SINGLE PERPENDICULAR CURB RAMPS W/ TURNING SPACE

PD-04A



PD-04B



**DESIGNER NOTES:**

- 1) ALL CROSS SLOPES ARE PREFERRED 1.6% (1:64), MAXIMUM 2% (1:50).
- 2) SIDEWALK REALIGNMENT WILL REQUIRE DETAILED DESIGN.
- 3) AREAS SURROUNDED BY PCC/ASPHALT, BUILDINGS, OR ARE NEAR TO DRIVEWAYS, REALIGNED SIDEWALK, UTILITY AND SIGNAL POLES, OR WHEN PRIVATE SIDEWALK TIES IN, WILL REQUIRE DETAILED SURVEY AND DESIGN.
- 4) ALL BRICK CORNERS WILL REQUIRE SUPERVISOR APPROVAL BEFORE USING PROJECT DETAILS

**LEGEND**

- EXIST. GRASS
- PROPOSED SIDEWALK
- PROPOSED SIDE CURB
- DETECTABLE WARNINGS

**CONSTRUCTION NOTES:**

- 1) ALL CROSS SLOPES ARE PREFERRED 1.6% (1:64), MAXIMUM 2% (1:50) EXCEPT WHEN TRANSITIONING TO EXISTING SIDEWALK
- \* MATCH EXISTING SIDEWALK WIDTH

MODEL: pd-4-1 [Sheet]  
FILE NAME: c:\p\work\hisham\mid1063787\17225-shh-DistShts.dgn

USER NAME = mohammad.hamwi	DESIGNED -	REVISED -
	DRAWN - R. LEDEZMA	REVISED -
	CHECKED -	REVISED -
PLOT DATE = 8/14/2025	DATE - 10/02/2019	REVISED -

STATE OF ILLINOIS  
DEPARTMENT OF TRANSPORTATION


PROJECT DETAIL FOR SINGLE PERPENDICULAR CURB RAMPS WITH  
TURNING SPACE (PD-04)

SCALE: NONE SHEET 1 OF 1 SHEETS STA. TO STA.


F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
876	2025-1093-RS	COOK	33	31
PD-04		CONTRACT NO. 80B19		
		ILLINOIS FED. AID PROJECT		

ADA DETAIL FOR DEPRESSED CORNER CURB RAMPS

PD-05A



PD-05B



DESIGNER NOTES:

- 1) ALL CROSS SLOPES ARE PREFERRED 1.6% (1:64), MAXIMUM 2% (1:50).
- 2) SIDEWALK REALIGNMENT WILL REQUIRE DETAILED DESIGN.
- 3) AREAS SURROUNDED BY PCC/ASPHALT, BUILDINGS, OR ARE NEAR TO DRIVEWAYS, REALIGNED SIDEWALK, UTILITY AND SIGNAL POLES, OR WHEN PRIVATE SIDEWALK TIES IN, WILL REQUIRE DETAILED SURVEY AND DESIGN.
- 4) ALL BRICK CORNERS WILL REQUIRE SUPERVISOR APPROVAL BEFORE USING PROJECT DETAILS

LEGEND

PROPOSED SIDE CURB



EXIST. GRASS



PROPOSED SIDEWALK



DETECTABLE WARNINGS

CONSTRUCTION NOTES:

- 1) ALL CROSS SLOPES ARE PREFERRED 1.6% (1:64), MAXIMUM 2% (1:50) EXCEPT WHEN TRANSITIONING TO EXISTING SIDEWALK

\* MATCH EXISTING SIDEWALK WIDTH

MODEL: pd-5-1 [Sheet]  
FILE NAME: c:\p\work\hisham\mid1063787\ID117225-shh-DistSitus.dgn

	USER NAME = mohammad.hamwi	DESIGNED -	REVISED -
		DRAWN - R. LEDEZMA	REVISED -
		CHECKED -	REVISED -
	PLOT DATE = 8/14/2025	DATE -	REVISED -

STATE OF ILLINOIS  
DEPARTMENT OF TRANSPORTATION


PROJECT DETAIL FOR DEPRESSED CORNER CURB RAMPS  
(PD-05)

SCALE: NONE SHEET 1 OF 1 SHEETS STA. TO STA.


F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
876	2025-1093-RS	COOK	33	32
PD-05		CONTRACT NO. 80B19		
		ILLINOIS	FED. AID PROJECT	

ADA DETAIL FOR PARALLEL CURB RAMPS ADJACENT TO LANDSCAPING

PD-06A



PD-06B



DESIGNER NOTES:

- 1) ALL CROSS SLOPES ARE PREFERRED 1.6% (1:64), MAXIMUM 2% (1:50).
- 2) SIDEWALK REALIGNMENT WILL REQUIRE DETAILED DESIGN.
- 3) AREAS SURROUNDED BY PCC/ASPHALT, BUILDINGS, OR ARE NEAR TO DRIVEWAYS, REALIGNED SIDEWALK, UTILITY AND SIGNAL POLES, OR WHEN PRIVATE SIDEWALK TIES IN, WILL REQUIRE DETAILED SURVEY AND DESIGN.
- 4) ALL BRICK CORNERS WILL REQUIRE SUPERVISOR APPROVAL BEFORE USING PROJECT DETAILS

LEGEND

PROPOSED SIDE CURB

EXIST. GRASS

PROPOSED SIDEWALK

DETECTABLE WARNINGS

CONSTRUCTION NOTES:

- 1) ALL CROSS SLOPES ARE PREFERRED 1.6% (1:64), MAXIMUM 2% (1:50) EXCEPT WHEN TRANSITIONING TO EXISTING SIDEWALK
- \* MATCH EXISTING SIDEWALK WIDTH

MODEL: pd-6-1 [Sheet]  
FILE NAME: c:\p\work\hamwi\1063787\117225-shh-DistShts.dgn

USER NAME	= mohammad.hamwi	DESIGNED	-	REVISED	-
		DRAWN	-	REVISED	-
		CHECKED	-	REVISED	-
PLOT DATE	= 8/9/2025	DATE	= 10/02/2019	REVISED	-

DESIGNED	-
DRAWN	-
CHECKED	-
DATE	-

STATE OF ILLINOIS  
DEPARTMENT OF TRANSPORTATION

PROJECT DETAIL FOR PARALLEL CURB RAMPS  
(PD-06)

SCALE: NONE SHEET 1 OF 1 SHEETS STA. TO STA.

F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
876	2025-1093-RS	COOK	33	33
PD-06		CONTRACT NO. 80B19		
ILLINOIS		FED. AID PROJECT		