



Approach Slab Repair (Full depth) Sequence:

When the pour is stopped at the construction joints in the sequence as shown, the next pour shall not be made until both of the following are met:

1. At least 72 hours shall have elapsed from the end of the previous pour and
2. The concrete shall have attained a minimum modulus of rupture of 650 psi or a minimum compressive strength of 3500 psi

BILL OF MATERIALS

ITEM	UNIT	QUANTITY
APPROACH SLAB REPAIR (FULL DEPTH)	SQ. YD.	56

LEGEND:

- APPROACH SLAB REPAIR (FULL DEPTH)
- Approach Slab Repair (Full Depth) to be completed in sequence

DESIGNED <i>RAD</i>	EXAMINED _____	DATE - _____
CHECKED <i>RB</i>	ENGINEER OF STRUCTURAL SERVICES	
DRAWN <i>RAD</i>	PASSED _____	REVISED _____
CHECKED <i>JAM</i>	ENGINEER OF BRIDGES AND STRUCTURES	REVISED _____

**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**

**IL RTE 83 AT SALT CREEK
APPROACH SLABS REPAIR (S.N. 022-0045)**

SHEET NO. 10 OF 13 SHEETS

F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
344	543-X-B-1-2	DUPAGE	31	13
CONTRACT NO. 60T76			ILLINOIS FED. AID PROJECT	