

48203023

LOCATION		OFFSET	LENGTH	AREA	SHOULDER WIDTH	HOT-MIX ASPHALT SHOULDERS, 6 1/2"
STATION	STATION		(FT)	(SQ FT)	(FT)	(SQ YD)
IL 84						
317+40.00	318+29.71	LT	89.71		4.90	49
317+45.00	318+38.23	RT	93.23		4.70	49
322+19.00	322+95.40	LT	76.40		3.00	26
322+95.40	323+05.00	LT	9.60		3.57	4
322+01.95	323+05.00	RT	103.05		3.00	35
FULTON ROAD						
NORTHWEST QUADRANT				28		4
FULTON STREET						
NORTHEAST QUADRANT				57		7
TOTAL						174

35400450 40701871

LOCATION		LENGTH	AREA	WIDTH	PORTLAND CEMENT CONCRETE BASE COURSE WIDENING, 9 1/2"	HOT-MIX ASPHALT PAVEMENT (FULL-DEPTH), 9 1/2"
STATION	STATION	(FT)	(SQ FT)	(FT)	(SQ YD)	(SQ YD)
IL 84						
317+45.00	318+33.98	88.98		24		238
321+81.00	322+01.95	20.95		2	5	
322+01.95	323+05.00	103.05		1	12	
FULTON ROAD						
9+05.00		9+36.50	31.5	24		84
9+36.50		9+87.79	51.29	24		137
NORTHWEST QUADRANT			233			26
SOUTHWEST QUADRANT			338			38
LT SIDE ON FULTON STREET			555			62
FULTON STREET						
10+12.77		10+31.90	19.13	20		43
10+31.90		10+50.00	18.1	20		41
10+50.00		11+00.00	50	18		100
NORTHEAST QUADRANT			75			9
SOUTHEAST QUADRANT			55			7
TOTAL						785

28000400

LOCATION				PERIMETER EROSION BARRIER
STATION	OFFSET	STATION	OFFSET	FOOT
318+57.81	59.19' RT	319+30.14	57.48' RT	74
318+47.80	68.8' LT	318+88.80	65.9' LT	40
318+88.80	65.9' LT	319+30.14	57.48' RT	134
320+62.72	53.88' LT	320+94.32	58.9' RT	118
320+62.72	53.88' LT	321+04.90	17.8' RT	75
320+94.32	58.9' RT	11+00.00	13.5' RT	108
TOTAL				549

Z0075496

LOCATION		OFFSET	CONCRETE RETAINING WALL REMOVAL
STATION	STATION	LT/RT	(FOOT)
IL 84			
322+69.00	322+80.00	RT	11
TOTAL			11

81200230

LOCATION		OFFSET	CONDUIT EMBEDDED IN STRUCTURE, 2" DIA., PVC
STATION	STATION	LT/RT	FOOT
IL 84			
318+41.54	321+28.81	LT	289
318+57.03	321+42.16	RT	287
TOTAL			576

THE SCHEDULES DO NOT INCLUDE QUANTITIES FOR THE SANITARY LIFT STATION PLANS OR LIGHTING PLANS.