FOR INDEX OF SHEETS, SEE SHEET NO. 2

FAS ROUTE 1780 (OLD US 50) ADT 2025 = 3,000 (ESTIMATED) SU = 13.4% MU = 2.5%

FUNCTIONAL CLASSIFICATION:

MAJOR COLLECTOR

STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION

D-98-063-19

PROPOSED HIGHWAY PLANS

FAS ROUTE 1780 (OLD US 50) SECTION 28CR-1 PROJECT STP-WYBF(464) CULVERT REPLACEMENT ST. CLAIR COUNTY

C-98-082-19

EXISTING
STRUCTURE
S.N. 082-2516

PROPOSED
STRUCTURE

STA. 735+69
OLD US 50 AT
W TRIB E BRANCH
OF SILVER CREEK
LAT: 38.60400' N

> GROSS LENGTH = 40 FT, = 0.008 MILE NET LENGTH = 40 FT, = 0.008 MILE

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

SUBMITTED

October 4, 2024

ENGINEER OF DESIGN AND ENGRON

October 4, 2014

LOCATION OF SECTION INDICATED THUS: -

PRINTED BY THE AUTHORITY OF THE STATE OF ILLINOIS

0 100' 200' 300' — 1"= 100'
0 10' 20' 30' — 1"= 10'
0 50' 100' — 1"= 50'
0 50' 100' — 1"= 30'
0 50' 100' — 1"= 20'

FULL SIZE PLANS HAVE BEEN PREPARED USING STANDARD ENGINEERING SCALES. REDUCED SIZED PLANS WILL NOT CONFORM TO STANDARD SCALES. IN MAKING MEASUREMENTS ON REDUCED PLANS, THE ABOVE SCALES MAY BE USED.

J.U.L.I.E.
JOINT UTILITY LOCATION INFORMATION FOR EXCAVATION
1-800-892-0123
OR 811

PROJECT ENGINEER: BILLIE OWEN
PROJECT MANAGER: BRANDON HUMPHREYS

CONTRACT NO. 76M49

0

INDEX OF SHEETS

- 1. COVER SHEET
- 2. INDEX OF SHEETS, HIGHWAY STANDARDS, GENERAL NOTES, & COMMITMENTS
- 3. SUMMARY OF QUANTITIES
- 4-5. TYPICAL SECTIONS
- 6. SCHEDULES OF QUANTITIES
- 7. LOCATION MAP
- 8-9. ALIGNMENTS, TIES, AND BENCHMARKS OLD US 50
- 10. OLD US 50 CULVERT REPLACEMENT EXISTING AND REMOVAL PLAN
- 11. OLD US 50 CULVERT REPLACEMENT ROADWAY PLAN AND PROFILE
- 12. PAVEMENT PATCHING (SPECIAL) DETAIL SHEET
- 13. EROSION CONTROL PLAN OLD US 50
- 14. DETOUR ROUTE MAP OLD US 50
- 15. GENERAL PLAN AND ELEVATION STRUCTURE NO. 082-2579
- 16-17. MULTI-CELL PRECAST CONCRETE BOX CULVERT APRON END SECTION DETAILS STRUCTURE NO. 082-2579
- 18. BORING LOGS SHEET

HIGHWAY STANDARDS

000001-08	STANDARD SYMBOLS, ABBREVIATIONS, AND PATTERNS
001001-02	AREAS OF REINFORCEMENT BARS
004006	DECIMAL OF AN INCLUAND OF A FOOT

001006 DECIMAL OF AN INCH AND OF A FOOT 280001-07 TEMPORARY EROSION CONTROL SYSTEMS

420001-10 PAVEMENT JOINTS 442101-09 CLASS B PATCHES

515001-04 NAME PLATE FOR BRIDGES

630001-13 STEEL PLATE BEAM GUARDRAIL

630106-02 LONG-SPAN GUARDRAIL OVER CULVERT
630301-09 SHOULDER WIDENING FOR TYPE 1 (SPECIAL) GUARDRAIL TERMINALS

630301-09 SHOULDER WIDENING FOR TYPE I (SPECIAL) GUARDRAIL TERMINALS

701001-02 OFF-RD OPERATIONS, 2L, 2W, MORE THAN 15' AWAY

701006-05 OFF-RD OPERATIONS, 2L, 2W, 15' TO 24' FROM PAVEMENT EDGE

701011-04 OFF-RD MOVING OPERATIONS, 2L, 2W, DAY ONLY

701201-05 LANE CLOSURE, 2L, 2W, DAY ONLY, FOR SPEEDS ≥ 45 MPH 701311-03 LANE CLOSURE, 2L, 2W, MOVING OPERATIONS - DAY ONLY

701901-09 TRAFFIC CONTROL DEVICES

725001-01 OBJECT AND TERMINAL MARKERS

782006-01 GUARDRAIL AND BARRIER WALL REFLECTOR MOUNTING DETAILS

BLR 21-9 TYPICAL APPLICATION OF TRAFFIC CONTROL DEVICES FOR CONSTRUCTION ON RURAL LOCAL HIGHWAYS

420701-03 PAVEMENT WELDED WIRE REINFORCEMENT

780001-05 TYPICAL PAVEMENT MARKINGS

GENERAL NOTES

1. THE UTILITIES KNOWN TO HAVE FACILITIES WITHIN THE PROJECT AREA ARE AS FOLLOWS:

- AMEREN ILLINOIS
- AT&T ILLINOIS
- CHARTER COMMUNICATIONS, INC.
- CLEARWAVE COMMUNICATIONS
- FRONTIER COMMUNICATIONS
- SLM WATER COMMISSION VILLAGE OF SUMMERFIELD
- TRI-TOWNSHIP WATER DISTRICT
- 2. THE TWO CHANGEABLE MESSAGE SIGNS REQUIRED FOR THIS PROJECT SHALL BE IN PLACE AND IN OPERATION TWO WEEKS PRIOR TO ANY LANE CLOSURE AT LOCATIONS DETERMINED BY THE ENGINEER. THE ENGINEER WILL PROVIDE THE MESSAGE TO THE CONTRACTOR FOR THE

THE ENGINEER. THE ENGINEER WILL PROVIDE THE MESSAGE TO THE CONTRACTOR FOR THE TWO WEEKS PRIOR TO CONSTRUCTION AND DURING CONSTRUCTION.

- 3. THE CONTRACTOR SHALL PROVIDE POSITIVE AND ADEQUATE DRAINAGE AT ALL TIMES.
- 4. ALL ELEVATIONS REFER TO THE USGS MEAN SEA LEVEL DATUM, NAVD 88.
- 5. THE DEPARTMENT STRONGLY ENCOURAGES THE PRIME CONTRACTOR AND THEIR APPROVED SUB-CONTRACTORS TO HIRE MINORITY, WOMEN AND DISADVANTAGED INDIVIDUALS FROM ITS FEDERALLY FUNDED HIGHWAY CONSTRUCTION CAREERS TRAINING PROGRAM (HCCTP) TO HELP MEET WORKFORCE AND TRAINEE GOALS. THIS PROGRAM IS TRAINING MINORITIES, WOMEN AND DISADVANTAGED INDIVIDUALS IN HIGHWAY CONSTRUCTION-RELATED SKILLS, E.G., MATH FOR THE TRADES, JOB READINESS, TECHNICAL SKILLS COURSEWORK (CARPENTRY, CONCRETE FLATWORK, BLUEPRINT READING, SITE PLANS, SITE WORK, TOOLS USE, ETC.) AND OSHA 10 HOUR CERTIFICATION, TO PREPARE THEM FOR A CAREER IN THE HIGHWAY CONSTRUCTION TRADES. GRADUATES ARE WELL-TRAINED AND READY TO BECOME PRODUCTIVE ENTRY-LEVEL CONSTRUCTION WORKERS. CONTACT THE DISTRICT 8 EEO OFFICE AT 618-346-3360 AND/OR THE HCCTP COORDINATOR AT 618-874-6528 TO LEARN MORE ABOUT THE PROGRAM AND FOR ASSISTANCE IN MEETING WORKFORCE AND TRAINEE GOALS.

COMMITMENTS

NONE

REV - MS

MODEL: General Notes Sheet [Sheet]
FILE NAME: c:\pw_work\pwidot\humphreysb\

USER NAME = Brandon.Humphreys	DESIGNED -	REVISED -
	DRAWN -	REVISED _
	CHECKED -	REVISED _
PLOT DATE = 8/2/2024	DATE -	REVISED -

SCALE:

				20% STATE
				BOX CULVERT
CODE			TOTAL	0004
NO.	ITEM	UNIT	QUANTITY	RURAL
20200100	EARTH EXCAVATION	CU YD	69	69
20700220	POROUS GRANULAR EMBANKMENT	CU YD	174	174
25100630	EROSION CONTROL BLANKET	SQ YD	36	36
23100030	ENGLISH GOINTIGE BLANKET	04 15	30	30
28000305	TEMPORARY DITCH CHECKS	FOOT	14	14
29400407	CTONE DIDDAD OLACCAA	20 VD	122	422
28100107	STONE RIPRAP, CLASS A4	SQ YD	133	133
28200200	FILTER FABRIC	SQ YD	81	81
31102000	SUBBASE GRANULAR MATERIAL, TYPE C	CU YD	17	17
44200050	WELDED WIRE REINFORCEMENT	SQ YD	110	110
44213200	SAW CUTS	FOOT	154	154
44213204	TIE BARS 3/4"	EACH	45	45
48101200	AGGREGATE SHOULDERS, TYPE B	TON	20	20
50100100	REMOVAL OF EXISTING STRUCTURES	EACH	1	1
30100100	NEW VAL OF EXISTING STRUCTURES	LACIT	<u>'</u>	'
51500100	NAME PLATES	EACH	1	1
54001001	BOX CULVERT END SECTIONS, CULVERT NO. 1	EACH	2	2
54010606	PRECAST CONCRETE BOX CULVERTS 6' X 6'	FOOT	64	64
	1			

					CONSTR. COD
					80% FEDERAL 20% STATE
Γ	ì				BOX CULVER
	CODE			TOTAL	0004
1	NO.	ПЕМ	UNIT	QUANTITY	RURAL
ŀ	110.	TI EW	ONT	QOAMIT	TOTAL
	63000003	STEEL PLATE BEAM GUARDRAIL, TYPE A, 9 FOOT POSTS	FOOT	338	338
	63000360	LONG-SPAN GUARDRAIL OVER CULVERT, 18 FT 9 IN SPAN	FOOT	88	88
	63100167	TRAFFIC BARRIER TERMINAL, TYPE 1 (SPECIAL) TANGENT	EACH	4	4
-	03 100 107	TRAITIC BARRIER TERMINAL, TIFE T (GFECIAL) TANGENT	EACIT	4	4
	63200310	GUARDRAIL REMOVAL	FOOT	476	476
	67100100	MOBILIZATION	L SUM	1	1
	70100450	TRAFFIC CONTROL AND PROTECTION, STANDARD 701201	L SUM	1	1
-	70107025	CHANGEABLE MESSAGE SIGN	CAL DA	38	38
	72501000	TERMINAL MARKER - DIRECT APPLIED	EACH	4	4
	78001120	PAINT PAVEMENT MARKING - LINE 5"	FOOT	90	90
	78200005	GUARDRAIL REFLECTORS, TYPE A	EACH	7	7
	X4420201	PAVEMENT PATCHING (SPECIAL)	SQ YD	110	110
	X5810103	MEMBRANE WATERPROOFING SYSTEM FOR BURIED STRUCTURES	SQ YD	63	63
	X7011800	TRAFFIC CONTROL AND PROTECTION, STANDARD BLR 21	LSUM	1	1
	Z0016702	DETOUR SIGNING	L SUM	1	1
- 11	/ () () () () / () / ()	IDETOUR SIGNING	I LOUN	1 1	I I


* SPECIALTY ITEM

REV - MS

 USER NAME = Brandon.Humphreys	DESIGNED ==	REVISED -								F.A.S.	SECTION	COUNTY	TOTAL	SHEE
	DRAWN -	REVISED _	STATE OF ILLINOIS		S	UMMAR	y of Qu	ANTITIES		1780	28CR-1	ST. CLAIR	18	3
	CHECKED -	REVISED =	DEPARTMENT OF TRANSPORTATION							i		CONTRAC	T NO. 76N	л49
PLOT DATE = 8/13/2024	DATE _	REVISED -		SCALE:	SHEET 1	OF 1	SHEETS	STA.	TO STA.	1	ILLINOIS FED. A			

CONSTR. CODE 80% FEDERAL

DDEL: Summary of Quantities Sheet [Sheet]




LEGEND

- (1) EXISTING BITUMINOUS SURFACE COURSE, 1 1/2"
- (2) EXISTING BITUMINOUS BINDER COURSE, 3/4"
- (3) EXISTING BITUMINOUS RESURFACING, 6 1/2"
- (4) EXISTING P.C.C. PAVEMENT, 9"
- (5) EXISTING P.C.C. PAVEMENT, 9"-7"-9"
- (6) EXISTING AGGREGATE SHOULDER
- (7) EXISTING STEEL PLATE BEAM GUARDRAIL, TYPE A, 6' POSTS
- (8) EXISTING CULVERT HEADWALL
- (9) PROPOSED PAVEMENT PATCHING (SPECIAL)
- (10) PROPOSED SUBBASE GRANULAR MATERIAL, TY C, 6"
- (11) PROPOSED AGGREGATE SHOULDER, TY B
- (12) PROPOSED STEEL PLATE BEAM GUARDRAIL, TYPE A, 9' POSTS
- (13) PROPOSED LONG-SPAN GUARDRAIL OVER CULVERT
- (14) PROPOSED CULVERT HEADWALL

USER NAME = Brandon.Humphreys	DESIGNED -	REVISED -				F.A.S. RTF	SECTION	COUNTY	TOTAL SHEE
	DRAWN -	REVISED -	STATE OF ILLINOIS		EXISTING TYPICAL SECTIONS	1780	28CR-1	ST. CLAIR	18 4
	CHECKED -	REVISED -	DEPARTMENT OF TRANSPORTATION					CONTRAC	T NO. 76M49
PLOT DATE = 8/26/2024	DATE -	REVISED -		SCALE:	SHEET 1 OF 2 SHEETS STA. TO STA.		ILLINOIS FED. AID	PROJECT	

FILE NAME: c:\pw_work\pwidot\humphreysb\



LEGEND

- (1) EXISTING BITUMINOUS SURFACE COURSE, 1 1/2"
- (2) EXISTING BITUMINOUS BINDER COURSE, 3/4"
- (3) EXISTING BITUMINOUS RESURFACING, 6 1/2"
- (4) EXISTING P.C.C. PAVEMENT, 9"
- (5) EXISTING P.C.C. PAVEMENT, 9"-7"-9"
- (6) EXISTING AGGREGATE SHOULDER
- (7) EXISTING STEEL PLATE BEAM GUARDRAIL, TYPE A, 6' POSTS
- (8) EXISTING CULVERT HEADWALL
- (9) PROPOSED PAVEMENT PATCHING (SPECIAL)
- (10) PROPOSED SUBBASE GRANULAR MATERIAL, TY C, 6"
- (11) PROPOSED AGGREGATE SHOULDER, TY B
- (12) PROPOSED STEEL PLATE BEAM GUARDRAIL, TYPE A, 9' POSTS
- (13) PROPOSED LONG-SPAN GUARDRAIL OVER CULVERT
- (14) PROPOSED CULVERT HEADWALL

USER NAME = Brandon.Humphreys	DESIGNED -	REVISED -							F.A.S. RTE.	SECTION	COUNTY	TOTAL	SHEET NO.
	DRAWN -	REVISED -	STATE OF ILLINOIS		PRO		TYPICAL SECTIONS		1780	28CR-1	ST. CLAIR	18	5
	CHECKED -	REVISED -	DEPARTMENT OF TRANSPORTATION								CONTRAC	CT NO. 76	6M49
PLOT DATE = 10/1/2024	DATE -	REVISED -		SCALE:	SHEET 2	OF 2	SHEETS STA.	TO STA.		ILLINOIS FED, AID	PROJECT		

	EROSION CONTROL SCHEDULE												
CLASS 2A NUTRIENT NUTRIENT NUTRIENT METHOD 2 BLANKET CHECKS CLASS A4 FABR										FILTER FABRIC			
STATION	OFFSET	ТО	STATION	OFFSET	ACRE	POUND	POUND	POUND	ACRE	SQ YD	FOOT	SQ YD	SQ YD
	OLD US 50												
735+47	23.8' LT	ТО	735+90	31.1' LT							14	70.1	40.2
735+49	15.6' LT	ТО	735+89	23.8' LT	0.003	0.3	0.3	0.3	0.003	16.6		5.1	
735+49	14.7' RT	ТО	735+89	23.5' RT	0.004	0.4	0.4	0.4	0.004	19.2		5.1	
735+53	23.5' RT	ТО	735+84	30.9' RT								52.6	40.2
				SUBTOTALS	0.007	0.7	0.7	0.7	0.007	35.8	14	132.9	80.4
				TOTALS	0.01	1	1	1	0.01	36	14	133	81

GUARDRAIL SCHEDULE											
STATION TO		STATION	LENGTH OF NEED	STEEL PLATE BEAM GUARDRAIL, TYPE A, 9 FOOT POSTS	LONG-SPAN GUARDRAIL OVER CULVERT, 18 FT 9 IN SPAN	TRAFFIC BARRIER TERMINAL, TYPE 1 (SPECIAL) TANGENT	GUARDRAIL REMOVAL	TERMINAL MARKER - DIRECT APPLIED	GUARDRAIL REFLECTORS, TYPE A	NOTES	
			FOOT	FOOT	FOOT	EACH	FOOT	EACH	EACH		
						OLD US 50					
734+47	ТО	736+88	243.7	174.9	43.8	2	244	2	4	WESTBOUND OLD US 50	
734+54	TO	736+83	231.2	162.4	43.8	2	232	2	3	EASTBOUND OLD US 50	
			SUBTOTALS	337.3	87.6	4	476	4	7		
			TOTALS	338	88	4	476	4	7		

	PATCHING SCHEDULE											
STATION	то	STATION	LENGTH	WIDTH	SAW CUTS	TIE BARS, 3/4"	WELDED WIRE REINFORCEMENT	PAVEMENT PATCHING (SPECIAL)				
			FOOT	FOOT	FOOT	EACH	SQ YD	SQ YD				
	OLD US 50											
735+49	735+49 TO 735+89 40 24.7 154 45 110 110											
				TOTALS	154	45	110	110				

PAVEMENT MARKINGS SCHEDULE										
					PAVEMENT RKINGS					
STATION	ТО	STATION	LENGTH	LIN	E 5 - INCH					
STATION	10	JIAITON		SOLID	SKIP-DASH					
				WHITE	YELLOW					
			FOOT	FOOT	FOOT					
		C	LD US 50							
735+49	ТО	735+89	40	80	10					
			TOTALS		90					


	PAVING SCHEDULE									
LO	CATI	ON	LENGTH	SUBBASE GRANULAR MATERIAL, TY C	AGGREGATE SHOULDERS, TYPE B					
STATION	ТО	STATION	FOOT	CU YD	TON					
			OLD (JS 50						
735+49	TO	735+54	5		2.6					
735+54	TO	735+61	7	3.2	4.0					
735+61	TO	735+69	8	5.1	3.1					
735+69	ТО	735+76	7	5.1	3.1					
735+76	ТО	735+84	8	3.2	4.0					
735+84	ТО	735+89	5		2.6					
	2	S	UBTOTALS	16.5	19.4					
			TOTALS	1 7	20					


SCALE:


USER NAME = Brandon.Humphreys	DESIGNED -	REVISED -
	DRAWN -	REVISED -
	CHECKED -	REVISED -
PLOT DATE = 10/1/2024	DATE -	REVISED -

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

		F.A.S. RTE	SECTION	COUNTY	Y TOTAL SHEE NO.	
SCHEDULE OF QUANTITIES	1780	28CR-1	ST. CLAIR	18	6	
				CONTRACT	ΓNO. 76	И49
HEET 1 OF 1 SHEETS STA.	TO STA.		ILLINOIS FED. AID PROJECT			







3. ALL ELEVATIONS REFER TO USGS MEAN SEA LEVEL DATUM, NAVD 88.


A CONCRETE SLAB OF A LIFT STATION IN THE

SOUTHEAST QUADRANT OF OLD US 50 &

SUMMERFIELD ROAD.

476.808'

BM 2



PLOT DATE = 8/9/2024


DATE

DEPARTMENT OF TRANSPORTATION

SHEET 2 OF 2 SHEETS STA. TO STA.

SCALE: NTS

CONTRACT NO. 76M49



Peralte-Clarkus Clark

USER NAME = \$USER\$ REVISED DRAWN REVISED CHECKED -REVISED -DATE - 7/30/2024

STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION


OLD US 50 CULVERT REPLACEMENT EXISTING AND REMOVAL PLAN SHEET 1 OF 1 SHEETS STA. 733+00 TO STA. 739+00


SCALE: 1"=20'


COUNTY TOTAL SHEET NO.

ST. CLAIR 18 10 SECTION 1780 28CR-1 CONTRACT NO.76M49

Long Section Number








NOTES

A DETOUR ROUTE WILL BE USED TO MAINTAIN TRAFFIC DURING CONSTRUCTION. THE ROADWAY AT THE PROJECT LOCATION WILL BE CLOSED TO THROUGH TRAFFIC. LOCAL ACCESS IS TO BE MAINTAINED TO ALL ENTRANCES OUTSIDE OF THE IMPROVEMENT

SIGNS WILL BE PLACED 100' PRIOR TO INTERSECTION OR TO FIT FIELD CONDITIONS, UNLESS OTHERWISE NOTED OR DIRECTED BY




WORK AREA





TRAFFIC FLOW

TYPE III BARRICADE


DETOUR SIGN







CUSTOM SIGN DETAIL



BACKGROUND TYPE : ORANGE 1.5" RADIUS, 0.6" BORDER, 0.4" INDENT, BLACK ON ORANGE "OLD", D 2K, "ROUTE 50", D 2K QUANTITY: 7

USER NAME = Brandon.Humphreys	DESIGNED -	REVISED -
	DRAWN -	REVISED -
	CHECKED -	REVISED -
PLOT DATE = 8/6/2024	DATE -	REVISED -

STATE OF ILLINOIS **DEPARTMENT OF TRANSPORTATION**


DETOUR ROUTE MAP OLD US 50 SHEET 1 OF 1 SHEETS STA. TO STA.

EAST


OLD


SCALE: NTS

A.S. RTE	SECTION	COUNTY	TOTAL SHEETS	SHE	
1780	28CR-1		ST. CLAIR	18	14
		CONTRACT	NO. 76	И49	
	ILLINOIS	PROJECT			




8/5/2024 4:54:38 PM





END VIEW




PLAN


GENERAL NOTES


- Box Culvert End Sections shall be constructed according to the requirements of Section 540 of the Standard Specifications except as modified herein. End sections will be paid for at the contract unit price per each for Box Culvert End Sections.
- 2. Box section dimensions, materials, and reinforcement details for Box Culvert End Sections shall be according to the requirements for ASTM C 1577 as required for the design of the portion of the culvert within the limits of Precast Concrete Box Culverts except as modified herein.
- The details contained herein are for constructing the end sections using cast-in-place (CIP) construction. The Contractor may propose to furnish the end sections using precast construction methods and the end sections may consist of multiple precast concrete segments. The Contractor shall be responsible for determining all details associated with the precast option including any strengthening or stiffening provisions necessary for handling the precast segments. Conceptual details followed by shop drawings and design calculations sealed by an Illinois Licensed Structural Engineer shall be submitted to the Engineer for review and approval. Elements of the precast option shall at a minimum result in the same wingwall geometry and not have a thickness less than that detailed herein. The option to construct the end sections using precast construction methods shall be at no additional charge.
- Shop drawings that detail slab thickness and reinforcement layout for the Box Culvert End Sections shall be provided to the Engineer for review and approval. Reinforcement bars not detailed herein shall be detailed with a clear distance at the end of the reinforcement not less than $\frac{1}{2}$ " nor more than 2".
- The contractor may use reinforcement bars in lieu of welded wire reinforcement (WWR).
 Reinforcement bars shall be limited to the sizes of #3 through #5 bars, a maximum spacing of the lesser of 8" or the member thickness, and shall result in an area of reinforcement equal to or greater than that provided by the WWR. Minimum lap lengths detailed herein are applicable to WWR and reinforcement bars.
- 6. Reinforcement (circumferential and longitudinal) in the precast concrete box culvert segments immediately adjacent to the box culvert end sections that is being lapped with the end section reinforcement shall not be less than that required by ASTM C 1577 for the design fill height or the reinforcement detailed for the end section, whichever is greater.
- One drain hole shall be provided in each wingwall for end sections of box culverts having an
 opening with a clear rise greater than 3 ft. The drain hole shall be located within 1/3 of the clear
 rise of the box culvert and shall conform to the requirements of Article 503.11 of the Standard
 Specifications.


APRON END SECTION DIMENSIONS

			Double	e Cell	Triple	Cell				
Span (S)	Rise (R)	Tt , Tb , & Ts	Α	В	С	D	E	Concrete Cu. Yd.	E	Concrete Cu. Yd.
6'-0"	6'-0"	8"	7'-5"	4'-3"	6'-11½"	9'-10"	29'-91/4"	12.4		\leq










SECTION B-B


(Top slab at upstream end)

SECTION B-B (Bottom slab)


SECTION C-C



(Top slab at downstream end)



ALT. SECTION D-D



Extend precast concrete box culvert reinforcement into end section. (Bend as necessary to provide 2" clear cover.) #4 s or s1 bars Max. spa. = Tt

SECTION D-D


TOEWALL CONSTRUCTION SEQUENCE 1. Perform excavation and construct toewall.

- 2. Backfill accordingly and prepare bedding for box culvert end sections.
- 3. Construct remainder of box culvert end section.


Note:

If soil conditions permit, the toewall may be poured monolithically with the bottom slab of the end section using Alt. Section D-D subject to approval from the Engineer.





SECTION F-F



BAR s

BAR s1

	USER NAME =	DESIGNED EHK	REVISED -
-		CHECKED JWM	REVISED -
	PLOT SCALE =	DRAWN BPH	REVISED -
	PLOT DATE =	CHECKED JWM	REVISED -

STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION

COUNTY TOTAL SHEETS NO.

ST. CLAIR 18 17 SECTION MULTI-CELL PRECAST CONCRETE BOX CULVERT APRON END 1780 28CR-1 SECTION DETAILS - 2 CONTRACT NO. 76M49 SHEET 3 OF 3 SHEETS

Illinois Dep of Transpo Division of Highways Illinois Department of Transpo ROUTEAS 1780 (Old US 50 PESCI	ortation		Old	LUS 50) at W	Tributary E Branch of S	Silver		ED P		8/1	
SECTION128CR-1									יבט או		EG - N	ш
COUNTY St. Clair DI									1	40# A	utoma	tic
STRUCT. NO. 082-2516 Station 735+70		D E P	B L O	U C S	M 0 1	Surface Water Elev. Stream Bed Elev.	n/a	a ft ft	D E P	B L O	U C S	M 0
BORING NO. B-1 Station 735+43 Offset 7.70ft N Ground Surface Elev. 474.57	 ft	H (ft)	W S (/6")	Qu (tsf)	S T (%)	Groundwater Elev.: First Encounter Upon Completion Aftern/a Hrs.	n/a	ft	H (ft)	W S (/6")	Qu (tsf)	S T (%
Asphalt ~ 4"	473.6	_				End of Boring						
Concrete - slow drilling Brown Silty Clay	i	_	6 3	1.25P P	25				_			
A. Ab	471.1		2	4.05					_			
As Above		5	5	1.05 B	23				25			
ST 6.0 - 8.0	468.6	_	-	avg.								
	466.1	_	1	0.32	20.0							
Browish-gray Clay		10	2	0.75 P	24				30			
		_	1 2	1.7	22				_			ř.
	461.6		4	В					_			
Becomes Brown & Gray		-15	2 4	1.92 B	24							
	458.6		WH									
Brown sandy Clay, w/ gravel			2 2	0.26 B	17							
		_	3									

The Unconfined Compressive Strength (UCS) Fallure Mode is indicated by (B-Bulge, S-Shear, P-Penetrometer)
The SPT (N value) is the sum of the last two blow values in each sampling zone (AASHTO T206)

BBS, from 137 (Rev. 8-99)

P	Illinois Department of Transportation Division of Highways
	Division of Highways

ROUTEAS 1780 (Old US 50 PESCRIPTION

SCALE:

SOIL BORING LOG

Page 1 of 1

 Old US 50 at W Tributary E Branch of Silver
 LOGGED BY
 KEG - MTH

SECTION _____128CR-1 LOCATION _, SEC. , TWP. , RNG. , PM COUNTY St. Clair DRILLING METHOD Hollow Stem Auger HAMMER TYPE 140# Automatic D B U M S L C O P O S I T W S Qu T D B U M E L C O P O S I T W S H S Qu T M Surface Water Elev. ____ STRUCT. NO. n/a_ft Stream Bed Elev. ft Station Groundwater Elev.: BORING NO. H S Qu S Qu T First Encounter
Upon Completion 735+43 7.70ft N n/a ft Station Offset

Ground Surface Elev. 474.57	ft	(ft)	(/6")	(tsf)	(%)	After _ n/a _ Hrs.	n/a	ft	(ft)	(/6")	(tsf)	(%)
						End of Boring						
Asphalt ~ 4"	_473.6											
Concrete - slow drilling	1		6						_			Ì
Brown Silty Clay			6	1.25P	25							
		_	3	Р					_			
	471.1		{									
	471.1	_	2						_			
As Above			2	1.05	23				_			l
		-5	5	В					-25			
		_										
	468.6											
ST 6.0 - 8.0		_	-	avg.	avg							
0.0 = 0.0			-	0.92								
	466.1											
			1									
Browish-gray Clay		_	2	0.75 P	24				_			
		10	3	P					-30			
		_							-30			
			1									
			2	1.7	22				_			
			4	В					_			
	461.6		-									
Becomes Brown & Gray			1						_			
Becomes Brown a Gray			2	1.92	24							
		-15		В					-35			
	458.6											
B		_	WH	0.00	17							
Brown sandy Clay, w/ gravel			2 2	0.26 B	17							
		_	-						-			
			ĺ									
			3									
			3	1.0	14							
	454.6	-20	6	В					-40			

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by (B-Bulge, S-Shear, P-Penetrometer)
The SPT (N value) is the sum of the last two blow values in each sampling zone (AASHTO T206)

BBS, from 137 (Rev. 8-99)

USER NAME = Brandon.Humphreys	DESIGNED -	REVISED -
	DRAWN -	REVISED -
	CHECKED -	REVISED -
PLOT DATE = 7/17/2024	DATE -	REVISED -

	BORING LOGS SHEET					F.A.S. RTE	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
						1780	28CR-1	ST, CLAIR	18	18
								CONTRAC	T NO. 76	M49
	SHEET 1	OF 1	SHEETS	STA.	TO STA.		ILLINOIS F	ED. AID PROJECT		