## GENERAL NOTES

Reinforcement bars shall conform to the requirements of ASTM A 706 Gr 60. Reinforcement bars designated (E) shall be epoxy coated.

Plan dimensions and details relative to existing plans are subject to nominal construction variations. The Contractor shall field verify existing dimensions and details affecting new construction and make necessary approved adjustments prior to construction or ordering of materials. Such variations shall not be cause for additional compensation for a change in scope of the work, however, the Contractor will be paid for the quantity actually furnished at the unit price bid for the work.

Layout of slope protection system may be varied to suit ground conditions in the field as directed by the Engineer.

The Contractor is advised that the existing PPC Deck Beams are in a deteriorated condition with reduced load carrying capacity. It is the contractor's responsibility to account for the condition of the beams when developing construction procedures for removal and replacement of the superstructure. The contractor shall submit a demolition plan. See Section 501 of the Standard Specifications.

The minimum thickness of the concrete overlay shall be 5",  $9^3_A$ " at the back of curb, and varies as required to adjust for the new profile grade and beam camber.

See Roadway Plans for RWIS details.

The Illinois Department of Transportation is NOT the owner of record for this bridge. Those seeking historic, as-built or other existing documents and plans must contact the owner of record to make arrangements for access to this information.

Sheet No Sheet Title  1 General Plan & Elevation  2 General Data  3 Stage Construction Details I  4 Stage Construction Details II  5 Temporary Concrete Barrier  6 Top of CWS Elevations I  7 Top of CWS Elevations II  8 Top of West Approach Slab Elevations  9 Top of East Approach Slab Elevations	
2 General Data 3 Stage Construction Details I 4 Stage Construction Details II 5 Temporary Concrete Barrier 6 Top of CWS Elevations I 7 Top of CWS Elevations II 8 Top of West Approach Slab Elevations	
7 Top of CWS Elevations II 8 Top of West Approach Slab Elevations	
7 Top of CWS Elevations II 8 Top of West Approach Slab Elevations	
7 Top of CWS Elevations II 8 Top of West Approach Slab Elevations	
7 Top of CWS Elevations II 8 Top of West Approach Slab Elevations	
7 Top of CWS Elevations II 8 Top of West Approach Slab Elevations	
8 Top of West Approach Slab Elevations	
9 Top of East Approach Slab Elevations	
10 Superstructure	
11 Superstructure Details	
12 West Bridge Approach Slab Details	
13 East Bridge Approach Slab Details	
14 Bridge Approach Slab Details	
15 Wyoming 2-Tube Steel Railing	
16 Wyoming 2-Tube Steel Railing Details	
17 Framing Plan	
18 17x48 PPC Deck Beams - 27'-2"	
19	
. 20 17x48 PPC Deck Beam Details	
21 West Abutment	
22 East Abutment	
23 Piers 1 & 2	
24 Metal Shell Pile Details	
25 Bar Splicer Assembly and Mechanical Splicer Details	
26 Boring Logs I	
27 Boring Logs II	
28 Boring Logs III	
29 Boring Logs IV	
30 Boring Logs V	
31 Traffic Barrier Terminal, Type 6A (Special) I	
32 Traffic Barrier Terminal, Type 6A (Special) II	
33 Attenuator Connection & Guardrail Connection Details	

## TOTAL BILL OF MATERIAL

ITEM	UNIT	SUPER	SUB	TOTAL
Stone Riprap, Class A4	Sq. Yd.	-	520	520
Filter Fabric	Sg. Yd.	-	520	520
Protective Coat	Sq. Yd.	755	18	773
Removal of Existing Structures	Each	-	-	1
Structure Excavation	Cu. Yd.	-	204	204
Concrete Structures	Cu. Yd.	-	108.6	108.6
Concrete Superstructure	Cu. Yd.	<i>1</i> 56.3	-	156.3
Bridge Deck Grooving	Sg. Yd.	648	-	648
Concrete Encasement	Cu. Yd.	-	21.6	21.6
Precast Prestressed Concrete Deck Beams (17" Depth)	Sq. Ft.	3986	-	3986
Reinforcement Bars, Epoxy Coated	Pound	39,660	12,460	52,120
Bar Splicers	Each	234	120	354
Furnishing Metal Shell Piles 12'' x 0.25"	Foot		1400	1400
Driving Piles	Foot	-	1400	1400
Test Pile Metal Shells	Éach	-	4	4
Name Plates	Each		1	1
Geocomposite Wall Drain	Sq. Yd.	-	127	127
Pipe Underdrains for Structures, 4"	Foot	-	145	145
Porous Granular Embankment, Special	Cu. Yd.		102	102
Concrete Wearing Surface (Variable Depth)	Cu. Yd.	90	-	90
Steel Railing (Special)	Foot	210	-	210
Temporary Sheet Piling	Sq. Ft.	-	1747	1747
		•		

Bollinger, Lach & Associates, Inc.

	USER NAME = gonzalo	DESIGNED	JM7
		CHECKED	JJI
IÇ.	PLOT SCALE =	DRAWN	GM
	PLOT DATE = 8/17/2012	CHECKED	JJI

REVISED -	McHENRY COUNTY	
REVISED -		
REVISED -	DIVISION OF TRANSPORTATION	0 D E E
REVISED -	LAWRENCE ROAD BRIDGE OVER PISCASAW	CREE