STATE OF ILLINOIS LAMRENCE 24 1 11-09-2018 LETTING ITEM 027 DEPARTMENT OF TRANSPORTATION **DIVISION OF HIGHWAYS PROPOSED** FOR INDEX OF SHEETS, SEE SHEET NO. 2 HIGHWAY PLANS **F.A.P. ROUTE 332 (IL 1) SECTION 18B** ADT (2017) = 4450PROJECT NHPP-955F(217) BRIDGE REPLACEMENT WITH CULVERT **LAWRENCE COUNTY** C-97-064-13 **EXISTING SN 051-8000:** REINFORCED CONCRETE SLAB BRIDGE R 12 W R 11 W SURVEY STATION 304+33.80 SKEW 0' PROPOSED SN 051-2009 BIRDS CAST-IN-PLACE DOUBLE CELL 12' X 5' SURVEY STATION 304 + 33.80 LOCATION OF SECTION INDICATED THUS: - -SKEW 0' 5 STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION FULL SIZE PLANS HAVE BEEN PREPARED USING STANDARD ENGINEERING SCALES. REDUCED SIZED PLANS WILL NOT PINKSTAFF CONFORM TO STANDARD SCALES. IN MAKING MEASUREMENTS 5 ON REDUCED PLANS, THE ABOVE SCALES MAY BE USED. J.U.L.LE. CREEK JOINT UTILITY LOCATION INFORMATION FOR EXCAVATION 1-800-892-0123 OR 811 DIRECTOR OF HIGHWAYS PROJECT IMPLEME PROJECT ENGINEER: DEBRA BARRETT PRINTED BY THE AUTHORITY PROJECT MANAGER: BRIAN BIERMAN OF THE STATE OF ILLINOIS GROSS LENGTH = 156 FT. = 0.030 MILE **CONTRACT NO. 74619** NET LENGTH = 156 FT. = 0.030 MILE

021

0

0

0

0

#### GENERAL NOTES

PLAN DIMENSIONS AND DETAILS RELATIVE TO THE EXISTING STRUCTURE HAVE BEEN TAKEN FROM EXISTING PLANS AND ARE SUBJECT TO NOMINAL CONSTRUCTION VARIATIONS. IT SHALL BE THE CONTRACTOR'S RESPONSIBILITY TO VERIFY DIMENSIONS AND DETAILS IN THE FIELD AND MAKE NECESSARY APPROVED ADJUSTMENTS PRIOR TO CONSTRUCTION OR ORDERING OF MATERIAL.

SUCH VARIATIONS SHALL NOT BE CAUSE FOR ADDITIONAL COMPENSATION FOR A CHANGE IN THE SCOPE OF THE WORK. THE CONTRACTOR WILL BE PAID FOR THE QUANTITY FURNISHED AT THE UNIT PRICE BID FOR THE WORK.

THE CONTRACTOR SHALL PROVIDE INTERNET ACCESS TO THE HOT-MIX ASPHALT PLANT QUALITY CONTROL LAB SO THAT HOT-MIX ASPHALT PLANT REPORTS CAN BE E-MAILED TO THE DISTRICT HEADQUARTERS. THIS WORK SHALL BE INCLUDED IN THE COST OF HOT-MIX ASPHALT ITEMS.

TREES 3" OR GREATER IN DIAMETER AT BREAST HEIGHT SHALL NOT BE CLEARED FROM APRIL 1ST THROUGH SEPTEMBER 30TH OF ANY GIVEN YEAR.

EXCAVATION FOR THE PORTLAND CEMENT CONCRETE BASE COURSE 10" WHICH CONSISTS OF 3 FT WIDE, 8" THICK

HMA SHOULDER AND AGGREGATE SHOULDER SHALL BE PAID FOR AS EARTH EXCAVATION (WIDENING). EARTH EXCAVATION

(WIDENING) MATERIAL SHALL BE USED TO SHAPE THE GROUND LINE WHERE PCC WIDENING IS REQUIRED. THIS WORK SHALL

NOT BE PAID FOR SEPARATELY BUT INCLUDED WITH THE PAY ITEM PORTLAND CEMENT CONCRETE BASE COURSE 10".

THE EXISTING PAVEMENT MARKINGS AND RAISED REFLECTIVE PAVEMENT MARKERS THAT CONFLICT WITH STAGE I & II OF STANDARD 701321 (SPECIAL) SHALL BE COVERED BY PAVEMENT MARKING BLACKOUT TAPE, 5".

THE FOLLOWING MIXTURE REQUIREMENTS ARE APPLICABLE TO THIS PROJECT:

APPLICATION	AC/PG	DESIGN AIR	MIXTURE	FRICTION	TESTING
		VOIDS	COMPOSITION	AGGREGATE	PARAMETER
HMA SURFACE COURSE (1 1/2")	PG 64-22	4.0% @ N90	IL-9.5	MIXTURE C	QC/QA

SHEET NO		TITLE
	COVED CHEET	

BRIDGE PLANS

21-24

CROSS SECTIONS

1	COVER SHEET
2	GENERAL NOTES, INDEX OF SHEETS & LIST OF STANDARDS
3-4	SUMMARY OF QUANTITIES
5	SCHEDULE OF QUANTITIES
6	TYPICAL SECTIONS
7	PLAN/PROFILE SHEET
8-9	STAGE CONSTRUCTION SHEETS
10	EROSION CONTROL SHEET
11	PAVING DETAILS

THE FOLLOWING STANDARDS ARE A PART OF THESE PLANS AND ARE INCLUDED FOLLOWING THE LAST NUMBERED SHEET OF THE PLANS.

STANDARD NO	DESCRIPTION
000001-06	STANDARD SYMBOLS, ABBREVIATIONS AND PATTERNS
001001-02	AREAS OF REINFORCEMENT BARS
001006	DECIMAL OF AN INCH AND OF A FOOT
280001-07	TEMPORARY EROSION CONTROL SYSTEMS
483001-05	PCC SHOULDER
515001-03	NAME PLATE FOR BRIDGES
701001-02	OFF-ROAD OPERATIONS, 2L, 2W, MORE THAN 15' AWAY
701006-05	OFF-ROAD OPERATIONS, 2L, 2W, 15' TO 24" FROM PAVEMENT EDGE
701011-04	OFF-ROAD MOVING OPERATIONS, 2L, 2W, DAY ONLY
701201-04	LANE CLOSURE, 2L, 2W, DAY ONLY, FOR SPEEDS >= 45 MPH
701301-04	LANE CLOSURE, 2L, 2W, SHORT TIME OPERATIONS
701311-03	LANE CLOSURE 2L, 2W MOVING OPERATIONS - DAY ONLY
701321-17	LANE CLOSURE, 2L, 2W, BRIDGE REPAIR WITH BARRIER
701326-04	LANE CLOSURE, 2L, 2W, PAVEMENT WIDENING, FOR SPEEDS >= 45 MPH
701901-07	TRAFFIC CONTROL DEVICES
704001-08	TEMPORARY CONCRETE BARRIER
780001-05	TYPICAL PAVEMENT MARKINGS

USER NAME = steffenmk	DESIGNED -	REVISED -	
	DRAWN -	REVISED -	
PLOT SCALE = 100.0000 ' / in.	CHECKED -	REVISED -	
PLOT DATE = 8/16/2018	DATE -	REVISED -	

05115041					F.A.P. RTE	SEC.	TION		COUNTY	TOTAL SHEETS	
GENERAL	NOTES	& IND	EX OF SHEET	S	332	18	3B		LAWRENCE	24	2
									CONTRACT	NO. 7	4619
SHEET	OF	SHEETS	STA.	TO STA.			ILLINOIS	FED. AI	ID PROJECT		

PLOT DATE = 8/16/2018

DATE

REVISED

	CUMMARY OF QUANTITIES		2070 STATE	CON	STRUCTION TYPE CODE	] [	CLIMANAA	סר סר	OLIANITITIC		2070 317(12	CONS	TRUCTION TYPE CODE
	SUMMARY OF QUANTITIES		TOTAL	0004			SUMMA	RY UF	QUANTITIES		TOTAL	0004	
CODE NO	ITEM	UNIT	QUANTITIES			CODE NO		ITEM	1	UNIT	OUANTITIES		
20100110	TREE REMOVAL (6 TO 15 UNITS DIAMETER)	UNIT	159	159		42001300	PROTECTIVE	COAT		SQ YD	149	149	
20100210	TREE REMOVAL (OVER 15 UNITS DIAMETER)	UNIT	54	54		44000100	PAVEMENT F	REMOVAL		SQ YD	187	187	
20200100	EARTH EXCAVATION	CU YD	891	891		44000155	HOT-MIX AS	SPHALT SURFAC	CE REMOVAL, 1 1/2"	SQ YD	149	149	
20200500	EARTH EXCAVATION (WIDENING)	CU YD	183	183		50100100	REMOVAL OF	EXISTING S	RUCTURES	EACH	1	1	
20201200	REMOVAL AND DISPOSAL OF UNSUITABLE MATERIAL	CU YD	301	301		50800105	RE INFORCEM	MENT BARS		POUND	43090	43090	
28000250	TEMPORARY EROSION CONTROL SEEDING	POUND	31	31		50800515	BAR SPLICE	:RS		EACH	122	122	
28000305	TEMPORARY DITCH CHECKS	FOOT	40	40		51500100	NAME PLATE	:S		EACH	1	1	
28100109	STONE RIPRAP, CLASS A5	SO YD	124	124		52200020	TEMPORARY	SOIL RETENT	ON SYSTEM	SQ FT	326	326	
28200200	FILTER FABRIC	SO YD	124	124		54003000	CONCRETE F	30X CULVERTS		CU YD	210.1	210.1	
31101900	SUBBASE GRANULAR MATERIAL, TYPE C	TON	67	67		63200310	GUARDRAIL	REMOVAL		FOOT	623	623	
35300500	PORTLAND CEMENT CONCRETE BASE COURSE 10"	SO YD	657	657		67000400	ENGINEER'S	FIELD OFFI	CE, TYPE A	CAL MO	5	5	
0600290	BITUMINOUS MATERIALS (TACK COAT)	POUND	13	13		67100100	MOBILIZATI	ON		L SUM	1	1	
10603320	HOT-MIX ASPHALT SURFACE COURSE, MIX "C", N90	TON	22	22		70100450	TRAFFIC CO	ONTROL AND PE	ROTECTION, STANDARD	L SUM	1	1	
2000500	PORTLAND CEMENT CONCRETE PAVEMENT 10"	SO YD	149	149			701201						
NAME =	USER NAME = steffenmk   DESIGNED -		REVISED -									FAR	
	USEN NAME - SERTAMINK   USEN	4619-sht-soq.dgn			STATE OF DEPARTMENT OF T		ION		SUMMARY OF QUANTI	ITIES	[ 	F.A.P. SECTI 8TE. SECTI 332 18E	

	SUMMARY OF QUANTITIES			CON	STRUCTION TYPE CODE	$\exists 1$	SUMMARY OF QUANTITIES		Ţ	CONS	TRUCTION TYPE CODE
CODE NO	ITEM UP QUANTITIES	UNIT	TOTAL QUANTITIES	0004		CODE NO	ITEM	UNIT	TOTAL QUANTITIES	0004	
70100500	TRAFFIC CONTROL AND PROTECTION, STANDARD	L SUM	1	1		X0900064	MEMBRANE WATERPROOFING SYSTEM FOR BURIED STRUCTURES	SQ YD	257	257	
	701326	<u> </u>									
		ļ				* X2501000	SEEDING, CLASS 2 (SPECIAL)	ACRE	0.3	0.3	
70103815	TRAFFIC CONTROL SURVEILLANCE	CAL DAY	6	6							
						X4401198	HOT-MIX ASPHALT SURFACE REMOVAL, VARIABLE	SQ YD	117	117	
70106500	TEMPORARY BRIDGE TRAFFIC SIGNALS	EACH	1	1			DEPTH				
70106700	TEMPORARY RUMBLE STRIPS	EACH	6	6		X7010202	TRAFFIC CONTROL AND PROTECTION, STANDARD	EACH	1	1	
		1					701321 (SPECIAL)				
70107005	PAVEMENT MARKING BLACKOUT TAPE, 5"	FOOT	800	800							
						X7015005	CHANGEABLE MESSAGE SIGN	CAL DAY	28	28	
70400100	TEMPORARY CONCRETE BARRIER	FOOT	362	362							
						<b>x</b> Z0054505	ROCK FILL - REPLACEMENT	TON	301	301	
70400200	RELOCATE TEMPORARY CONCRETE BARRIER	FOOT	337	337							
70600250	IMPACT ATTENUATORS, TEMPORARY (NON-	EACH	2	2							
	REDIRECTIVE), TEST LEVEL 3										
70600350	IMPACT ATTENUATORS, RELOCATE (NON-	EACH	2	2							
	REDIRECTIVE), TEST LEVEL 3										
78001110	PAINT PAVEMENT MARKING - LINE 4"	FOOT	351	351							
				•							
A2001016	TREE, ACER RUBRUM (RED MAPLE), 2" CALIPER,	EACH	9	9							
	BALLED AND BURLAPPED										
B2001116	TREE, CERCIS CANADENSIS (EASTERN REDBUD), 2"	EACH	9	9							
	CALIPER, TREE FORM, BALLED AND BURLAPPED	1									

\* SPECIALTY ITEM

FILE NAME =	USER NAME = steffenmk	DESIGNED -	REVISED -					F.A.P.	SECTION	COUNTY	TOTAL	SHEET
pw:\\ILØ84EBIDINTEG.:111:no1s.gov:PWIDOT\Do	cuments\IDOT Offices\District 7\Projects\746	9 <b>DRAWN</b> ta\CABsheets\D774619-sht-soq.dgn	REVISED -	STATE OF ILLINOIS		SUMMARY OF QUANTITIES		332	18B	LAWRENCE	24	4
	PLOT SCALE = 100.0000 '/ in.	CHECKED -	REVISED -	DEPARTMENT OF TRANSPORTATION				552		CONTRACT	NO.	74619
Default	PLOT DATE = 8/16/2018	DATE -	REVISED -		SCALE: N/A	SHEET 1 OF SHEETS STA.	TO STA.		ILL INOIS FEI	AID PROJECT		

Ρ.	VING SCHEDULE		BITUMINOUS MATERIALS (TACK COAT)	HOT-MIX ASPHALT SURFACE COURSE, MIX "C", N90	HOT-MIX ASPHALT SURFACE REMOVAL, 1 1/2"	HOT-MIX ASPHALT SURFACE REMOVAL, VARIABLE DEPTH	SUBBASE GRANULAR MATERIAL, TYPE C	PORTLAND CEMENT CONCRETE PAVEMENT 10"	PROTECTIVE COAT	PAVEMENT REMOVAL
STATION -	O STATION	LENGTH								
1 I AM	LINE	FOOT	POUND	TON	SQ YD	SQ YD	TON	SQ YD	SQ YD	SQ Y
	303+90	34	4.5	7.6	90.7	-	-	-	-	-
303+56	1	16	2. 1	3.6	-	42.7	-	-	-	-
303+56 303+90	304+06			1	_	_		140 0	149.0	187.
	304+06 304+62	56	-	-	_		67.0	149.0	173.0	101.
303+90			- 3 <b>.</b> 7	6.3	-	74. 7	- -	149.0	-	-
303+90 304+06	304+62	56								

REVISED -

REVISED -

REVISED

REVISED -

PORTLAND CEMENT CONCRETE BASE COURSE

SQ YD

281.5

376.0

657

SHOULDER SCHEDULE

SIDE

LT/RT

RT

DESIGNED -

CHECKED -

DATE

WIDTH

(FT)

6.33

LENGTH

FOOT

432

TOTALS:

STATION TO STATION

USER NAME = steffenmk

PLOT DATE = 8/16/2018

pw:\\IL084EBIDINTEG.:111:nois.gov:PWIDOT\Documents\IDOT Offices\District 7\Projects\746 <mark>9@RWWh</mark>te\CABsheets\D774619-sht-sch.dgn

306+52

302+27

302+20

FILE NAME =

EARTH EXCAVATION (WIDENING)

CU YD 78.2

104.4

183

STATE OF ILLINOIS

**DEPARTMENT OF TRANSPORTATION** 

	TREE R	EMOVAL	
STATION	OFFSET	TREE REMOVAL (6 TO 15 UNITS DIAMETER)	TREE REMOVAL (OVER 15 UNITS DIAMETER)
303+27	40' LT	10	-
303+27	40′ LT	10	-
303+31	40' LT	7	-
303+35	40′ LT	10	-
303+50	45′ LT	8	-
303+50	45′ LT	12	-
303+65	41' LT	-	16
303+75	40′ LT	13	-
304+00	65′ LT	-	22
304+08	39′ LT	8	-
304+20	49′ LT	-	16
304+35	57′ LT	13	-
304+56	52′ LT	11	-
304+65	50′ LT	11	-
304+79	47′ LT	13	-
304+84	54′ LT	11	-
304+86	47′ LT	11	-
304+93	46′ LT	1 1	-
	TOTALS:	159	54

SCHEDULE OF QUANTITIES

SHEET 1 OF SHEETS STA.

SCALE: N/A

COUNTY TOTAL SHEET NO.

LAWRENCE 24 5

CONTRACT NO. 74619


SECTION


18B

332

TO STA.

			EARTH	EARTH EXC	EMBANKMENT	EARTHWORK BALANCE
	LOCATION	N	EXCAVATION	ADJ. FOR		WASTE (+) OR
			(cut)	SHRINKAGE	(fill)	SHORTAGE (-)
			CU YD	CU YD	CU YD	CU YD
303+00	ТО	303+50	33. 7	25.3	8.3	17.0
303+50	ТО	303+90	85.9	64.4	20.3	44.1
303+90	ТО	304+06	56.0	42.0	11.0	30.9
304+06	ТО	304+21	214.0	160.5	15.8	144.7
304+21	TO	304+25	91.7	68.8	5.7	63.1
304+25	ТО	304+43	0.0	0.0	25.6	-25.6
304+43	ТО	304+47	98.4	73.8	5.7	68.1
304+47	ТО	304+62	217.5	163.1	14.5	148.7
304+62	ТО	304+90	70.9	53.2	12.7	40.5
304+90	TO	305+25	22. 9	17.2	7. 1	10.1
	TOTALS:		891	668	127	542






### TYPICAL CROSS SECTION


STA 302+27 TO STA 303+90 STA 304+90 TO STA 306+29

## TYPICAL CROSS SECTION

STA 303+90 TO STA 304+06 STA 304+62 TO STA 304+90

\* SEE GENERAL NOTES FOR SHOULDER GRADING





# TYPICAL CROSS SECTION


STA 304+06 TO STA 304+62


# TYPICAL CROSS SECTION


STA 303+56 TO STA 303+90 STA 304+90 TO STA 305+12


USER NAME = steffenmk	DESIGNED -	REVISED -								F.A.P.	SECTION	COUNTY	TOTAL SHEET SHEETS NO.	
	DRAWN -	REVISED -	STATE OF ILLINOIS			TYPIC	AL SECTI	ONS		332	18B	LAWRENCE	24 6	
PLOT SCALE = 100.0000 ' / in.	CHECKED -	REVISED -	DEPARTMENT OF TRANSPORTATION									CONTRAC	T NO. 74619	
PLOT DATE = 8/16/2018	DATE -	REVISED -		SCALE:	SHEET	OF	SHEETS	STA.	TO STA.		ILLINOIS FE	D. AID PROJECT		

FILE NAME: pw://IL084EBIDINTEG.IIIInols.g









# EROSION CONTROL GENERAL NOTES

#### EROSION CONTROL MEASURES AT THE START OF CONSTRUCTION

1. THE AREAS OF EXCAVATION AND EMBANKMENT PLACEMENT SHALL BE MANAGED FOR THE PURPOSES OF CONTROLLING EROSION WITHIN THE IMPROVEMENT AREA. REDUCING WATER FLOW BY TEMPORARY DIVERSION, MINIMIZING SILTATION AT THE RIGHT-OF-WAY LINE, AND ESTABLISHING VEGETATIVE COVER WHICH WILL BECOME PERMANENT VEGETATION AND ACT AS AN EROSION CONTROL BARRIER. WORK AT THE START OF CONSTRUCTION SHALL CONSIST OF THE FOLLOWING:

(a) AREAS OF EXISTING VEGETATION (WOODS AND GRASSLANDS) OUTSIDE THE PROPOSED CONSTRUCTION LIMITS SHALL BE IDENTIFIED FOR PRESERVING AND SHALL BE PROTECTED FROM BRUSH CUTTING, TREE REMOVAL AND OTHER ACTIVITIES THAT WOULD BE DETRIMENTAL TO THEIR MAINTENANCE AND DEVELOPMENT.

- (b) DEAD, DISEASED, OR UNSUITABLE VEGETATION WITHIN THE SITE SHALL BE REMOVED AS DIRECTED BY THE ENGINEER.
- (c) BARE AND SPARSELY VEGETATED GROUND IN HIGHLY ERODIBLE AREAS AS DETERMINED BY THE ENGINEER SHALL BE TEMPORARILY SEEDED AT THE START OF CONTRUCTION WHEN NO CONSTRUCTION ACTIVITIES ARE EXPECTED WITHIN SEVEN CALENDAR DAYS.

#### EROSION CONTROL MEASURES DURING CONSTRUCTION

1. DURING CONSTRUCTION, AREAS OUTSIDE THE CONSTRUCTION LIMITS AS OUTLINED PREVIOUSLY HEREIN SHALL BE PROTECTED FROM DAMAGING EFFECTS OF CONSTRUCTION, THE CONTRACTOR SHALL NOT USE THIS AREA FOR PARKING OF VEHICLES OR CONSTRUCTION EQUIPMENT, STORAGE OF MATERIALS, OR OTHER CONSTRUCTION RELATED ACTIVITIES.


(g) WITHIN THE CONSTRUCTION ZONE, CRITICAL AREAS WHICH HAVE A HIGH FLOW OF WATER, AS DETERMINED BY THE ENGINEER, SHALL REMAIN UNDISTURBED UNTIL CONTINUOUS OPERATIONS CAN ENSURE TIMELY COMPLETION OF WORK IN THESE AREAS TO MINIMIZE SOIL EROSION.


(b) EARTH STOCKPILES SHALL BE TERMPORARILY SEEDED IF THEY ARE TO REMAIN UNUSED FOR MORE THAN FOURTEEN CALENDAR DAYS.

EROSION CONTROL MEASURES AFTER FINAL GRADING:


- 1. EXCAVATION AND EMBANKMENT AREAS SHALL BE PERMANENTLY SEEDED WHEN FINAL GRADED.
- (a) TEMPORARILY EROSION CONTROL SYSTEMS SHALL REMAIN IN PLACE WITH PROPER MAINTENANCE UNTIL PERMANENT EROSION CONTROL IS IN PLACE AND WORKING PROPERLY WITH ALL PROPOSED TURF AREAS SEEDED AND A PROPER STAND ESTABLISHED.


USER NAME = steffenmk	DESIGNED -	REVISED -								F.A.P.	SECTION	COUNTY	TOTAL	SHEET
	DRAWN -	REVISED -	STATE OF ILLINOIS			ROSION		OL PLAN		332	18B	LAWRENCE	24	10
PLOT SCALE = 40.0000 ' / in.	CHECKED -	REVISED -	DEPARTMENT OF TRANSPORTATION									CONTRAC	T NO. 7	4619
PLOT DATE = 8/16/2018	DATE -	REVISED -		SCALE:	SHEET	OF	SHEETS	STA.	TO STA.		ILLINO	S FED. AID PROJECT		






F	ILE NAME =	USER NAME = steffenmk	DESIGNED -	REVISED -						F.A.P.	SECTION	COUNTY TOTAL SHEET SHEET
Р	w:\\IL084EBIDINTEG.:ll:no:s.gov:PWIDOT\Do	cuments\IDOT Offices\District 7\Projects\746	9DRADWNta\CABsheets\D774619-sht-details.o	arREVISED −	STATE OF ILLINOIS		HMA RESU	URFACING DETAILS		332	18B	LAWRENCE 24 11
		PLOT SCALE = 100.0000 '/ in.	CHECKED -	REVISED -	DEPARTMENT OF TRANSPORTATION					'		CONTRACT NO. 74619
D	efault	PLOT DATE = 8/16/2018	DATE -	REVISED -		SCALE: N/A	SHEET 1 OF	SHEETS STA.	TO STA.		ILLINOIS FED.	AID PROJECT








- See Detail I, II or III When "A" is 3'-1" or less, the temporary concrete barrier shall be restrained to the new slab according to Detail I, II or III. No restraint is required when "A" is greater than 3'-1".

NEW SLAB OR NEW DECK BEAM




shall be 3" plus the wearing surface depth.


EXISTING DECK BEAM

# US Std. 11/16" I.D. x 21/2" O.D. x approx. 8 guage thick washer RESTRAINING PIN

#### SECTIONS THRU SLAB OR DECK BEAM


EXISTING SLAB





# STEEL RETAINER P 1" x 8" x "W"

(Detail I and II)



STEEL RETAINER P 1" x "H" x 10" (Detail III)

#### BAR SPLICER FOR #4 BAR - DETAIL III

Cost of retainer assembly is included with Temporary Concrete Barrier. A retainer assembly shall be located at the approximate Q of each temporary concrete barrier.

The retainer plate shall not be removed until the concrete on the adjacent stage is ready to be poured. For Detail III applications the retainer plate shall not be removed until just prior to placing the adjacent beam.

When the 'A' dimension is less than  $1\frac{1}{2}$ ", the wood block shall be omitted and the barrier shall be placed in direct contact with the steel retainer plate. For deck beam applications the minimum required 'A' distance is 6" to accommodate the shear key clamping device.

- Detail I Installation for a new bridge deck or bridge slab.
- Detail II Installation for a new deck beam with an initial concrete wearing surface. Additional bar splicers shall be provided at 6'-0" centers and paired with the bar splicers of the concrete wearing surface reinforcement to accommodate the installation of the retainer assemblies. The cost of the additional bar splicers is included with the concrete wearing surface.
- Detail III Installation for a new deck beam with no initial wearing surface or with an initial hot-mix asphalt (HMA) wearing surface present. The deck beam directly beneath the temporary concrete barrier shall be fabricated with bar splicer inserts in the side of the beam, as detailed, to accommodate the installation of the retainer assemblies. A pair of bar splicers, 6" apart, shall be placed at 6'-0" centers along the length of the beam. The cost of the bar splicers is included with the deck beam.

R-27

8-11-2017

DESIGNED - JOSEPH G. YOUNG **EXAMINED** CHECKED - HAREEM I. DAR MICHAEL B. MOSSMAN PASSED CHECKED - J.G.Y. / H.I.D. / G.R.A.


OCTOBER 3, 2018


**STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION**  TEMPORARY CONCRETE BARRIER FOR STAGE CONSTRUCTION STRUCTURE NO. 051 - 2009 SHEET 3 OF 9 SHEETS

SECTION COUNTY 332 LAWRENCE 24 14 CONTRACT NO. 74619

10/4/2018 10:47:58 AM

REVISED -REVISED -





DESIGNED - JOSEPH G. YOUNG

CHECKED - HAREEM I. DAR

DRAWN - MICHAEL B. MOSSMAN

PASSED

CHECKED - J.G.Y./H.J.D./ G.R.A.

ENGINEER OF BRIDGE DESIGN

REVISED - \_\_\_\_\_

REVISED - \_\_\_\_\_


REVISED - \_\_\_\_\_

STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION


CULVERT DETAILS - BOTTOM SLAB
STRUCTURE NO. 051 - 2009

SHEET 5 OF 9 SHEETS

10/4/2018 10:48:42 AM



10/4/2018 10:49:01 AM



10/4/2018 10:49:23 AM

CHECKED - HAREEM I. DAR

CHECKED - J.G.Y./H.I.D./G.R.A.

DRAWN - MICHAEL B. MOSSMAN

PASSED

REVISED -

REVISED -

STATE OF ILLINOIS **DEPARTMENT OF TRANSPORTATION** 

**CULVERT DETAILS** STRUCTURE NO. 051 - 2009 SHEET 7 OF 9 SHEETS

COUNTY TOTAL SHEETS NO.


LAWRENCE 24 18 SECTION 332 18B CONTRACT NO. 74619 ILLINOIS FED. AID PROJECT

#### STANDARD BAR SPLICER ASSEMBLY

Threaded splicer bar length = min. lap length +  $1\frac{1}{2}$ " + thread length


\* Epoxy not required on Bar Splicer Assembly components used in conjunction with black bars.

Location	Bar size	No. assemblies required	Minimum lap length
Top slab	#5	52	2'-9"
Walls	#5	18	2'-9"
Bottom slab	#5	52	2'-9"




#### INSTALLATION AND SETTING METHODS

"A": Set bar splicer assembly by means of a template bolt.
"B": Set bar splicer assembly by nailing to wood forms or cementing to steel forms.
(E): Indicates epoxy coating.



#### STANDARD MECHANICAL SPLICER

Location	Bar size	No. assemblies required



#### NOTES

Splicer bars shall be deformed with threaded ends and have a minimum 60 ksi yield strength.

All reinforcement shall be lapped and tied to the splicer bars.

Bar splicer assemblies shall be epoxy coated according to the requirements for reinforcement bars. See Section 508 of the Standard Specifications.

See approved list of bar splicer assemblies and mechanical splicers for alternatives.

BSD-1

2-17-2017

 DESIGNED JOSEPH G. YOUNG
 EXAMINED

 CHECKED HAREEM I. DAR

 DRAWN MICHAEL B. MOSSMAN
 PASSED

 CHECKED J.G.Y. / H.I.D. / G.R.A.

PAGE OF BRIDGE DESIGNATION OF BRIDGES AND STRUCTURES

DATE - OCTOBER 3, 2018

DOG DESIGN

REVISED 
REVISED 
REVISED -

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

BAR SPLICER ASSEMBLY AND MECHANICAL SPLICER DETAILS
STRUCTURE NO. 051 - 2009

SHEET 8 OF 9 SHEETS

MODEL 0512009-74619-008

10/4/2018 10:49:46 AM

딢	ı
ō.	ı
9	ı
2	ı
ó	ı
4	ı
`	ı
2003	ı
$\preceq$	ı
$\stackrel{\sim}{\sim}$	ı
-	ı
5/05	ı
=	ı
č	ı
au	ı
1	ı
2009/CADD PI	ı
	ı
₹	ı
$\leq$	ı
5	ı
⊇	ı
2	ı
	ı
ts/05_	ı
2	ĺ
2	ı
ŭ	ı
ž.	ı
2	ı
_	ı
š	ı
Ψ.	ı
3	ı
Ü	ı
2	ı
Ϋ́	ı
	ı
ges and Struct	ı
ā	ı
	ı
ŭ	ı
0	ı
≌	ı
'n	ı
_	ı
Ö	ı
nrean o	ı
ıreau	ı
e.	ı
⋾	ı
9	ĺ
Ses	ı
ë	ı
Ě	ĺ
5	ı
_	ı
$\overline{}$	ı
cuments/IDOI Offic	ı
⋾	ı
2	ĺ
=	ı
9	ĺ
⊑	ĺ
3	ĺ
ō	ĺ
9	ı
_	ĺ
Š	ĺ
=	ı
M	ı
ī	ı
>	ı
0	ĺ
015.gc	ĺ
S	ĺ
0	ĺ

Illinois Depail of Transporta				J	SOIL BORING LO	JG	Date	8/1	LO
ROUTE FAP 332 (IL 1) DESCRIPTION				Ш	nnamed Creek Lo	OGGED E			
<del></del>									
SECTION 18B LO	CATIO	ON _	R 12 \	N - Se	c 1 - E 1/2, R 11 W - Sec 6 - W 1/2, S	SEC., TW	P. 4 N,	RNG.,	. 3
COUNTYLawrence DRILLING	G ME	THOD	Holl	ow ste	m auger & spllt spoon HAMMER T	YPE	Auto	140#	ŧ
STRUCT. NO. 051-2009 (exist 8000)	D	В	U	М	Surface Water Elev432.83_	ft D		U	Ī
Station 304+33.8	E	L	C S	0	Stream Bed Elev. 431,91			C	
BORING NO1 (South)	T	w		s	Groundwater Elev.;	+		"	
Station304+19	н	S	Qu	Т	∇ First Encounter418.6_		S	Qu	l
Offset 17.0ft Rt Ground Surface Elev 438,64 ft	(ft)	/6"	(tsf)	(%)	□ Upon Completion 425.1     ■ After 48 Hrs 432.1		) /6"	(tsf)	
16" aggregate shoulder	(,	, -	()	()	Gray, fine grained, SAND. 12% 47		1	0,1	ł
	_				passing #200 sieve. (continued)		2	В	
437.34 Soft, damp, gray, SILTY LOAM.					Very soft, very damp, gray, SANDY LOAM,				
, ,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		1			Soft to medium, damp, gray,	L6.64	5		
	_	2	0.3	20	SANDY CLAY w/ Sandstone	-	6	0.5	t
		2	В		fragments. 41 Brown, SANDSTONE. 41	L5.24 L5.14	13	S	ļ
					Extent of exploration.				l
	-5	0			-	-2	5		l
		0		12					
		1			Benchmark: BM 445 chiseled square on the SE wingwall of	_	4		
<b>▼</b> 431.64	_				existing SN 051-8000 = 439.46'	-			
Medium, damp, gray marbled		0			elevation.	_			
reddish brown, SILTY CLAY.		0	0.5 B	22					
	_	_				-			
429,14						_			
Soft, damp, red marbled gray, SANDY LOAM.	<u>-10</u>	0	0.3	22		3	0		
	-	1	В В	~~		-			
426,34		0				_	4		
Stiff, damp, gray marbled reddish brown, SILTY CLAY.	_	1	1.2	28		-	┪		
T T T T T T T T T T T T T T T T T T T		1	В				1		l
						_	-		
	-15	1				-3	5		
422 94		2	1.2	32			Ì		
Very soft, very damp, gray, SILTY 422.84		3	В				-		l
LOAM.  Grav. SANDY LOAM. 421.64	_					-	-		l
Soft, damp, gray, SILTY LOAM.		0		L			1		l
		1	0.3 B	18		_	4		l
	_	<u> </u>	⊢°-			-	-		l
419.14									l
▽	-20	1				-4	0		L

Illinois Depart	atio	on		S	OIL BORING LOG		
Division of Highways Illinois Department of Transp						Date	8/10/
ROUTE FAP 332 (IL 1) DESCRIPTION	<b>_</b>			Ur	named Creek LOGGED	BY <u>E.S</u>	Sandsch
SECTION 18B LO	CATIO	ON _	R 12 \	N - Se	c 1 - E 1/2, R 11 W - Sec 6 - W 1/2, SEC., TW	VP. 4 N, I	RNG., 3
COUNTYLawrence DRILLING	G ME	THOD	Holl	ow ste	em auger & split spoon HAMMER TYPE	Auto	140#
STRUCT. NO.   051-2009 (exist 8000)	D E P T H	B L O W S /6"	U C S Qu (tsf)	M 0 I S T (%)	Surface Water Elev. 432.83 ft Stream Bed Elev. 431.91 ft  Groundwater Elev.:		
16" aggregate shoulder.	_					+	
437.48 Soft to medium, damp, brown/gray, SILTY LOAM.		3 4 3	0.4 S	19			
	-5	3 1 2	0.6 B	20			
431.78 Medium to stiff, damp, gray, SILTY CLAY.		0 1 2	1.0 B	21			
429,28 Stiff, damp, gray marbled brown,		2					
CLAY.	<u>-10</u>	3	1.3 B	27			
Ā	_	1 2 3	1.7 B	26			
424.28 Very soft, very damp, gray, SILTY LOAM.	-15	1	0.2	30			
Extent of exploration.	_	2	В				
Benchmark: BM 445 chiseled square on the SE wingwall of existing SN 051-8000 = 439,46'	_						

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by (B-Bulge, S-Shear, P-Penetrometer, E-Estimated)
Abbreviations W.O.H - Sampler Advanced By Weight of Hammer, W.O.P - Advanced by Weight of Pipe, B.S. - Before Seating
The SPT (N value) is the sum of the last two blow values in each sampling zone (AASHTO T206) BBS, from 137 (Rev. 8-99)

00213 Dw.\\\	SIGNED	-	JOSEPH G. YOUNG	EXAMINED	January F. J. M.
S M CH	ECKED	-	HAREEM I. DAR	-	ENGINEER OF BRIDGE DESIGN
DR NO DR	AWN	-	MICHAEL B. MOSSMAN	PASSED	& Carl Progress
	ECKED	-	J.G.Y. / H.I.D. / G.R.A.		ENGINEER OF BRIDGES AND STRUCTURES
10/4	/2018	10:5	0:07 AM		

DATE - OCTOBER 3, 2018 REVISED -REVISED -

STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION

F.A.P. RTE. COUNTY TOTAL SHEET NO.

LAWRENCE 24 20 SECTION SOIL BORING LOGS 18B STRUCTURE NO. 051 - 2009 CONTRACT NO. 74619 SHEET 9 OF 9 SHEETS ILLINOIS FED. AID PROJECT

