1. COVER PAGE

INDEX OF SHEETS, GENERAL NOTES, STATE STANDARDS

3. SUMMARY OF QUANTITIES

4.-5. STAGING PLANS

6.-8. BRIDGE PLANS (SN 049-0131)

9. US 41 DETOUR PLAN

10. TYPICAL APPLICATION RAISED REFLECTIVE PAVEMENT MARKERS (SNOW-PLOW RESISTANT)

11. TRAFFIC CONTROL AND PROTECTION FOR SIDE ROADS, INTERSECTIONS AND DRIVEWAYS

LIST OF STATE STANDARDS

701301-02 LANE CLOSURE, 2L, 2W, SHORT TIME OPERATIONS

701606-04 URBAN LANE CLOSURE, MULTILANE, 2W WITH MOUNTABLE MEDIAN

702001-06 TRAFFIC CONTROL DEVICES
704001-03 TEMPORARY CONCRETE BARRIER

631031-06 TRAFFIC BARRIER TERMINAL, TYPE 6

GENERAL NOTES

BEFORE STARTING ANY EXCAVATION, THE CONTRACTOR SHALL CALL "J.U.L.I.E" AT (800) 892-0123 FOR FIELD LOCATIONS OF BURIED ELECTRIC, TELEPHONE AND GAS UTILITIES. 48 HOUR NOTIFICATION IS REQUIRED.

THE CONTRACTOR WILL NOT BE ALLOWED TO SET UP A YARD OR FIELD OFFICE ON STATE PROPERTY WITHOUT WRITTEN PERMISSION FROM THE DEPARTMENT.

ALL DAMAGE TO EXISTING PAVEMENT MARKINGS OR RAISED REFLECTIVE PAVEMENT MARKERS OUTSIDE THE REMOVAL LINE SHOWN ON THE PLANS SHALL BE REPLACED AT THE CONTRACTOR'S EXPENSE.

BEFORE BEGINNING ANY WORK, THE CONTRACTOR SHALL RETAIN AND RECORD FOR FUTURE REFERENCE, ALL EXISTING PAVEMENT MARKING LINES AND RAISED REFLECTIVE PAVEMENT MARKERS IN ORDER THAT THESE LOCATIONS CAN BE RE-ESTABLISHED FOR STRIPING. EXACT LOCATIONS OF ALL PAVEMENT MARKINGS SHALL BE AS DIRECTED BY THE ENGINEER.

IT SHALL BE THE CONTRACTORS RESPONIBILITY TO VERIFY ALL DIMENSIONS AND CONDITIONS EXISTING IN THE FIELD PRIOR TO CONSTRUCTION AND ORDERING OF MATERIALS.

THE CONTRATOR SHALL CONTACT THE DISTRICT ONE TRAFFIC CONTROL SUPERVISOR AT (847) 705-4470 A MINIMUM OF 72 HOURS IN ADVANCE OF BEGINNING WORK.

THE CONTRACTOR SHALL CONTACT PATRICE HARRIS AT (708) 597-9800 TWO (2) WEEKS PRIOR TO PLACEMENT OF PERMANENT PAVEMENT MARKINGS.

THESE PLANS HAVE BEEN PREPARED FROM NOTES RECIEVED FROM BRIDGE INSPECTORS

THE CONTRACTOR SHALL BE REQUIRED TO PROVIDE ACCESS TO ABUTTING PROPERTY AT ALL TIMES DURING THE CONSTRUCTION OF THIS PROJECT.

DO NOT SCALE PLANS FOR CONSTRUCTION DIMENSIONS.

DOUBLE LANE MARKERS ARE TO BE USED AS SHOWN ON THE DISTRICT ONE DETAIL FOR TYPICAL APPLICATION OF RAISED REFLECTIVE PAVEMENT MARKERS (SNOW-PLOW RESISTANT) SHOWN IN THE PLANS.

CONCRETE SUPERSTRUCTURES SHALL HAVE A SEVEN DAY MINIMUM CURE.

THE CONTRATOR SHALL COORDINATE CONSTRUCTION ACTIVITIES WITH UTILITY COMPANIES.

THE CONTRATOR SHALL BE RESPONSIBLE

NOTIFICATION OF ALL EMERGENCY SERVICES, SCHOOL DISTRICTS, I.D.O.T.'S

COMMUNICATIONS CENTER, SPRINGFIELD TRUCK PERMIT SECTION AND OTHER AGENCIES

AFFECTED BY THE CLOSURE. THE CONTRACTOR SHALL ALSO BE RESPONSIBLE FOR POSTING

SIGNS THAT WILL INDICATE THE DATES THE CLOSURE WILL BE IN PLACE.

THE CONTRACTOR SHALL CONTACT DISTRICT ONE TRAFFIC AT (847) 705-4424 ONE WEEK PRIOR TO IMPLEMENTING THE DETOUR SO TRAFFIC SIGNAL TIMINGS CAN BE ADJUSTED.

REVISIONS
NAME DATE

ILLINOIS DEPARTMENT OF TRANSPORTATION

INDEX OF SHEETS
GENERAL NOTES
AND STATE STANDARDS
PARK AVE.

SCALE: VERT.
HORIZ.
DATE

CHECKED BY

CONTRACT NO. 60D24

TO STA.

FED. ROAD DIST. NO. ILLINOIS FED. AID PROJECT

COUNTY TOTAL SHEET NO.

COOK 11 2

F.A.U. RTE. 3597

SECTION

07/0T-

ILE NAME = c1/7/2007/design_ LOT SCALE = 59.0161 '/ IN, SCALE = 59.0161 '/ IN,