


2" ACCESS HOLES IN REAR OF CABINET


- NOTES: 1. USE 16 GAUGE STEEL FOR CABINET.
 - THE TOP SHELF SHALL SLIDE IN OR OUT WITH THE TOP DOOR OPEN.
 - 3. ALL HINGES AND HASPS WILL BE WELDED TO THE CABINET.
 - 4. ALL EDGES SHALL BE GROUND SMOOTH.
 - 5. TWO (2" DIA.) ACCESS HOLES WILL BE REQUIRED FOR EACH SHELF.
 - 6. CABINET SHALL BE PAINTED WITH TWO COATS OF FLAT PAINT.
 - 7. 2 EACH MATCHING KEY PADLOCKS, WITH 3 KEYS PROVIDED, MASTER MODEL 3 T OR EQUIVALENT.
 - 4 EACH PLAIN STEEL, NON-REMOVABLE PIN, NO HOLE 4"X4" SQUARE CORNER HINGES TO BE WELDED ON.
 - 2 EACH EXTRA HEAVY, PLAIN STEEL, FIXED STAPLE, NO HOLE, 7 1/4 " HASPS TO BE WELDED ON.

-FLAT STOCK DIMENSIONS VARY DEPENDING ON TYPE OF ROLLER ASSEMBLY.

LOCKABLE COMPUTER CABINET



PAVEMENT MARKING



BARRIER WALL MARKER

	REVISIONS NAME DATE	ILLINOIS DEPARTMENT OF TRANSPORTATION F.A.P. ROUTE 693 (IL-9) DETAILS	
rjngroup Excellence through Ownership			
200 West Front Street Wheaton, II 60187		SCALE: NOT TO SCALE DATE: AUGUST 7, 2007	DRAWN BY: JMC CHECKED BY: DWB

17 DATE: 8/8/2007 17 TIME: 9:56:17 AM 17TED 81: 17T-00-8/2006_Distribut_02.dg