

				CONTRAC	CT NO.	68677
		F.A.P. RTE.	SECTION	COUNTY	SHEETS	SHEET NO.
		310	(41-A)BI	R McDONOUGH	66	64
		STA.	STA. TO STA.			
/EY	MARKERS	FED, RO	FED. ROAD DIST. NO. ILLINDIS FED. AID PROJECT			

Pure cement and water or melted sulfur user to seal tablet in rock ledge, concrete pavement or structure, set in hole 38(1.5) in diameter.

1. All type II markers shall be cast in place, and precast markers will not be allowed.

- 2. Two permanent magnets, each having a diameter of 19 $(\frac{3}{4})$ and a thickness of 6 $(\frac{1}{4})$, or equivalent, shall beattached to the underside of the tablet with an approved epoxy bonding agent.
- 3. The location of the markers shall be in accordance with the plans in general, the markers will be placed at the P.T.'s and P.C.'s of horizontal curves and spaces along the tangents in a way that a minimum of two markers are alway inter-visible, and not to exceed 300m(1000').
- 4. The markers shall be placed under the direction of the Engineer and shall be installed in a workmanlike manner in order that there will be no further settlement or horizontal shifting. The monuments shall be placed in a way that the survey point will fall within the portion of the plaque provided for that purpose.
- 5. The project designation, the centerline station, the survey point, and the elevation shall be permanently marked by the use of metal dies after marker has been installed.

		All dimensions are in millimeters (inches) unless otherwise noted,			
		ILLINOIS DEPARTMENT OF TRANSPORTATION			
		DISTRICT CADD STANDARD			
REVISIONS	BY				
. 0-3.01, NEW REVISION BOX	T.P.	PERMANENT SURVEY TIE			
ESIGNER NOTE, REVISED TITLE BOX		&			
ADD DESIGNER NOTE	J.A.				
OVED GEN. NOTE UNDER TIES	M.A.	PERMANENT SURVEY MARKERS TY.I - TY.II			
		CADD STD. NO. 667101-D4 DRAWN BY CADD SCALE: NOT DRAWN TO SCALE CHECKED BY			
	L	667101-D4			