

...\deck\_beams\_fy08\0590011.dgn 8/30/2007 2: 40: 22 PM

ROUTE NO.	SECTION	COUNTY		YOTAL SHEETS	BHEET NO.	SHEET NO. 1		
		Maca	upin	6	4	3 вн	EETS	
FEG. AGAD DIST, NO. 7		10.11035	FED, AID PROJECT-					
FEGL ASIAD DIST, NO. 7 ILLINGIS FEDLA Contract Number: 728								

## GENERAL NOTES

All structural steel shall conform to AASHTO Classification M-270 Gr. 36, unless otherwise noted.

Plan dimensions and details relative to existing plans are subject to routine variations. The Contractor shall field verify existing dimensions and details affecting new construction and make necessary approved adjustments prior to construction or ordering of materials. Such variations shall not be cause for additional compensation for a change in scope of the work, however, the Contractor will be paid for the quantity actually furnished based upon the unit price bid for the work.

The contractor is advised that the existing PPC Deck Beams are in a deteriorated condition with reduced load carrying capacity. It is the contractors responsibility to account for the condition of the beams when developing construction procedures.

See Section 584 of the Standard Specifications for Epoxy Grouting of Threaded Rods: Minimum embedment 9".

If the contractor's procedure for placement of beams involves placement of cranes or other heavy equipment on the bridge, a detailed procedure shall be submitted to the Engineer for approval. The procedure shall include calculations, prepared and sealed by an Illinois Licensed Structural Engineer, verifying that the equipment and procedure used will not overstress the existing beams. To distribute load to multiple beams and protect the existing surface, in all cases a double layer mat of heavy timbers shall be used at all times under crane tracks or wheels and any outriggers in the down position. If necessary, shims shall be used under the crane mat to ensure uniform contact with the underlying beams.

The cost of epoxy grouting threaded rods on the pier cap, abutments and beams shall be included with Furnishing and Erecting Structural Steel. The Contractor has the option of using used steel. See Special Provisions.. The cost of excavation required shall be included with Furnishing and Erecting Structural Steel.

