STATE OF ILLINOIS

DEPARTMENT OF TRANSPORTATION

DIVISION OF HIGHWAYS


FOR INDEX OF SHEETS, SEE SHEET NO. 2

PROPOSED HIGHWAY PLANS

SBI ROUTE 15B (OLD IL 15) SECTION (17C)B


WAYNE COUNTY
BRIDGE REPLACEMENT WITH BOX CULVERT

C-97-053-05



D-97-020-05





PRINTED BY THE AUTHORITY OF THE STATE OF ILLINOIS

PROJECT ENGINEER : MARK DAUGHER SQUAD LEADER : DESIGNER : BRIAN BIERMAN TELEPHONE : 217/342-3951 EX

CONTRACT NO. 74092

TOWNSHIP : ARRINGTON

N 2005 ADT = 159

GROSS LENGTH = 193 FEET = 0.04 MILES NET LENGTH = 193 FEET = 0.04 MILES

		CONTRACT	NU. 14	092
S.B.I. RTE.	SECTION	COUNTY	TOTAL	SHEET NO.
158	(17C)B	WAYNE	17	2
STA.		TO STA.		
FFD. ROAL	DOIST NO. THE	INDIS FED ATD	PROJECT	

GENERAL NOTES

PERIMETER EROSION BARRIER IS FOR PLACEMENT AT THE TOE OF THE PROPOSED FILL SLOPE ALONG THE TOTAL LENGTH OF THE PROJECT. EROSION CONTROL BLANKET IS FOR PLACEMENT ON ALL NEW SLOPE CONSTRUCTION.

THE TOTAL QUANTITY OF PAINT PAVEMENT MARKING-LINE 4 INCH CONSISTS OF 104 FEET OF WHITE AND 20 FEET OF YELLOW.

THE PROCESS OF REMOVAL OF UNSUITABLE MATERIAL AND REPLACING WITH ROCK FILL SHALL BE A CONTINUOUS OPERATION AND CLOSELY MONITORED BY THE CONTRACTOR. ANY UNSUITABLE MATERIAL REMOVED DURING THE COURSE OF A DAY SHALL BE REPLACED WITH ROCK FILL THAT SAME DAY. THE SLOPE STABILITY OF THE NEW CULVERT CUT DEPENDS ON THIS MATERIAL BEING IN PLACE.

AGGREGATE FOR AGGREGATE SHOULDERS, TYPE B SHALL BE CRUSHED STONE, CRUSHED CONCRETE OR RAP.

THE REMOVAL OF ALL EARTHWORK, SUB-GRADE AND PAVEMENT WITHIN THE LIMITS OF THE EXISTING BRIDGE STRUCTURE SHALL BE INCLUDED IN THE COST OF THE PAY ITEM REMOVAL OF EXISTING STRUCTURES. ALL EARTHWORK AND SUB-GRADE REMOVAL NECESSARY TO FACILITATE THE REMOVAL OF THE EXISTING BRIDGE STRUCTURE WHILE MAINTAINING SLOPE STABILITY (1: 1 MINIMUM) SHALL BE INCLUDED IN THE COST OF THE PAY ITEM REMOVAL OF EXISTING STRUCTURES. ALL PAVEMENT REMOVAL IN THESE AREAS WILL BE PAID FOR AS PAVEMENT REMOVAL.

THE LOCATIONS AND/OR DEPTHS OF UNDERGROUND UTILITIES SHOWN HAVE BEEN TAKEN FROM INFORMATION FURNISHED BY THE UTILITY OWNERS AND MUST BE CONSIDERED APPROXIMATE, FIELD MARKINGS OF ACILITIES IN CRITICAL AREAS MAY BE OBTAINED BY PROVIDING A MINIMUM OF 96 HOURS ADVANCE NOTICE THROUGH THE J.U.L.I.E. SYSTEM BY CALLING 800-892-0123.

INDEX OF SHEETS

SHEET NO

TITLE

- COVER SHEET GENERAL NOTES, INDEX OF SHEETS, LIST OF HIGHWAY STANDARDS SUMMARY OF QUANTITIES TYPICAL SECTIONS
- PLAN SHEET 6 TRAFFIC CONTROL PLAN 7-12A. BOX CULVERT DETAILS 13-17 CROSS SECTIONS

THE FOLLOWING STANDARDS ARE A PART OF THESE PLANS AND ARE INCLUDED FOLLOWING THE LAST NUMBERED SHEET OF THE PLANS.

STD. NO.	DESCRIPTION
000001-04	STANDARD SYMBOLS, ABBREVIATIONS AND PATTERNS
001001-01	AREAS OF REINFORCEMENT BARS
001006	DECIMAL OF AN INCH AND OF A FOOT
420001-06	PAVEMENT JOINTS
420101-03	. 24' JOINTED PCC PAVEMENT
515001-02	NAME PLATE FOR BRIDGES
630001-07	STEEL PLATE BEAM GUARDRAIL
630101-07	GUARDRAIL MOUNTED ON EXISTING CULVERTS
630301-04	SHOULDER WIDENING FOR TYPE 1 (SPECIAL) GUARDRAIL TERMINALS
635006-02	REFLECTOR AND TERMINAL MARKER PLACEMENT
635011-01	REFLECTOR MARKER AND MOUNTING DETAILS
701001-01	OFF-RD OPERATIONS, 2L. 2W, MORE THAN 15' AWAY
	OFF-RD OPERATIONS, 2L. 2W, 15' TO 24" FROM PAVEMENT EDGE
	OFF-RD MOVING OPERATIONS, 2L, 2W, DAY ONLY
701301-02	LANE CLOSURE, 2L, 2W, SHORT TIME OPERATIONS
701311-02	LAME CLOSURE 2L, 2W MOVING OPERATIONS-DAY ONLY
702001-06	TRAFFIC CONTROL DEVICES
780001-01	TYPICAL PAVEMENT MARKINGS
781001-02	TYPICAL APPLICATIONS RAISED REFLECTIVE PAVEMENT MARKERS

ILLINOIS DEPARTMENT OF TRANSPORTATION **GENERAL NOTES** AND INDEX OF SHEETS SCALE: VERT.

CHECKED BY

DATE

CONTRACT NO. 74092

S.B.I. RTE.	SECTION		COUNTY		TOTAL SHEETS	SHEET NO.		
15B	15B (17C)B WAYNE		WAYNE		17	3		
STA.	STA. TO STA.							
FED. ROA	D DIST. NO.	LLINOIS	FED.	AID	PROJECT			

	SUMMARY OF QUANTITIES			CONSTRUCTION TYPE CODE			
CODE NO	TOTAL ITEM UNIT QUANTITIES		i -	X028 - ZA			
20200100	EARTH EXCAVATION	CU YD	15	15			
20201200	REMOVAL AND DISPOSAL OF UNSUITABLE MATERIAL	CU YD	100	100			
20400800 20700220 25001000	FURNISHED EXCAVATION POROUS GRANULAR EMBANKMENT SEEDING, CLASS 2 (SPECIAL)	CU YD GU YD ACRE	105 250 0.1	105 250 0.1			
25100630	EROSION CONTROL BLANKET	sa yo	299	299	·		
28000400	PERIMETER EROSION BARRIER	FOOT	386	386	• .		
28100107	STONE RIPRAP, CLASS A4	SQ YD	94	94			
28200200	FILTER FABRIC	SQ YD	142	142			
31101000	SUB-BASE GRANULAR MATERIAL, TYPE B	TON	34	34			
42000500	PORTLAND CEMENT CONCRETE PAVEMENT 10"	SQ YD	139	139			
44000100	PAVEMENT REMOVAL	SQ YD	60	60			
48101200	AGGREGATE SHOULDERS, TYPE B	TON	86	86			
00100100	REMOVAL OF EXISTING STRUCTURES	EACH	1	1			
51500100	NAME PLATES	EACH	1	. 1			
54000900	BOX CULVERT END SECTIONS, SPECIAL	EACH	2	2			
54011009	PRECAST CONCRETE BOX CULVERT 100 X 90	FOOT	62	62			
53000025	STEEL PLATE BEAM GUARD RAIL, ATTACHED TO STRUCTURES	FOOT	50	50			
53100167	TRAFFIC BARRIER TERMINAL TYPE 1, SPECIAL (TANGENT)	EACH	4	4			
53200310	GUARDRAIL REMOVAL	FOOT	164	164			
7000500	ENGINEER'S FIELD OFFICE, TYPE B	CAL MO	4	4			
57100100	MOBILIZATION	L SUM	1	1			
70101800	TRAFFIC CONTROL AND PROTECTION (SPECIAL)	L SUM	1	1			
8001110	PAINT PAVEMENT MARKING - LINE 4"	FOOT	124	124			
8200410	GUARDRAIL MARKERS, TYPE A	EACH	8	8			
8201000	TERMINAL MARKER - DIRECT APPLIED	EACH	4	4			
0054505	ROCK FILL (REPLACEMENT) .	TON	2460	246			
	•						
	•						

ONS TILITAN	DIS DEPARTMENT OF TRANSPORTATION
DATE	JIS DEFARTMENT OF TRANSFORTATION
	SUMMARY
	OF
	QUANTITIES
SCALE: VER	
DATE	CHECKED BY


PLOT DATE = 8/24/2007 FILE NAME = cityrojcota\/4092 PLOT SCALE = 28.0000 // IN. USEN NAME = steffennk

* SPECIALTY ITEMS Rev.


CONTRACT NO. 74092

COUNTY TOTAL SHEETS NO.

WAYNE 17 4 S.B.I. SECTION 15B (17C)B STA. TO STA. FED. ROAD DIST. NO. ILLINOIS FED. AID PROJECT




EXISTING ROADWAY TYPICAL SECTION



PROPOSED TYPICAL SECTION


STA 1010+89.5 TO STA 1011+13.5: *=0'-7'
STA 1011+13.5 TO STA 1011+60 : *=7'
STA 1012+12 TO STA 1012+58.5: *=7'
STA 1012+58.5 TO STA 1012+82.5: *=7'-0'



PROPOSED TYPICAL SECTION

STA 1011+60 TO STA 1011+74 STA 1011+98 TO STA 1012+12

ONCE EXISTING RESURFACING AND PCC PAVEMENT IS REMOVED, PLACE SUB-BASE GRANULAR MATERIAL, TYPE B AS NEEDED TO ALLOW FOR NEW PCC PAVEMENT 10" (2" AVERAGE)



STA 1011+74 TO STA 1011+98

ILLINOIS DEPARTMENT OF TRANSPORTATION

TYPICAL SECTIONS.

SCALE: VERT. HORIZ. DATE

DRAWN BY CHECKED BY

T DATE = 8/24/2007 E NAME = c:\pro.jects\74892d\c T SCALE = 28.0008 // IN. R NAME = steffenmk

COUNTY TOTAL SHEETS NO. SECTION WAYNE 17 5 15B (17C)B STA. TO STA. FED. ROAD DIST. NO. ILLINOIS FED. AID PROJECT

PAVEMENT SCHEDULE

STATION TO STATION	LENGTH	AVERAGE PAVEMENT WIDTH	AREA	SUB-BASE GRANULAR MATERIAL, TYPE B	PCC PAVEMENT 10"	PAVEMENT REMOVAL	AGGREGATE SHOULDERS, TYPE B
	LIN FT	FEET	SQ FT	TON	SQ YD	SQ YD	TON
1010+89,5 TO 1011+13.5 1011+13.5 TO 1011+60.0 1011+60.0 TO 1011+74.0 1011+74.0 TO 1011+98.0 1011+98.0 TO 1012+12.0 1012+12.0 TO 1012+58.5 1012+58.5 TO 1012+82.5	24 47 14 24 14 47 24	18.0 18.0 24.0 24.0 24.0 18.0	48 93 37 64 37 93 48	0.0 0.0 4.3 25.5 4.3 0.0	0.0 0.0 37.3 64.0 37.3 0.0	0.0 0.0 30.0 0.0 30.0 0.0	6. 4 24. 7 4. 3 15. 8 4. 3 24. 7 6. 4
	193			34	139	60	86

GUARDRAIL SCHEDULE

STATION TO STATION	LENGTH	STEEL PLATE BEAM GUARDRAIL, ATTACHED TO STRUCTURES	GUARDRAIL REMOVAL	TRAFFIC BARRIER TERMINAL, TYPE 1 SPECIAL (TANGENT)	GUARDRAIL MARKER, TYPE A	TERMINAL MARKER, DIRECT APPLIED
	LIN FT	F00T	FOOT	EACH	EACH	EACH
1011+23.5 TO 1012+48.5	125	50	164	4	8	4


NOTE(1):

ADJUST DITCH FLOWLINE AS NECESSARY TO ALLOW WATER FLOW AROUND PROPOSED WINGWALLS WHILE STAYING WITHIN R.O.W. THE COST OF THIS WORK WILL BE INCLUDED WITH EARTH EXCAVATION.

EXIST, CURVE CURI
PI STA, = 1013+88.47

\$\triangle = 45^\circ 10' \ 43'' \ (RT) \)
\$D = 42^\circ 40' \ 37'' \)
\$R = 134.26' \)
\$L = 105.86' \)
\$E = 11.16' \)
\$\theta = 6

S.E. RUN = ____ P.C. STA. = 1013+32.61 P.T. STA. = 1014+38.48



LOCAL BENCHMARKS:

STA. 991+60, 36' LT CUT SQUARE IN THE CENTER OF CULVERT HEADWALL NORTH OF THE INTERSECTION OF OLD ROUTE 15 AND IL 15.

12' SOUTH CUT SQUARE ON THE SOUTHWEST WINGWALL OF SN 096-0057 ON OLD ROUTE 15.

STA, 1007+00, 27' LT CUT SQUARE IN THE NORTHEAST CORNER OF CULVERT ON THE NORTHSIDE OF IL 15.

STATION TO STATION	· EARTH EXCAVATION (cut)	EARTH EXC ADJ. FOR SHRINKAGE	(f[])	EARTH BALANCE WASTE (+) OR SHORTAGE (-)
	CU YD	CU YD	CU YD	CU YD
1010+89,5 T0 1011+13.5 1011+13.5 T0 1011+60.0 1011+60.0 T0 1011+74.0 1011+74.0 T0 1011+98.0	2.52 4.88 0.00	1,89 3,66 0,00	0.30 18.41 24.89	1.59 -14.75 -24.89
1011+98.0 TO 1012+12.0	0.00	0.00	26.89	-26.89
1012+12.0 TO 1012+58.5	3, 23	2.42	38.18	-35.75
1012+58.5 TO 1012+82.5 TOTAL =	1. 67 12. 3	1. 25 9. 2	5.44 114.1	-4.19 -104.9
PAY ITEMS: FURNISHED EARTH EXCA	EXCAVATION VATION	105 CU YD 15 CU YD		

PAVEMENT REMOVAL

---- EXISTING GUARDRAIL TO BE REMOVED


PROPOSED GUARDRAIL


ILLINOIS DEPARTMENT OF TRANSPORTATION

PLAN SHEET

SCALE: VERT. HORIZ. DATE

DRAWN BY CHECKED BY





⊥to € Roadway

SHEET NO. SHEET NO. I(17C)B WAYNE 17 6 SHEET

General Notes

Excavation behind abutment walls shall be performed to balance front and back soil pressure before removing

Build tops of headwalls parallel to profile grade. Reinforcement bars shall conform to the requirements of ASTM A706 Gr 60 (IL Modified). See Special Provisions.

The design fill height for the precast boxes is less than 2 feet.

The welded wire fabric extending from the outside face of the vertical walls of the precast box sections shall be 2x3 W4.5 x W4.0 or equivalent. Substitution of reinforcement bar for welded wire fabric is not allowed.

For End Section only, 1^{l_2} " cover unless otherwise noted.

The ends of the the precast box sections adjacent to the end section shall be formed without the male and female shapes specified in Article 8.1 of AASHTO M273. See Section D-D on sheet 4 of 6.

All portions of the precast box culverts in contact with cast-in-place concrete shall be sandblasted according to Article 503,09(b),

The box culvert end section shall be built in the field and a precast option is not allowed except the cut-off wall may be precast. If the contractor elects to use a precast cut-off wall, shop drawings and a proposed construction sequence shall be submitted to the Engineer for approval.

The joints between precast box sections shall be sealed and all void filled with a mastic joint sealer. In addition, the joints shall be externally sealed on all four sides with a 13 inch wide external sealing band. The seal shall be centered over the joint, secured in place and protected during the backfilling process.

TOTAL BILL OF MATERIAL

70771E DIE 01 1111	/ 4-/15/14	
ITEM	UNIT	TOTAL
Removal of Existing Structures	Each	1
Removal and Disposal of Unsuitable Material	Cu. Yd.	100
Rockfill (Replacement)	Ton	246
Precast Concrete Box Culverts 10' x 9'	Foot	62
Box Culvert End Sections (Special)	Each	2
Name Plates	Each	1
Stone Riprap, Class A4	Sq. Yd.	94
Filter Fabric	Sq. Yd.	142
Porous Granular Embankment	Cu, Yd.	250

LOCATION SKETCH

O0


GENERAL PLAN AND ELEVATION DOUBLE 10'x9' PRECAST BOX CULVERT SBI ROUTE 15B - SECTION (17C)B WAYNE COUNTY STATION 1011+86.00 STRUCTURE NO. 096-2009

D. Greifzu

CHECKED S. Ryan

SBI Rt. 15B (17C)B WAYNE

CONTRACT NO. 74092





Limits of Porous Granular Embankment

The limits shall be as shown above or as directed by the Engineer.


The granular material shall be compacted according to Article 205.06, or as directed by the Engineer.

That portion of the PGE outside the aggregate shoulders and behind the end section wingwalls shall be covered with a minimum of 1 foot of cohesive material as directed by the Engineer. Cost included with Porous Granular Embankment.







RIPRAP DETAILS SBI ROUTE 15B - SECTION (17C)B WAYNE COUNTY STATION 1011+86.00 STRUCTURE NO. 096-2009





South end shown, North end similar



D. Greifzu







· v₁ bars INSTALLATION AND SETTING METHODS "A" Set bar splicer assembly by means of a template bolt. "B" Set bar splicer assembly by nailing to wood forms or cementing to steel forms. Mandatory Construction Joint 0 Construction Joint Threaded or Coil Splicer Rods Threaded or Coil Loop Couplers Threaded or Coil Splicer Rods

FOR BOX CULVERT END SECTIONS

1		į.
DESIGNED	D. Greifzu	OCTOBER 10, 2007
CHECKED	S. Ryan	EXAMINED Thomas & Domagalaki)
DRAWN	D. Greifzu	PASSED Ralph E. andersa
CHECKED	S. Ryan	ENGINEER OF BRIDGES AND STRUCTURES
***************************************		•

SHEET NO. 5 ROUTE NO. SECTION SHEETS SHEET NO. SBI R+. (17C)B WAYNE 6 SHEET 17 11

NOTES

CONTRACT NO. 74092

Bar splicer assemblies shall be of an approved type and shall develop in tension at least 125 percent of the yield strength of the lapped reinforcement bars.

Splicer rods shall be of minimum 60 ksi yield strength, threaded or coiled full length.

All reinforcement bars shall be lapped and tied to the splicer rods or dowel bars.

Other systems of similar design may be submitted to the Engineer for approval. Approval shall be based on certified test results from an approved testing laboratory that the proposed bar splicer assembly satisfies the following requirements:

- Minimum Capacity (Tension in kips) = 1.25 x fy x A_t 1
- Tension iii kips)

 Minimum *Pull-out Strength = $0.66 \times fy \times A_f$ (Tension in kips)

Where fy = Yield strength of lapped reinforcement bars in ksi.

- A_t = Tensile stress area of lapped reinforcement bars. * = 28 day concrete

	Bar	· Si	olicer	foi	#5	bar		
Min.	Capacity	=	23.0	kip	s - 1	ensic	n	
Min.	Pull-out	Sti	ength	=	12.3	kips	-	tension
No.	Required	=	36					

BAR SPLICER ASSEMBLY DETAILS SBI ROUTE 15B - SECTION (17C)B WAYNE COUNTY STATION 1011+86.00 STRUCTURE NO. 096-2009

ROUTE NO.	SECTION	cou	NTY	TOTAL SHEETS	SHEET NO.	SHEET NO. 6
SBI R+. 15B	(17C)B	WAYNE		17	12	6 знеет
FED. ROAD DIST	NO. 7	ILLINOIS PED. ATO PROJECT-				

CONTRACT NO. 74092



SOIL BORING LOG

Page <u>1</u> of <u>1</u>

Of Hallope	JITUITUIT		JOIL DONING LO	70	
Division of Highways Illinois Department of Tran	sportation				Date <u>10/14/05</u>
ROUTE SBI 15 B (Old IL 15) DE	ESCRIPTION	Un	-named Stream	LOGGED BY	E. Sandschafer
SECTION (17C)	LOCATION	Sec 6 - SW 1/	4, Sec 7 - NW 1/4, SEC. , TWP. 2	S, RNG. 6 E, 3 PM	
COUNTY Wayne	DRILLING METHOD	Hollow_ste	m auger & split spoon HAMI	WER TYPE	Auto 140#
STRUCT. NO. 096-005 Station 1011+86 BORING NO. 1 Station 1011+64.5 Offset 4.00ff Ri Ground Surface Elev. 41 2" asphall over 7" concrete povement. Wedium, damp, brown to gray, SILTY CLAY.	E L P O T W H S	C 0 5 I S V V V V V V V V V V V V V V V V V V	Stream Bed Elev. Groundwater Elev.: First Encounter Upon Completion	399.24 ft E 398.86 ft P 7 384.7 ft H 384.7 ft (ft) \[\sqrt{389.04} \]	L C 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
Soft, very damp, gray, SILTY LOAM.	402.34 0 0 1	0.3 23	Very dense, moist, brown, CLAY SHALE w/ trace sand. Extent of exploration.	383.54	5 4 11 2.5 K 50 B 34 50/4" 12
3" of wood in sampler, no soil recovery.	-10 I4 -20 I4 -20 I4	102	Benchmark: BM 457 chiseled square on SW wingwall of existing structure = 408.78'	-30	-
No recovery this trip, estimated wood plugging borehole.	394.84	1 1			- - -
Very stiff, damp, red mottled gray, CLAY w/ sand and wood fragments.		1.7 18		-3:	
Very soft, wet, red, SANDY LOAM. Very stiff, damp, brown mottled	392.34 3 7 391.14 6	0.2 19 B			
aray CLAY TILL	1	1 1	H		1 1 1

The Unconfined Compressive Strength (UCS) Follure Mode is indicated by (B-Bulge, S-Shear, P-Penetrometer)
The SPT (N value) is the sum of the last two blow values in each sampling zone (AASHTO T206)

BBS, from 137 (Rev. 8-99)

SOIL BORING LOG

Page <u>1</u> of <u>1</u>

### ROUTE Sell 5 B (Old 11 50 DESCRIPTION	OF FEUTISPO Division of Highways	11 1011011				JUIL DUNING LO	0				
Section County Wagne Oritical Method Sec 6 - SW I/4 Sec 7 - NW I/4 Sec 8 - NW I/4 Sec	Tillnois Department of Trans	portation							Date	10/1	4/05
DOUNTY Wayne DRILLING METHOD Hollow stem auger & split spoon HAMMER TYPE Auto 140 #	ROUTE S <u>BI 15 B (Old IL 15)</u> DE	SCRIPTION			Un	-named Stream	LOGGED	BY	<u>E.</u>	Sandsci	hafer
Strict	SECTION (17C)	LOCATIO	N	Sec 6 -	SW 1/	4, Sec 7 - NW 1/4, SEC. , TWP. 2 S	. RNG. 6 E, 3	PM		×	
Stellan 1011-96	COUNTY Wayne	DRILLING METH	0Đ	Hol	low ste	m auger & split spoon HAMME	R TYPE		Auto	140#	
Stidion			B	111	и			0	B		u
## SOURTHO NO. 2									_		l "
SORING NO. 2	Station 1011+06				-	Stream Bed Elev	8.8611				1
Stition DD2*13.5 H S Qu T First Encounter 374.8 ft H S Qu T First Encounter 374.8 ft H S Qu T First Encounter 385.1 ft H S Qu T T T T T T T T T	0007110 1/0		1 -		-	0			-	"	
Stiff to soft, damp, gray and 404.61 5 2 2 3 1.5 5 5 0.4 17 0.67 0.57 17 0.67 0.57 1.5 0.67 0.57 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0	SURING NU. 2			0,,			740 64			Ou	
Ground Surface Elev. 409.31 ft ft (17) (67) (881) (22) After Hr.S. M/A ft (17) (67) (881) (72)	STOTION 1012+13.5		"	"	ĺ			1 "		""	'
Red marbled gray, SILTY LOAM. 388.81 3 1.3 20			(76")	(tsf)	(7)			(ft)	(/6")	(tef)	100
Confined Confined		9.31 11 111	1707	11011	17.7			111/			l
Silff, damp, brown, SILTY CLAY. Silff, damp, red morbled gray, CLAY. 366.81 5 366.81 5 366.81 5 366.81 5 366.81 5 366.81 5 366.81 5 366.81 5 366.81 11 8 366.81 11 8 366.81 11 8 366.81 11 8 366.81 11 8 366.81 11 8 366.81 11 8 366.81 11 8 366.81 11 8 366.81 11 8 366.81 11 8 366.81 11 8 366.81 11 8 366.81 11 8 366.81 11 8 366.81 11 8 366.81 11 8 366.81 11 8 366.81 11 8 366.81 11 8 366.81 11 8 366.81 11 8 366.81 11 8 366.81 11 8 366.81 11 8 366.81 11 8 366.81 11 8 366.81 11 8 366.81 11 8 366.81 11 8 366.81 11 8 366.81 11 8 366.81 11 8 366.81 11 8 366.81 11 8 366.81 11 8 366.81 11 8 366.81 11 8 366.81 11 8 366.81 11 8 366.81 11 8 366.81 11 8 366.81 11 8 366.81 11 8 366.81 11 8 366.81 11 8 366.81 11 8 366.81 11 8 366.81 11 8 366.81 11 8 366.81 11 8 366.81 11 8 366.81 11 8 366.81 11 8 366.81 11 8 366.81 11 8 366.81 11 8 366.81 11 8 366.81 11 8 366.81 11 8 366.81 11 8 366.81 11 8 366.81 11 8 366.81 11 8 366.81 11 8 366.81 11 8 366.81 11 8 366.81 11 8 366.81 11 8 366.81 11 8 366.81 11 8 366.81 11 8 366.81 11 8 366.81 11 8 366.81 11 8 366.81 11 8 366.81 11 8 366.81 11 8 366.81 11 8 366.81 11 8 366.81 11 8 366.81 11 8 366.81 11 8 366.81 11 8 366.81 11 8 366.81 11 8 366.81 11 8 366.81 11 8 366.81 11 8 366.81 366.81 366.81 366.81 366.81 366.81 366.81 366.81 366.81 366.81 366.81 366.81 366.81 366.81 366.81 366.81 366.81 366.81 366.81 366.81 366.81 366.81 366.81 366.81 366.81 366.81 366.81 366.81 366.81 366.		400 61				Red marbled gray, SILTY LOAM.	388.81				20
CLAY. 386.81 5 5 6 6 6 6 6 6 6 6		700.01							4	B	<u> </u>
3	STIFT, damp, brown, SILIY CLAY.										
3 1.5 24 Brown, SANOSTONE. 386.55 8 1.7 16 18 18 18 18 18 18 18			_			JOEAN.					
4 PP							386.81				
Sitf to soft, damp, gray and rown, SILTY LOAM. 404.61			3	1.5	24	Brown, SANDSTONE.	Λ	r	8	1.7	18
### Authorized Comp. gray and rown, SILTY LOAM. 15			4	PP		Red marbled gray, CLAY,	_386.5#		11	В	
### Author 15 15 15 15 15 15 15 1		_									
### 1945 5 2 5 5 5 5 5 5 5							384 81				ĺ
15 15 15 15 15 15 15 15	Tiff to not dome are and	404.61	2			Hard, very moist, brownish tan,	30 1101		7		
Clay Shale layering.			3	1.5	15	CLAY SHALE w/ some Sandy			19	+4.5	13
17	HOWII, SILIT LUAM.		1	1		Clay Shale layering.					
19 +4.5 19 29 PP 10 29			+	 							
19 +4.5 19 29 PP 10 29			-								
19 +4.5 19 29 PP 19 19 29 PP 19 19 29 PP 19 19 29 PP 19 19 19 19 19 19 1			۱,						17		İ
397.31 4 397.31 4 397.31 4 5 10 23 50/4° 8 5 10 23 50/4° 8 5 10 23 50/4° 8 6 8 6 8 6 8 6 8 6 8 6 8 6 8 6 8 6 8		-	I	1						1.75	ļ
-10 5			1		19						11
### Siland 17 18 18 18 18 18 18 18			0	PP					29	PP	ļ
### Siland 17 18 18 18 18 18 18 18										ĺ	
### Siland 17 18 18 18 18 18 18 18		_									
Solution	-10	5					- 30	16	İ		
### dedium, damp, gray mottled red, 4		******	5	0.4	17				23	+4.5	15
A		_	5	S				_	37	PP	
A			†								
SilTry CLAY.		707 71	1								
SiLTY CLAY.	ledium, damo, arav mottled red.	331.31	4								
6 B -15 3 -35 47 4 0.6 24 5 B Extent of exploration. 2 Benchmark: BM 457 chiseled square on SW wingwall of existing structure = 408.78' 101 A		-	5	10	23						
-15 3 -35 47 -35 47 -35 50/4* 5 B Extent of exploration. 2										ļ	
## 4		_	+ -	1-							
## 4			_							İ	
## 4										l	
5 B 373.51 50/5° Extent of exploration. 2 Benchmark: BM 457 chiseled square on SW wingwall of existing structure = 408.78′ 5 B structure = 408.78′		-15						-35			
Extent of exploration. 2 Benchmark: BM 457 chiseled square on SW wingwall of existing structure = 408,78' 2 CLAY. Extent of exploration. Benchmark: BM 457 chiseled square on SW wingwall of existing structure = 408,78'			1	1	24	1	777 F.				8
391.51 3 1.7 26 square on SW wingwall of existing structure = 408.78'			5	В		Extent of exploration	3/3.51		50/5"	 	
Stiff, damp, red marbled gray, 5 B Square on SW wingwall of existing structure = 408.78'						Extens of exploration.					
Stiff, damp, red marbled gray, 5 B Square on SW wingwall of existing structure = 408.78'			1								1
39.51 3 1.7 26 square on SW wingwall of existing structure = 408.78' SLAY. 389.81			2			Benchmark: BM 457 chiseled]
Stiff, damp, red marbled gray, 5 B structure = 408.78'		391.51	3	1.7	26	square on SW wingwall of existing		-		1	
369.81		**************************************		1 1		structure = 408.78'					
1	LAI.	_	+	1		1					
1		700.01	-								
1ed marbied gray, SILIT LUAM20 1 40	Red marbled grav, SILTY LOAM.		1					-40			1

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by (B-Bulge, S-Shear, P-Penetrometer) The SPT (N value) is the sum of the last two blow values in each sampling zone (AASHTO T206)

BBS, from 137 (Rev. 8-99)

DESIGNED	D. Greifzu
CHECKED	S. Ryan
DRAWN	D. Greifzu
CHECKED	S. Ryan

...\wayne county soldier bile final ii.dgn 10/10/2007 9:12:33 AM

	UCTUBER 10, 2007
EXAMIN	mas & Dimagalaku
PASSED	Ralph E. anderson
	ENGINEER OF BRIDGES AND STRUCTURES

BORING LOGS

SBI ROUTE 15B - SECTION (17C)B


WAYNE COUNTY


STATION 1011+86.00

STRUCTURE NO. 096-2009

ROUTE NO.	SECTION	COUNTY		TOTAL SHEETS	SHEET NO.
SBI Rt. 15B	(17C)B	WAYNE		17	12a
FED. ROAD DIST	ST. NO. 7 ILLINOIS FED. AND PRO		OJECT-		

CONTRACT NO. 74092





DESIGNED D. Greifzu

CHECKED S. Ryan

DRAWN D. Greifzu

CHECKED S. Ryan

CHECKED S. Ryan

CHECKED S. Ryan

CHECKED S. Ryan

...\wayne county soldier pile final ii.dgn 40/10/2007 9:29:3

EXISTING PLANS

SBI ROUTE 15B - SECTION (17C)B

WAYNE COUNTY

STATION 1011+86.00

STRUCTURE NO. 096-2009

