STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION

| HOUTE NO. | • • • • • • • • • • • • • • • • • • • | OOUMTY | | TOTAL | #原7 |
|------------------------|---------------------------------------|---------|----------------|-------|-----|
| FAP 686 | 1141-1 | JACKSON | | 12 | 4 |
| PIID, ROAD CHIT, NO. 7 | | ALIPONE | PRO AD PROMET- | | |

CONTRACT NO. 78019

BITUMINOUS MIX DESIGN

| LOCATION: | HOT-MIX ASPHALT SURFACE COURSE |
|---|--|
| MIXTURE USE(S): | HOT-MIX ASPHALT SURFACE COURSE, MIX C, N90 |
| AC/PG: | PG64-22 |
| RAP % (MAX): | 10 |
| DESIGN AIR VOIDS: | 4.0%, 90 GYRATION DESIGN |
| MIXTURE COMPOSITION: (GRADATION MIXTURE) | IL - 9.5 mm or IL 12.5 mm |
| FRICTION AGGREGATE: | C SURFACE |

| LOCATION: | HOT-MIX ASPHALT SHOULDERS | |
|---|---------------------------|--|
| MIXTURE USE(S): | HOT-MIX ASPHALT SHOULDERS | |
| AC/PG: | PG58-22 | |
| RAP % (MAX): | 50 | |
| DESIGN AIR VOIDS: | 2.0%, 30 GYRATION DESIGN | |
| MIXTURE COMPOSITION: (GRADATION MIXTURE) | HMA Shoulders | |
| FRICTION AGGREGATE: | NONE | |

PAINT PAVEMENT MARKING - LINE 4"

| COLOR | QUANTITY (FOOT) |
|--------|--------------------|
| YELLOW | 1911 |
| WHITE | 642 |
| TOTAL | 2653 |