FAP	SECTION	COUNTY VERMILION		TOTAL SHEETS	SHEET NO.	
729	34Z~4			285	3	
FED. ROAD DIST, NO.		ILLINOIS	FED.	AID PRO	DJECT	

GN 105.04
THE METRIC DIMENSIONS AND SPECIFICATIONS GIVEN HEREIN ARE INTENDED TO MEET METRIC DESIGN CRITERIA. HOWEVER, THE EXISTING FACILITIES WERE CONSTRUCTED USING ENGLISH DIMENSIONS. WHERE THE METRIC DIMENSIONS DIFFER FROM THE PHYSICAL DIMENSIONS OF THE EXISTING FACILITIES TO REMAIN IN PLACE, THE EXISTING DIMENSIONS SHALL CONTROL. (FOR EXAMPLE, PAVEMENT WIDTH FOR RESURFACING.) THE EXISTING DIMENSIONS HAVE BEEN ACCOUNTED FOR IN THE PLAN QUANTITIES.

G.N.-105.07
EXISTING STATE-OWNED AND MAINTAINED UTILITY LINES ARE SHOWN ON THE PLANS
TO INDICATE THEIR PRESENCE AND APPROXIMATE LOCATION. THE CONTRACTOR SHALL
NOTIFY THE DISTRICT OPERATIONS ENGINEER TWO WEEKS PRIOR TO COMMENCING ANY
EXCAVATION IN THE VICINITY OF THESE LINES. THE STATE WILL THEN LOCATE AND
MARK THE HORIZONTAL LOCATIONS OF THE LINES AND PROVIDE ANY AVAILABLE
INFORMATION AS TO THEIR DEPTH. SHOULD ANY OF THE LINES BE DAMAGED BY THE
CONTRACTOR'S OPERATION, THE CONTRACTOR SHALL REPAIR THEM TO THE
SATISFACTION OF THE ENGINEER AND AT NO COST TO THE STATE.

ALSO THERE MAY BE UTILITIES PRESENT WHICH WERE INSTALLED BY THE STATE BUT ARE MAINTAINED BY OTHERS (CITY, TOWN, ETC.) THE APPROXIMATE LOCATIONS OF THESE LINES ARE ALSO SHOWN ON THE PLANS ALONG WITH THE NAME OF THE MAINTAINIG AGENCY. THE CONTRACTOR SHALL COORDINATE THE LOCATING OF THESE LINES WITH THE LOCAL AGENCY PRIOR TO COMMENCING ANY EXCAVATION OR BORING INTHEIR VICINITY. SHOULD THESE LINES BE DAMAGED BY THE CONTRACTOR'S OPERATIONS, THE CONTRACTOR SHALL REPAIR THEM TO THE SATISFACTION OF, AND AT NO COST TO, THE LOCAL AGENCY AND THE STATE.

G.N.-105.09 ALL ELEVATIONS SHOWN IN THE PLANS ARE ABASED ON U.S.G.S MEAN SEA LEVEL DATUM.

G. N. -107. 12 THE NAME, ADDRESS, AND TELEPHONE NUMBER OF THE LOCAL RAILROAD CONTACT IS:

MR. LUCIOUS G. BOBBITT
ASSISTANT DIVISION ENGINEER
NORFOLK SOUTHERN RAILWAY COMPANY
1735 EAST CONDIT STREET
DECATUR, IL 62521
217-425-2037

SPECIAL ATTENTION IS CALLED TO ARTICLE 107.12 REGARDING RAILROAD FLAGGERS. THE NAME, ADDRESS, AND TELEPHONE NUMBER OF THE RAILROAD CONTACT PERSON FOR FLAGGERS IS:

MR. KEN MICHAEL NORFOLK SOUTHERN RAILWAY COMPANY P.O. BOX 242 SIDNEY, IL 61877 217-425-2130 G.N.-107.31
UTILITY LINES WERE PLOTTED FROM INFORMATION FURNISHED BY THE VARIOUS
UTILITY COMPANIES INVOLVED (QUALITY LEVEL C &/OR QUALITY LEVEL D) AND THE
ACCURACY SHOULD BE CONSIDERED APPROXIMATE ONLY.

UTLILITY COMPANIES MAY BE ADJUSTING THEIR FACILITIES DURING CONSTRUCTION. THE CONTRACTOR SHALL COOPERATE WITH THESE ORGANIZATIONS WHILE THESE ADJUSTMENTS ARE BEING PERFORMED. J.U.L.I.E. - JOINT UTILITY LOCATION INFORMATION FOR EXCAVATORS SYSTEM (800) 892-0123.

G.N.-202
GRADING SHALL BE DONE BY HAND AROUND LIGHT POLES, UTILITY POLES, SIGN POSTS, SHRUBS, TREES OR OTHER NATURAL OR MAN-MADE OBJECTS WHERE SHALLOW FILLS OR CUTS ARE ADJACENT TO THE ITEMS. IT IS THE INTENT THAT THE LIMITS OF CONSTRUCTION BE SUCH AS TO PRESERVE IN THE ORIGINAL STATE AS MUCH AREA OF TEMPORARY EASEMENTS AS POSSIBLE. THE DECISION AS TO ITEMS TO REMAIN IN PLACE SHALL BE AS DIRECTED BY THE ENGINEER.

THIS WORK WILL NOT BE PAID FOR SEPARATELY, BUT SHALL BE CONSIDERED INCLUDED IN THE CONTRACT UNIT PRICE PER CUBIC YARD FOR EARTH EXCAVATION AND NO ADDITIONAL COMPENSATION WILL BE ALLOWED.

G. N. -250A

THE FOLLOWING APPLICATION RATES HAVE BEEN USED TO CALCULATE THE VARIOUS ITEMS NECESSARY FOR SEEDING AND SODDING.

FERTILIZER NUTRIENTS RATE (SODDING)
NITROGEN 225 KG/HA (200 LBS/ACRE)
PHOSPHOROUS 225 KG/HA (200 LBS/ACRE)
POTASSIUM 225 KG/HA (200 LBS/ACRE)
SUPPLEMENTAL WATERING 30 L/SQ METER (10 GAL/SQ YD)
1 UNIT = 1000 L

G.N.-281
THE RIPRAP GRADATION SHALL BE IN ACCORDANCE WITH THE GRADATION SPECIFIED IN THE PLANS OR, WITH APPROVAL OF THE ENGINEER, A RIPRAP GRADATION MEETING A D50 GREATER THAN OR EQUAL TO 150 mm (0.5 FEET). D50 IS DEFINED AS THE MEAN ROCK SIZE AS DESCRIBED IN THE FHWA HYDRAULIC ENGINEERING CIRCULARS (HEC 11, HEC 14 AND HEC 15).

IF GRAVEL IS USED FOR THE BEDDING MATERIAL UNDER RIPRAP, THE GRAVEL SHALL BE CRUSHED AS ALLOWED UNDER ARTICLE 1005.01.

G.N.-353
THE SHADED AREAS OF P.C. CONCRETE BASE COURSE CONSTRUCTED ADJACENT TO COMBINATION CONCRETE CURB AND GUTTER AS SHOWN IN THE PLANS SHALL BE POURED MONOLITHIC WITH THE COMBINATION CONCRETE CURB AND GUTTER. THIS WORK WILL BE MEASURED AND INCLUDED IN THE CONTRACT UNIT PRICE PER SQUARE YARD FOR PORTLAND CEMENT CONCRETE BASE COURSE OF THE THICKNESS SPECIFIED IN THE PLANS AND NO ADDITIONAL COMPENSATION WILL BE ALLOWED.