INDEX OF SHEETS

1. TITLE SHEET
2. INDEX OF SHEETS
   APPLICABLE STATE STANDARDS
3. SUMMARY OF QUANTITIES
   SCHEDULE OF CLEANING STARTING DATES
4. EXPRESSWAY TYPICAL SECTIONS
5. EXPRESSWAY CLEANING
6. TRAFFIC CONTROL DETAILS FOR FREEWAY SHOULDER CLOSURES AND PARTIAL RAMP CLOSURES

STATE STANDARDS

701101-02 OFF-ROAD OPERATIONS, MULTILANE, 15' TO 24" FORM PAVEMENT EDGE
701426-04 LANE CLOSURE, MULTILANE INTERMITTENT OR MOVING OPERATION FOR SPEEDS >45 MPH
701901-01 TRAFFIC CONTROL DEVICES

GENERAL NOTES

FOR ALL MOVING OPERATIONS ON EITHER THE SHOULDER OR WHEN A LANE IS CLOSED, VEHICLES SHALL BE EQUIPED WITH TRUCK/TRAILER MOUNTED ATTENUATOR AND ARROW BOARD AS SHOWN IN DETAIL C OF HIGHWAY STANDARD 701426. WHILE OPERATIONS ARE ENTIRELY ON THE SHOULDER, ARROW BOARDS SHALL BE IN WARNING MODE (NO ARROW SHOWING).

TRUCK MOUNTED ATTENUATORS ARE REQUIRED ON ALL CLEANING OPERATIONS.

WHEN WITHIN THE INNER CITY THE TWO FOLLOW VEHICLES SHALL HAVE A TRUCK MOUNTED ATTENUATOR.

WHEN THE SHOULDER DOES NOT EXIST, OR IS NARROW, FOLLOWING VEHICLES SHOWN ON THE SHOULDER SHALL RIDE AS CLOSE TO THE EDGE OF THE TRAVELLED WAY AS PRACTICAL AND THE SPACING TO THE NEXT VEHICLE REDUCED TO APPROXIMATELY 150m (500 FT).

WATER TRUCKS USED TO CONTROL DUST PROPAGATION ARE ALLOWED TO OPERATE BY THEMSELVES. THEY SHALL AVOID SUDDEN STOPS.

ALL VEHICLES SHALL HAVE HEADLIGHTS AND EMERGENCY FLASHERS OPERATING AND SHALL DISPLAY AN AMBER COLORED OSCILLATING, ROTATING OR FLASHING LIGHT(S). AT LEAST ONE AMBER LIGHT IS TO BE VISIBLE FROM ANY DIRECTION.

ALL SWEEPERS, WATER TRUCKS AND FOLLOW VEHICLES SHALL HAVE ARROW BOARDS, AND APPROPRIATE SIGNS.

LONGITUDINAL DISTANCES MAY BE ADJUSTED TO FIT FIELD CONDITIONS. THE LATERAL PLACEMENT OF THE FLAGGER MAY BE VARIED FROM THAT SHOWN ON THE STANDARD.