



- LEGEND**
- WORK ZONE
  - DRUM WITH STEADY BURNING MONODIRECTIONAL LIGHT AT 50' C-C SPACING (20' ON LANE TAPER)
  - TYPE III BARRICADE WITH FLASHING LIGHTS. QUANTITY AS REQUIRED FOR PROPER CLOSURE TO SATISFACTION OF THE ENGINEER
  - SIGN ON PORTABLE OR PERMANENT SUPPORT
  - SIGN WITH FLASHING LIGHT
  - IMPACT ATTENUATORS, TEMPORARY (NON-REDIRECTIVE) TEST LEVEL 2. NOTE: NARROW REQUIRED.
  - ARROW BOARD
  - CHANGEABLE MESSAGE SIGN

- NOTES:**
1. REFER TO STANDARD 701606 FOR ADDITIONAL SIGNS AND DEVICES NOT SHOWN.
  2. REFER TO STANDARD 701801 FOR SIDEWALK CLOSURES.

FILE NAME = D264882-shr-staging9.dgn	USER NAME = dwozniarski	DESIGNED -	REVISED -
		DRAWN -	REVISED -
		CHECKED -	REVISED -
		DATE - 2-22-2010	REVISED -

**STATE OF ILLINOIS  
DEPARTMENT OF TRANSPORTATION**

**IL 40  
MAINTENANCE OF TRAFFIC - PRE-STAGE**

SCALE: 1" = 20'    SHEET NO. 9 OF 35 SHEETS    STA. 717+00 TO STA. 724+00

F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
646	IB-2	WHITESIDE	257	36
CONTRACT NO. 64B80				
FED. ROAD DIST. NO.    ILLINOIS FED. AID PROJECT				