


- LEGEND**
- WORK ZONE
 - DRUM WITH STEADY BURNING MONODIRECTIONAL LIGHT AT 50' C-C SPACING (20' ON LANE TAPER)
 - TYPE III BARRICADE WITH FLASHING LIGHTS. QUANTITY AS REQUIRED FOR PROPER CLOSURE TO SATISFACTION OF THE ENGINEER
 - SIGN ON PORTABLE OR PERMANENT SUPPORT
 - SIGN WITH FLASHING LIGHT
 - IMPACT ATTENUATORS, TEMPORARY (NON-REDIRECTIVE), TEST LEVEL 2. NOTE: NARROW REQUIRED.
 - ARROW BOARD
 - CHANGEABLE MESSAGE SIGN

- NOTES:**
- REFER TO STANDARD 701606 AND DISTRICT STANDARD 94.2 FOR ADDITIONAL SIGNS AND DEVICES NOT SHOWN.
 - HMA SURFACE REMOVAL, HMA BINDER AND HMA SURFACE COURSE WILL BE COMPLETED WITH TEMPORARY LANE CLOSURES USING STANDARD 701601. FINAL PAVEMENT MARKINGS WILL BE COMPLETED WITH TEMPORARY LANE CLOSURES USING STANDARD 701427.



FILE NAME = D264880-shr-staging2.dgn	USER NAME = dwozniarski	DESIGNED -	REVISED -
		DRAWN -	REVISED -
		CHECKED -	REVISED -
		DATE - 2-22-2010	REVISED -

**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**

IL 40 MAINTENANCE OF TRAFFIC - STAGE 3			
SCALE: 20'	SHEET NO. 29 OF 35 SHEETS	STA. 714+00	TO STA. 716+00

F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
646	1B-2	WHITESIDE	257	56
FED. ROAD DIST. NO. ILLINOIS FED. AID PROJECT			CONTRACT NO. 64B80	