



TYPICAL SECTION

STA. 291+20 TO STA. 322+95
 STA. 328+67 TO STA. 331+05

LEGEND

- ① EX PCC PAVEMENT, 9"
- ② EX HOT-MIX ASPHALT OVERLAY, 2 1/4"
- ③ PR HOT-MIX ASPHALT REMOVAL, 1 1/2"
- ④ PR HOT-MIX ASPHALT SURFACE COURSE, 1 1/2"
- ⑤ PR HOT-MIX ASPHALT SHOULDER, 6 1/2"
- ⑥ PR PAVEMENT MARKING
- ⑦ PR GUTTER REMOVAL

*NOTE: When the superelevation rate of the pavement is between 0% and 4%, the shoulder shall be sloped at 4%. When the superelevation rate of the pavement exceeds 4%, the shoulder shall be sloped so that the algebraic difference between pavement and shoulder will not be greater than 8%.

FILE NAME =	USER NAME = sparksgw	DESIGNED -	REVISED -	STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION	TYPICAL SECTIONS			F.A.S. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.		
ei:\pw\work\p\idot\sparksgw\02222050\0672084-sht-typical.dgn		DRAWN -	REVISED -		SCALE:	SHEET NO.	OF SHEETS	STA.	TO STA.	1610	22RS-10	SCOTT	42	8
		CHECKED -	REVISED -		CONTRACT NO. 72084									
		DATE -	REVISED -		ILLINOIS FED. AID PROJECT									